

1 LOCATION OF WATER WELL: County: <u>Sedgwick</u> Fraction <u>SW</u> <u>1/4</u> <u>NW</u> <u>1/4</u> Section Number <u>36</u> Township Number <u>T 27 S</u> Range Number <u>R 3</u> <u>EW</u>
--

Distance and direction from nearest town or city street address of well if located within city?

2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :	<u>See Below</u> <u>Tim Classen</u> <u>1950 So 231st West</u> <u>Ottawa KS 67052</u>	Board of Agriculture, Division of Water Resources Application Number:
---	---	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: <u>63</u> ft. ELEVATION: <u>38</u> ft.
--	---

Depth(s) Groundwater Encountered 1. 38 ft. 2. 30 ft. 3. 25 ft.

WELL'S STATIC WATER LEVEL 22 ft. below land surface measured on mo/day/yr 2-25-88

Pump test data: Well water was 30 ft. after 2 hours pumping 20 gpm

Est. Yield 50 gpm: Well water was 30 ft. after 2 hours pumping 20 gpm

Bore Hole Diameter 11 in. to 03 ft., and 03 in. to 03 ft.

WELL WATER TO BE USED AS:

1 Domestic	3 Feedlot	6 Oil field water supply	9 Dewatering	12 Other (Specify below)
2 Irrigation	4 Industrial	7 Lawn and garden only	10 Observation well	

Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <u>X</u> Clamped
------------------------------	----------------	-----------------	---------------------------------------

1 Steel

2 PVC

Blank casing diameter 5 in. to 43 ft. Dia. 12 in. weight 1.59 lbs./ft. Wall thickness or gauge No. 50L-26

Casing height above land surface 12 in.

3 RMP (SR)

4 ABS

7 Fiberglass

8 RMP (SR)

9 ABS

TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement
1 Steel	3 Stainless steel	5 Fiberglass
2 Brass	4 Galvanized steel	6 Concrete tile
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut
1 Continuous slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	7 Torch cut	10 Other (specify)
3 Mill slot		11 None (open hole)
4 Key punched		
SCREEN-PERFORATED INTERVALS:	From <u>43</u> ft. to <u>63</u> ft.	From <u>43</u> ft. to <u>63</u> ft.
GRAVEL PACK INTERVALS:	From <u>22</u> ft. to <u>63</u> ft.	From <u>22</u> ft. to <u>63</u> ft.

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
-------------------	---------------	----------------	-------------	---------

Grout Intervals: From 3 ft. to 22 ft. From 22 ft. to 63 ft. From 63 ft. to 63 ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	

Direction from well? NE How many feet? 70

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	Top soil			
2	38	clay			
38	48	fine to med sand			
48	63	red & green shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>2-25-88</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>318</u> This Water Well Record was completed on (mo/day/yr) <u>2-29-88</u> by (signature) <u>W. J. J. J.</u> under the business name of <u>W. J. J. J.</u>
--

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4