

1 LOCATION OF WATER WELL: County: Sedgwick		Section Number 31	Township Number 27	Range Number 3
Distance and direction from nearest town or city street address of well if located within city? See Below				
2 WATER WELL OWNER: DARREN BOGNER RR#, St. Address, Box #: 2062 Koeings Dr. City, State, ZIP Code: GARDEN PLAIN, KS 67050				
Board of Agriculture, Division of Water Resources Application Number:				
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 60 ft. ELEVATION: 9-32-94 ft.		
		Depth(s) Groundwater Encountered: 23 ft. 2. 20 ft. 3. 20 ft. WELL'S STATIC WATER LEVEL: 23 ft. below land surface measured on mo/day/yr Pump test data: Well water was 20 ft. after 1/2 hours pumping gpm Est. Yield: 20 gpm Well water was 20 ft. after 1/2 hours pumping gpm Bore Hole Diameter: 11 in. to 60 ft. and 60 in. to 60 ft. WELL WATER TO BE USED AS: ☒ 1 Domestic ☐ 3 Feedlot ☐ 6 Oil field water supply ☐ 9 Dewatering ☐ 12 Other (Specify below) ☐ 2 Irrigation ☐ 4 Industrial ☐ 7 Lawn and garden only ☐ 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes ☐ No ☒ If yes, mo/day/yr sample was submitted X Water Well Disinfected? Yes ☒ No ☐		
5 TYPE OF BLANK CASING USED:				
1 Steel ☒ 2 PVC ☒ 3 RMP (SR) ☐ 4 ABS ☐ 5 Wrought iron ☐ 6 Asbestos-Cement ☐ 7 Fiberglass ☐ 8 Concrete tile ☐ 9 Other (specify below) ☐ 10 Asbestos-cement ☐ 11 Other (specify) ☐ 12 None used (open hole) Blank casing diameter: 5 in. to 60 ft. Dia. 2.60 in. to 60 ft. Dia. 160 PSI ft. Casing height above land surface: 12 in. weight 2.60 lbs./ft. Wall thickness or gauge No. 160 PSI TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel ☐ 2 Brass ☐ 3 Stainless steel ☐ 4 Galvanized steel ☐ 5 Fiberglass ☐ 6 Concrete tile ☐ 7 PVC ☒ 8 RMP (SR) ☐ 9 ABS ☐ 10 Asbestos-cement ☐ 11 Other (specify) ☐ 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot ☐ 2 Louvered shutter ☐ 3 Mill slot ☒ 4 Key punched ☐ 5 Gauzed wrapped ☐ 6 Wire wrapped ☐ 7 Torch cut ☐ 8 Saw cut ☐ 9 Drilled holes ☐ 10 Other (specify) ☐ 11 None (open hole) SCREEN-PERFORATED INTERVALS: From 40 ft. to 60 ft. From 60 ft. to 60 ft. From 60 ft. to 60 ft. GRAVEL PACK INTERVALS: From 23 ft. to 60 ft. From 60 ft. to 60 ft. From 60 ft. to 60 ft.				
6 GROUT MATERIAL: 3 Neat cement 23 2 Cement grout 3 Bentonite 4 Other				
Grout intervals: From 3 ft. to 23 ft. From 23 ft. to 60 ft. From 60 ft. to 60 ft. From 60 ft. to 60 ft.				
What is the nearest source of possible contamination: 1 Septic tank ☐ 2 Sewer lines ☐ 3 Watertight sewer lines ☐ 4 Lateral lines ☒ 5 Cess pool ☐ 6 Seepage pit ☐ 7 Pit privy ☐ 8 Sewage lagoon ☐ 9 Feedyard ☐ 10 Livestock pens ☐ 11 Fuel storage ☐ 12 Fertilizer storage ☐ 13 Insecticide storage ☐ 14 Abandoned water well ☐ 15 Oil well/Gas well ☐ 16 Other (specify below) ☐ Direction from well? North How many feet? 80				
FROM		TO		LITHOLOGIC LOG
0		2		Top Soil
2		21		Sand
21		23		Clay
23		30		Sand
30		38		clay
38		47		Sand
47		60		Shale
FROM		TO		PLUGGING INTERVALS
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ (1) constructed, ☐ (2) reconstructed, or ☐ (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-3-94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 10-4-94 under the business name of Weninger Drilling by (signature) Karina Morrissey				
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.				

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4