

1 LOCATION OF WATER WELL: Fraction SE 1/4 SW 1/4 NE 1/4 Section Number 31 Township Number T 27 S Range Number R 3 E
 County: SEDWICK
 Distance and direction from nearest town or city street address of well if located within city?

308 N. MAIN

2 WATER WELL OWNER: FARMER'S COOPERATIVE

RR#, St. Address, Box #: 401 N MAIN

City, State, ZIP Code: GARDEN PLAIN, KS 67050

Board of Agriculture, Division of Water Resources

Application Number: NA

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL: 15.7 ft. ELEVATION: 1441.55 TOG

Depth(s) Groundwater Encountered: 1. 10 ft. 2. 10 ft. 3. 10 ft.

WELL'S STATIC WATER LEVEL: 9.56 ft. below land surface measured on mo/day/yr 3-1-94

Pump test data: Well water was 10 ft. after 10 hours pumping gpm

Est. Yield gpm Well water was 15.7 ft. after 10 hours pumping gpm

Bore Hole Diameter: 7 7/8 in. to 15.7 ft. and 15.7 in. to 15.7 ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well MW 4

Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:

5 Wrought iron

8 Concrete tile

CASING JOINTS: Glued Clamped

1 Steel

3 RMP (SR)

6 Asbestos-Cement

9 Other (specify below)

Welded

2 PVC

4 ABS

7 Fiberglass

Threaded X

Blank casing diameter: 2 in. to 5.2 ft. Dia 5.2 in. to 5.2 ft. Dia 5.2 in. to 5.2 ft. Dia 5.2 in. to 5.2 ft. Dia

Casing height above land surface: -6 in. weight 40 lbs./ft. Wall thickness or gauge No. Sch 40

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel

3 Stainless steel

5 Fiberglass

7 PVC

10 Asbestos-cement

2 Brass

4 Galvanized steel

6 Concrete tile

8 RMP (SR)

11 Other (specify)

9 ABS

12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot

3 Mill slot

5 Gauzed wrapped

8 Saw cut

11 None (open hole)

2 Louvered shutter

4 Key punched

6 Wire wrapped

9 Drilled holes

7 Torch cut

10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 5.2 ft. to 15.2 ft. From 5.2 ft. to 15.2 ft. From 5.2 ft. to 15.2 ft. From 5.2 ft. to 15.2 ft.

GRAVEL PACK INTERVALS: From 4.6 ft. to 15.7 ft. From 4.6 ft. to 15.7 ft. From 4.6 ft. to 15.7 ft. From 4.6 ft. to 15.7 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 1.0 ft. to 2.6 ft. From 2.6 ft. to 4.6 ft. From 4.6 ft. to 4.6 ft. From 4.6 ft. to 4.6 ft.

What is the nearest source of possible contamination:

1 Septic tank

4 Lateral lines

7 Pit privy

10 Livestock pens

14 Abandoned water well

2 Sewer lines

5 Cess pool

8 Sewage lagoon

11 Fuel storage

15 Oil well/Gas well

3 Watertight sewer lines 6 Seepage pit

9 Feedyard

12 Fertilizer storage

16 Other (specify below)

13 Insecticide storage

LEAKED LUST LINE

Direction from well?

How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	4	CLAY, black, SANDY, fine grained, round, 10-15%, w/SILT			
4	5	CLAY, orange, SANDY, fine to medium grained, well sorted, round, w/SILT. Sand increases w/depth.			
5	8	CLAY, orange, w/SAND			
8	15.7	SAND, gray, fine to medium grained, well sorted, round to subround. Wet at 10			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2/23/94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 483 This Water Well Record was completed on (mo/day/year) 3-11-94 under the business name of TEST by (signature) [Signature]