

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Gray		NE ¼ SW ¼ SE ¼	1	T 27 S	R 30 E (W)

Distance and direction from nearest town or city street address of well if located within city?

From South Side of Ingalls, 1½ Miles SW, 6 Miles South, 4 Miles West, 1,260 Ft. North & 1,380 Ft. West

2	WATER WELL OWNER:	DeeWayne Koehn	West
	RR#, St. Address, Box # :	Route 1 - Box 131	Board of Agriculture, Division of Water Resources
	City, State, ZIP Code :	Brookston, Texas 75421	Application Number: 9,162 & 9,994

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 4 DEPTH OF COMPLETED WELL: 265 ft. ELEVATION:

Depth(s) Groundwater Encountered 1. 147 ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL 147 ft. below land surface measured on mo/day/yr 6-6-96

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter 30 in. to 265 ft., and in. to ft.

WELL WATER TO BE USED AS:

5 Public water supply	8 Air conditioning	11 Injection well
1 Domestic	3 Feedlot	6 Oil field water supply
2 Irrigation	4 Industrial	7 Lawn and garden only
		9 Dewatering
		12 Other (Specify below)
		10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED:		5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
① Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)	Welded
2 PVC	4 ABS	7 Fiberglass	from 180 ft.	Threaded

Blank casing diameter . . . 16 . . . in. to . . . 150 . . . ft. Dia . . . 16 . . . in. to . . . 190 . . . ft. . . . in. to . . . ft.
Casing height above land surface . . . 12 . . . in. weight . . . 42.05 . . . lbs./ft. Wall thickness or gauge No. . . 250

TYPE OF SCREEN OR PERFORATION MATERIAL:			7 PVC	10 Asbestos-cement
① Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)	11 Other (specify)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS	12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	
		7 Torch cut	10 Other (specify)	

SCREEN-PERFORATED INTERVALS:		From 150	ft. to 180	ft., From 190	ft. to 265	ft.
		From	ft. to	ft., From	ft. to	ft.
GRAVEL PACK INTERVALS:		From 20	ft. to 265	ft., From	ft. to	ft.
		From	ft. to	ft., From	ft. to	ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
Grout Intervals: From 0 ft. to 20 ft. From ft. to ft. From ft. to ft.

What is the nearest source of possible contamination:			10 Livestock pens	14 Abandoned water well
1 Septic tank	4 Lateral lines	7 Pit privy	11 Fuel storage	15 Oil well/Gas well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	16 Other (specify below)
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage	N/A
Direction from well?			How many feet?	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
		See attached log			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-6-96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 208. This Water Well Record was completed on (mo/day/yr) 6-10-96 under the business name of Minter-Wilson Drilling Co., Inc. by (signature) *Nora Keller*