


1 LOCATION OF WATER WELL:	Fraction 1/4	Near Center E½ XX E½ XX	Section Number 13	Township Number T 27 S	Range Number R 30 E/W
---------------------------	-----------------	----------------------------	----------------------	---------------------------	--------------------------

County: Gray Distance and direction from nearest town or city street address of well if located within city?

From NE corner of Montezuma - 6½ Miles North, 6 Miles West, 2640 ft. North and 675 ft. West

2 WATER WELL OWNER:	Paul Yost Box 323 Montezuma, Kansas 67867	Board of Agriculture, Division of Water Resources Application Number: 20,695
---------------------	---	---

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL..... 310 ft. ELEVATION: .....
--	---



Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL 128 ft. below land surface measured on mo/day/yr 10-9-91

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter 30 in. to 310 ft., and in. to ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No XX If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No XX

5 TYPE OF BLANK CASING USED:	5 Wrought iron 1 Steel 3 RMP (SR)	8 Concrete tile 6 Asbestos-Cement	CASING JOINTS: Glued..... Clamped.....
------------------------------	--------------------------------------	--------------------------------------	--

2 PVC 4 ABS 7 Fiberglass from 210 ft. to 300 ft.

Blank casing diameter 18 in. to 160 ft. Dia 18 in. to 250 ft. Dia 18 in. to 310 ft.

Casing height above land surface 12 in. weight 47.39 lbs./ft. Wall thickness or gauge No. 250

TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC 1 Steel 3 Stainless steel	10 Asbestos-cement 2 Brass 4 Galvanized steel
---	------------------------------------	--

5 Fiberglass 8 RMP (SR)  
6 Concrete tile 9 ABS

SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped 1 Continuous slot 3 Mill slot	8 Saw cut 9 Drilled holes
-------------------------------------	---	------------------------------

6 Wire wrapped 10 Other (specify)  
2 Louvered shutter 4 Key punched 7 Torch cut

SCREEN-PERFORATED INTERVALS:	From 160 ft. to 210 ft.	From 250 ft. to 300 ft.
------------------------------	-------------------------	-------------------------

From ft. to ft. From ft. to ft. From ft. to ft.

GRAVEL PACK INTERVALS:	From 20 ft. to 310 ft.	From ft. to ft.
------------------------	------------------------	-----------------

From ft. to ft. From ft. to ft.

6 GROUT MATERIAL:	1 Neat cement Grout Intervals: From 0 ft. to 20 ft.	2 Cement grout From ft. to ft.	3 Bentonite 4 Other
-------------------	--	-----------------------------------	------------------------

5 Pit privy 10 Livestock pens 14 Abandoned water well  
6 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well  
7 Feedyard 12 Fertilizer storage 16 Other (specify below)

8 Feedyard 13 Insecticide storage

9 Feedyard How many feet? 150

Direction from well? West

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
------	----	----------------	------	----	--------------------

See attached log

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-9-91 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 208 This Water Well Record was completed on (mo/day/yr) 10-31-91 under the business name of Minter-Wilson Drilling Co., Inc. by (signature) Nora Keller
---