USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD KSA 82a-1201-1215

ı									
J	ш				 				
	T	-	3	EW	sec	1/4	1/4	1/4	No.
					- 50	٠, ٠	., .	., .	

Kansas State Dept. Of Health (Water Well Contractors) Forbes–Bldg. 740 Topeka, Kansas 66620

Location of well Haskell Lockport Pivot SEM 2 T 27 S R 31 W			T	l r		٠			1	1.
Locale with "X" in section below: A Well depth: 230 ft. Date of completion A Well depth: 250 ft. Date A Well depth: 250 ft.	1 Location of well:	Haskell	Lockport	Pivot S	1 /4	ı			Town number T 27 S	Range number R 31 W
Well distincted Store Driver Dog Inclusive Dog Inclusive Dog Inclusive Dog Inclusive Dog Driver Dog Inclusive Dog Driver Dog Inclusive Dog Driver Dr	Distance and directi at Sublet Street address of we	te, Ks., 17 no	y: from Jct. 8 orth, 10% eas	3 & 56 t			Ľa			67846
	Locate with "X" in		Sketch map:					4 We	II depth: 230 ft. D	ate of completion 4-4-
7 Cosing: MotorioSteel_Height days News Threaded Welded Sources St. Mr. 1. 10 in. to 23 th. depth force show of the state	w	1							Hollow rod Jetted Domestic Public Irrigation Air co	Bored Reverse rotary supply Industry
Screen: Manufacturer Johnson Division Johnson		- 1						Thi Dia	sing: Materia Steel H readed Welded X S am. Loin. to <u>23</u> 1t. depth D	urface 36.87 in.
Manufacturer Johnson Division Type Galv. Dio 16	2	Тур	e and color of material		ļ	From	То	8 5 4		
Slortpases V Length 201								Mo Tyr	anufacturer <u>Johnso</u> pe <u>Galv.</u> D	ia16"
9 Static water level:								Slo Set	t between 200 ft. and 200 st.	ength 20' 110 ft. 215-225 0-215-225-230
10 Pumping level below land surfaces: 90 ft. ofter 2 hrs. pumping 1110 g.p.m.								9 Sta	itic water level:	
11 Water sample submitted: Yes No Date 12 Well head completion: Pitless adapter								10 Pui	mping level below land surf 96 ft. after 2 hrs. 106ft. after 4 hrs.	pumping 663 g.p.m. pumping 1110g.p.m.
12 Well head completion: Pitless adapter 12 Inches above grade	0.00							11 W	iter sample submitted:	
Near cemen Bentonite Depth: From ft. to ft.								12 We	Il head completion:	-
ftDirectionType								K	Neat cement Bentonij	- 40
15 Pump: Not installed C Manufacturer's name Peerless-FMC Model number 4006 HP 100 Volts Length of drop pipe 140 ft. capacity 600 g.m.p.								14 Ne	earest source of possible cor	ntamination: N/A
Model number										
Type: Submersible Turbine								Mo	odel number 4606	700 Volts
(use a second sheet if needed) Certrifugal Other								Ту	pe:	_
Good well. Customer satisfied. This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Topography: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Minter-Wilson Drilling. 208 Business metay 493 Garden Cityense Rs.		(use	a second sheet if needed)						:	
Fields surrounging well. Topography: Hill Fields surrounging well. Business many 493 Garden Citypus Ks.	16 Remarks: elevat	Good well	l. Customer	satisfie	d.					
Upland Authorized representative	☐ Hill X Slope	Fields s	urroun g ing we	11.				rep Mint Bus Ad	cer-Wilson Dri iness name 493 Ga	rden Citigns Rs

Forward the white, blue and pink copies to the Kansas State Dept. Of Health.

Form WWC-5

The Professionals - MINTER-WILSON DRILLING CO

Irrigation and Domestic Water Systems
Complete Installation and Repairing

Phone 276-8269 • P.O. Box 493 • GARDEN CITY, KANSAS 67846

Haskell County

Ed Hesser

March 18, 1975

S & sec. 2 T. 27 R.31 Static later Level 96 Test 1 Pivot

Location: 11 miles South of Pierceville, 's Fast, 's North is est

O 2 Top Soil

2 34 Bron Clay

34 80 Fine to Medium Sana & Gravel (Loose) streaks of Coarse Gravel

80 97 Brown Clay

97 125 Fine to Medium Sand & Gravel 10% Clay (Loose)

125 137 Brown Sandy Clay

137 170 Fine to Medium Sand & Gravel (Loose)

170 192 Bro n Sandy Clay

192 200 Fine to Medium Sand & Gravel 10% Clay (Loose)

200 210 Fine to Medium Sand & Gravel (Loose)

210 215 Broom Sandy Clay

215 230 Fine to Medium Sand & Gravel 10% Clay (lbose)

230 302 Brown Sancy Clay

302 320 Brown Sanay Clay, streaks of Fine to Medium Sana & Fine Gravel 305

TD 230' Screen 20'