


1 LOCATION OF WATER WELL: County: Haskell Fraction: SE 1/4 SW 1/4 SW 1/4 Section Number: 32 Township Number: T 27 S Range Number: R 31 E/W

Distance and direction from nearest town or city street address of well if located within city?

12 North, 7/4 East of Sublette, Kansas

2 WATER WELL OWNER: Mr. Wilbur Yost
 RR#, St. Address, Box #: R.R. 1, Box 57
 City, State, ZIP Code: Copeland, Kansas 67837
 Board of Agriculture, Division of Water Resources
 Application Number: ---

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: X



4 DEPTH OF COMPLETED WELL: 332 ft. ELEVATION: Upland

Depth(s) Groundwater Encountered: 1. Not available ft. 3. --- ft.
 WELL'S STATIC WATER LEVEL: .192 ft. below land surface measured on mo/day/yr August 3, 1983
 Pump test data: Well water was --- ft. after --- hours pumping --- gpm
 Est. Yield 30-40 gpm: Well water was --- ft. after --- hours pumping --- gpm
 Bore Hole Diameter: 9.7/8 in. to 332 ft., and --- in. to --- ft.
 WELL WATER TO BE USED AS:
 Domestic Feedlot Oil field water supply Dewatering Injection well
 Irrigation Industrial Lawn and garden only Observation well
 Was a chemical/bacteriological sample submitted to Department? Yes --- No XX; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes XXX No ---

5 TYPE OF BLANK CASING USED:
 Steel RMP (SR) Asbestos-Cement Other (specify below) PVC ABS Fiberglass
 Casing diameter: 5 in. to 272 ft., Dia. --- in. to --- ft., Dia. --- in. to --- ft.
 Casing height above land surface: 12 in., weight 2.8 lbs./ft. Wall thickness or gauge No. 265
 CASING JOINTS: Glued XX Clamped --- Welded --- Threaded ---

TYPE OF SCREEN OR PERFORATION MATERIAL:
 Steel Stainless steel Fiberglass RMP (SR) Asbestos-cement
 Brass Galvanized steel Concrete tile ABS Other (specify) ---
 2 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:
 Continuous slot Mill slot Gauzed wrapped Saw cut None (open hole)
 Louvered shutter Key punched Wire wrapped Drilled holes
 Torch cut Other (specify) ---

SCREEN-PERFORATED INTERVALS: From 272 ft. to 332 ft., From --- ft. to --- ft.
 GRAVEL PACK INTERVALS: From 14 ft. to 332 ft., From --- ft. to --- ft.

6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other ---
 Grout Intervals: From 4 ft. to 14 ft., From --- ft. to --- ft., From --- ft. to --- ft.

What is the nearest source of possible contamination:
 Septic tank Lateral lines Pit privy Livestock pens Abandoned water well
 Sewer lines Cess pool Sewage lagoon Fuel storage Oil well/Gas well
 Watertight sewer lines Seepage pit Feedyard Fertilizer storage Other (specify below) ---
 Insecticide storage ---

Direction from well? Southwest How many feet? 50

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	10	Topsoil			
10	105	Fine to Med. Sand w/Clay Streaks			
105	150	Gravel			
150	278	Med. to Lar. Sand			
278	305	Blue Clay			
305	335	Med. To Lar. Sand			
335	340	Blue Clay			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) August 10, 1983 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 252 This Water Well Record was completed on (mo/day/year) August 11, 1983 under the business name of Friesen Windmill & Supply Inc. by (signature) [Signature]

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY
 T 27 R 31
 SEC. 32
 SE 1/4 SW 1/4 SW 1/4