

1	LOCATION OF WATER WELL: County: Haskell	Fraction SE ¼ SE ¼ NE ¼	Section Number 25	Township Number T 27 S	Range Number R 31 E/W
---	---	-----------------------------------	-----------------------------	----------------------------------	---------------------------------

Distance and direction from nearest town or city street address of well if located within city?

1/2 Mile North, 1 Mile West & 1 1/4 mile North of Copeland

2	WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :	Peter Giesbrecht 347 YY Road Copeland, Kansas 67837	Board of Agriculture, Division of Water Resources Application Number:
---	---	--	--

3	LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4	DEPTH OF COMPLETED WELL 390 ft. ELEVATION:
---	--	---	---

Depth(s) Groundwater Encountered 1**270**..... ft. 2**312**..... ft. 3**360**..... ft.
 WELL'S STATIC WATER LEVEL**242**..... ft. below land surface measured on mo/day/yr**7-15-07**.....
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield**1.0**..... gpm: Well water was ft. after hours pumping gpm
 WELL WATER TO BE USED AS:
 1 Domestic 2 Irrigation 3 Feedlot 4 Industrial 5 Public water supply 6 Oil field water supply 7 Domestic (lawn & garden) 8 Air conditioning 9 Dewatering 10 Monitoring well 11 Injection well 12 Other (Specify below)

Was a chemical/bacteriological sample submitted to Department? Yes No ...**X**.....; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes **X** No

5	TYPE OF BLANK CASING USED: 1 Steel 2 PVC Blank casing diameter 5 in. to 0-250 ft., Dia 5 in. to 270-350 ft., Dia in. to ft. Casing height above land surface 1.2 in., weight lbs./ft. Wall thickness or gauge No. SDR 26	5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below) CASING JOINTS: Glued X Clamped Welded Threaded
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 2 Brass SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Louvered shutter		3 Stainless Steel 4 Galvanized Steel 5 Fiberglass 6 Concrete tile 7 PVC 8 RMP (SR) 9 ABS 10 Asbestos-Cement 11 Other (Specify) 12 None used (open hole)
SCREEN-PERFORATED INTERVALS: From 250-270 ft. to 350-390 ft., From ft. to ft. GRAVEL PACK INTERVALS: From 20 ft. to 390 ft., From ft. to ft.		8 Saw cut 9 Drilled holes 10 Other (specify) ft. 11 None (open hole)

6	GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
Grout Intervals: From 0 ft. to 12 ft., From ft. to ft., From ft. to ft.	
What is the nearest source of possible contamination: 1 Septic tank 2 Sewer lines 3 Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Seepage pit 7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)	
Direction from well? How many feet?	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	15	Topsoil & clay	312	315	Sand
15	98	Clay & fine sand	315	330	Fine sand with clay
98	105	Sand	330	345	Clay & little lime
105	156	Sand & gravel	345	360	Sand (little fine)
156	208	Sand	360	370	Sand (turn coarse)
208	210	Coarse Gravel	370	375	Cemented sand & sand (coarse)
210	218	Clay & little lime	375	388	Sandstone & little clay
218	225	Sand	388	390	Sand
225	240	Clay & little lime			
240	255	Sand & clay & cemented sand			
255	270	Clay & sand & cemented sand			
270	279	Sand with clay & cemented sand			
279	285	Clay & little sand			
285	312	Clay & little lime			

7	CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-15-07 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 223 This Water Well Record was completed on (mo/day/yr) 7-30-07 under the business name of Dunham Drilling Inc. by (signature) Karen Dunham
---	---