

County: Haskell Fraction SW SW SW Sec. 23 T 27 S R 31 E (W)

CORRECTION(S) TO WATER WELL COMPLETION RECORD (WWC-5)

(to rectify lacking or incorrect information)

Owner: Clayton Unru

Location was listed as:

Section-Township-Range: 23-27S-31W

Fraction ($\frac{1}{4}$ $\frac{1}{4}$ $\frac{1}{4}$): None Given

Location changed to:

23-27S-31W

SW SW SW

Other changes: Initial statements: _____

Changed to: _____

Comments: _____

Verification method: Written & legal descriptions, and mapping tool & aerial photos on KGS website.

initials: DRF date: 10/30/2013

Submitted by: Kansas Geological Survey, Data Resources Library, 1930 Constant Ave., Lawrence, KS 66047-3726
to: Kansas Dept of Health & Environment, Bureau of Water, 1000 SW Jackson, Suite 420, Topeka, KS 66612-1367.

WATER WELL RECORD

Form WWC-5

Division of Water Resources App. No.

1 LOCATION OF WATER WELL: County: HASKELL CO KS	Fraction ¼ ¼ ¼ ¼	Section Number 23	Township No. T 27 S	Range Number R 31 <input type="checkbox"/> E <input checked="" type="checkbox"/> W
Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here <input type="checkbox"/> . Sublette, Ks: hwy 83&56 N 12 m to rd 70, E 10 M. rd ww, 2 N rd 50, E 1/10 to 1st House, N		Global Positioning System (GPS) information: Latitude: (in decimal degrees) Longitude: (in decimal degrees) Elevation: Datum: <input type="checkbox"/> WGS 84, <input type="checkbox"/> NAD 83, <input type="checkbox"/> NAD 27 Collection Method: <input type="checkbox"/> GPS unit (Make/Model:) <input type="checkbox"/> Digital Map/Photo, <input type="checkbox"/> Topographic Map, <input type="checkbox"/> Land Survey Est. Accuracy: <input type="checkbox"/> <3 m, <input type="checkbox"/> 3-5 m, <input type="checkbox"/> 5-15 m, <input type="checkbox"/> >15 m		
2 WATER WELL OWNER: UNRU, CLAYTON RR#, Street Address, Box #: 247 TT RD City, State, ZIP Code : COPELAND KS 67837				

3 LOCATE WELL WITH AN "X" IN SECTION BOX: N <table style="width:100%; text-align: center; border-collapse: collapse;"> <tr> <td style="border: 1px solid black; padding: 5px;">NW</td> <td style="border: 1px solid black; padding: 5px;">NE</td> </tr> <tr> <td style="border: 1px solid black; padding: 5px;">SW</td> <td style="border: 1px solid black; padding: 5px;">SE</td> </tr> </table> <p style="text-align: center;">S -----1 mile----- </p>	NW	NE	SW	SE	4 DEPTH OF COMPLETED WELL 400 ft. Depth(s) Groundwater Encountered (1) 265 ft. (2) ft. (3) ft. WELL'S STATIC WATER LEVEL 265 ft. below land surface measured on mo/day/yr. 8-13-13 Pump test data: Well water was 294 ft. after 1 hours pumping 70 gpm EST. YIELD 70 gpm. Well water was ft. after hours pumping gpm Bore Hole Diameter 9.75 in. to 400 ft., and in. to ft. WELL WATER TO BE USED AS: <input type="checkbox"/> Public water supply <input type="checkbox"/> Geothermal <input type="checkbox"/> Injection well <input checked="" type="checkbox"/> Domestic <input type="checkbox"/> Feedlot <input type="checkbox"/> Oil field water supply <input type="checkbox"/> Dewatering <input type="checkbox"/> Other (Specify below) <input type="checkbox"/> Irrigation <input type="checkbox"/> Industrial <input type="checkbox"/> Domestic-lawn & garden <input type="checkbox"/> Monitoring well Was a chemical/bacteriological sample submitted to Department? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If yes, mo/day/yr sample was submitted Water well disinfected? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No
NW	NE				
SW	SE				

5 TYPE OF CASING USED: Steel PVC Other
CASING JOINTS: Glued Clamped Welded Threaded
 Casing diameter .5" in. to 400 ft., Diameter in. to ft., Diameter in. to ft.
 Casing height above land surface 24 in., Weight 3.706 lbs./ft., Wall thickness or gauge No. SDR 21-316
TYPE OF SCREEN OR PERFORATION MATERIAL:
 Steel Stainless Steel PVC Other (Specify)
 Brass Galvanized Steel None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:
 Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)
 Louvered shutter Key punched Wire wrapped Saw cut Other (specify)
SCREEN-PERFORATED INTERVALS: From 280 ft. to 320 ft., From ft. to ft.
 From 340 ft. to 400 ft., From ft. to ft.
GRAVEL PACK INTERVALS: From 160 ft. to 400 ft., From ft. to ft.
 From ft. to ft., From ft. to ft.

6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other
 Grout Intervals: From 1 ft. to 25 ft., From ft. to ft., From ft. to ft.
 What is the nearest source of possible contamination:
 Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (specify below)
 Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well
 Watertight sewer lines Seepage pit Feedyard Fertilizer storage Oil well/gas well
 Direction from well Distance from well

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHO. LOG (cont.) or PLUGGING INTERVALS
0	3	SURFACE	399	400	CLAY "BLACK"
3	100	CLAY			
100	120	SAND			
120	140	GRAVEL			
140	160	SAND/CLAY STREAKS			
160	249	SAND			
249	310	SAND/CLAY STREAKS			
310	355	CLAY			
355	372	SANDY CLAY			
372	399	SANDSTONE			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo/day/year) 8-13-13 and this record is true to the best of my knowledge and belief.
 Kansas Water Well Contractor's License No. 430 This Water Well Record was completed on (mo/day/year) 8-13-13
 under the business name of Howard Dilg Co Box 806 Beaver Ok 73932 by (signature)

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send one copy to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.
 Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at <http://www.kdheks.gov/waterwell/index.html>