USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

| 1. Location of well: | County | Fraction | | Section number | Township number | Range number |
|--|----------------|--|----------------|----------------|--|---|
| | Haskell County | 1/4 1/4 NI | 3 1/4 | 1 | T 27 S. s | R 32 🛼 E/W |
| 2. Distance and direction from nearest town or city: 2 miles South, of Channel 11, 6 miles East, 2 South Street address of well location if in city: 3. Owner of well: Gen R.R. or street: Sou City, state, zip code: Gen | | | | | ene Heiman outh Star Route Garden City, Kans | as 67846 |
| 4. Locate with "X" | | Sketch map: | <u> </u> | | 6. Bore hole dia. <u>26</u> in Well depth 450 ft. | . Completion date 8.30. 78 |
| NW | X | | | | 7 Cable tool Rotary | |
| W 1 1 | E E | | | | | ublic supply Industry ir conditioning Stock il field water Other |
| sw | SE I | | | | 9. Casing: Material Stee Threaded Welded | |
| 1 M | | | | | Dia 16 in. to 450 ft. der | oth Wall Thickness: inches or |
| . Type and color of | material | tive to the second seco | | From To | Dia in. to ft. dep 10. Screen: Manufacturer's | |
| | | | | | Type Johnson Gal | r.Di100 - 16" |
| | | | | | Slot/gauze 0-275 P1 | 11mgth 275-450 Port. |
| | | | | | Set between Screen. | |
| | | | | | 11. Static water level: 117 ft. below land su | mo./day/yr. |
| | | - | | | 12. Pumping level below lan | |
| | | | | | 153_ ft. after _4_ | hrs. pumping 825 g.p.m. hrs. pumping 1500 g.p.m. |
| | | | | | 13. Water sample submitted: | g.p.m. mo./day/yr. |
| | | | | | 14. Well head completion: | Date |
| | | | | | 15. Well grouted? YSS | 1 ft Inches above grade |
| | | | | | With: Neat cement Depth: From ft. to | Bentonite X Concrete |
| | | | | | 16. Nearest source of possibl | |
| | | | | | Well disinfected upon comple | etion? Yes No |
| | | | | | 17. Pump: Manufacturer's name | Not installed 1d - 5 stg. 12" |
| | | | | | Model number Length of drop pipe 220 | HP 125 Volts |
| | | | | | Type:Submersible | X Turbine |
| | (Use a second | sheet if needed) | | | Jet Centrifugal | Reciprocating Other |
| 8. Elevation: | 19. Remarks: | 20. Water well contractor's This well was drilled under m | certification: | | | |
| opography: | | | | | is true to the best of my know Minter-Wilson D | rledge and belief. |
| X Hill | | | | | Business name | License No. |
| Slope Upland | | | | | Address Signed | Le Kenn Dat 9-20-00 |
| Valley | | | | | Authorized rep | resentative |

Professionals MINTER-WILSON DRILLING CO.

Water System opiete Installation and Repairing

Phone 276-8269 . P.O. Box A . GARDEN CITY, KANSAS 67846

GENE HEIMAN HASKELL COUNTY 3-30-78

Location: NE 1-27-32 2 miles south of channel 11, 6 miles east, & south

| 0 | 1 | Top soil |
|-----|-----|---|
| 1 | 37 | Brown clay |
| 37 | 50 | Fine to med. sand and gravel 15% clay (Loose) |
| 50 | 89 | Med. to coarse gravel (Loose) |
| 89 | 101 | Brown clay |
| 101 | 128 | Fine to med. sand and gravel (Loose) streaks |
| | | of coarse gravel |
| 128 | 160 | Brown clay |
| 160 | 199 | Fine to med. sand and gravel (Loose) |
| 199 | 215 | Brown clay |
| 215 | 244 | Blue clay |
| 244 | 255 | Fine to med. sand and gravel 15% clay (Loose) |
| 255 | 275 | Blue clay |
| 275 | 322 | Fine to med. sand and gravel (Loose) |
| 322 | 338 | Brown sandy clay |
| 338 | 344 | Fine to med. sand and gravel (Loose) |
| 344 | 350 | Brown clay |
| 350 | 365 | Fine to med. sand and gravel 35% clay (Loose) |
| 365 | 371 | Fine to med. sand and gravel 10% clay (Loose) |
| 371 | 395 | Brown clay |
| 395 | 403 | Fine to med. sand and gravel 10% clay (Loose) |
| 403 | 430 | Brown clay |
| 430 | 448 | Fine to med. sand and gravel 10% clay (Loose) |
| 448 | 455 | Brown gray and yellow clay (Hard) |
| | | |