

1 LOCATION OF WATER WELL:		Fraction Near Center		Section Number		Township Number		Range Number			
County: Haskell		1/4 1/4 SE 1/4		9		T 27 S		R 32 EW			
Distance and direction from nearest town or city street address of well if located within city?											
From Hwy. 56 & 83 West of Sublette - 16 Miles North, 3 Miles East, 1360 Ft. North & 1270 Ft. West											
2 WATER WELL OWNER:		Valor, Inc. c/o John Koehn									
RR#, St. Address, Box # :		HCR 1, Box 54				Board of Agriculture, Division of Water Resources					
City, State, ZIP Code :		Sublette, Kansas 67877				Application Number: 20439					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 400 ft. ELEVATION:									
		Depth(s) Groundwater Encountered 1. 106 ft. 2. ft. 3. ft.									
		WELL'S STATIC WATER LEVEL 106 ft. below land surface measured on mo/day/yr 9-28-89									
		Pump test data: Well water was ft. after hours pumping gpm									
		Est. Yield gpm: Well water was ft. after hours pumping gpm									
		Bore Hole Diameter 30 in. to 400 ft., and in. to ft.									
5 TYPE OF BLANK CASING USED:		5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded X 2 PVC 4 ABS 7 Fiberglass Threaded. Blank casing diameter 16 in. to 250 ft., Dia. 42.05 in. to ft., Dia. in. to ft. Casing height above land surface 12 in., weight lbs./ft. Wall thickness or gauge No. 250									
TYPE OF SCREEN OR PERFORATION MATERIAL:		1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 6 Wire wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 7 Torch cut 9 Drilled holes SCREEN-PERFORATED INTERVALS: From 250 ft. to 400 ft., From ft. to ft. GRAVEL PACK INTERVALS: From 20 ft. to 400 ft., From ft. to ft.									
6 GROUT MATERIAL:		1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 0 ft. to 20 ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? West How many feet? 80									
FROM		TO		LITHOLOGIC LOG		FROM		TO		PLUGGING INTERVALS	
				See attached log							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-29-89 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 208 This Water Well Record was completed on (mo/day/yr) 12-27-89 under the business name of Minter-Wilson Drilling Co., Inc. by (signature) Nora Keller											

The Professionals

MINTER-WILSON DRILLING CO.

INCORPORATED

Irrigation
and Domestic
Water Systems
Complete Installation
and Repairing

Phone 276-8269 • P.O. Box A • GARDEN CITY, KANSAS 67846

Valor, Inc. - John Koehn
Haskell County
4-7-89

Location: SE $\frac{1}{4}$ 9-27-32
From George Town - 3 E., $\frac{1}{4}$ N., $\frac{1}{4}$ W. &
65' E. of old well

Static Water Level - 150'

Test #1

0	5	Top soil
5	27	Brown clay
27	56	Fine sand
56	92	Fine to medium sand & gravel - loose
92	104	Brown clay
104	193	Fine to medium sand & gravel - streak of clay loose
193	202	Yellow gray clay
202	230	Blue gray clay
230	254	Blue clay
254	312	Fine to medium sand & gravel - loose
312	333	Brown sandy clay & small strip of gravel from 314 to 316
333	340	Fine to medium sand & gravel - loose
340	348	Brown sandy clay
348	361	Brown sandy clay - white rock mixed
361	369	Fine sand - loose
369	380	Brown sandy clay
380	394	Fine sand - loose
394	410	Brown sandy clay
410	425	Yellow clay - brown rock mixed
425	455	Blue shale - hard pull down