WATER WELL RECORD		Form WV	VC-5	Division of Water Resources App. No.				
1 LOCATION OF WATER WELL: County: HASKELL		Fraction	1/, NF 1/,	Section Num	nber	Township No. T 27 S	Range Number R 32	
County: HASKELL 1/4 SE 1/4 NE 1/4 NE 1/4 Street/Rural Address of Well Location, if unknown, distance & direction					Global Positioning System (GPS) information:			
from nearest town or intersection: If at owner's address, check here					Latitude: (in decimal degrees)			
JCT 83 & 56 SW OF SUBLETTE-15 MILES NORTH, 1 MILE				Longitude: (in decimal degrees)				
EAST, 4,059 FT NORTH & 30 FT WEST					Elevation:			
2 WATER WELL OWNER: ROBERT & CONNIE NIGHTENGALE					Datum: WGS 84, NAD 83, NAD 27 Collection Method:			
RR#, Street Address, Box #: 2225 - 50TH ROAD					GPS unit (Make/Model:)			
City, State, ZIP Code : COPELAND, KANSAS 67837				☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey Est. Accuracy: ☐ <3 m, ☐ 3-5 m, ☐ 5-15 m, ☐ >15 m				
3 LOCATE WELL		,		Est. Accuracy	<u>γ</u> :	3 m, <u>3-5 m</u> , <u></u>	5-15 m,	
WITH AN "X" IN 4 D	EPTH OF	COMPLETED WELI	485		ft.			
SECTION BOX: Dep	X: Depth(s) Groundwater Encountered (1) ft. (2) ft. (3) ft.							
N WE	WELL'S STATIC WATER LEVELft. below land surface measured on mo/day/yr							
	Pump test data: Well water was							
UNWNE - X EST. YIELD								
W E Bore Hole Diameter 39								
ew en Domestic Feedlot Oil field water supply Dewatering Other (Specify below)								
✓ Irrigation □ Industrial □ Domestic-lawn & garden □ Monitoring well								
Was a chemical/bacteriological sample submitted to Department? Yes V No								
S If yes, mo/day/yr sample was submitted 1 mile Water well disinfected? Yes No								
5 TYPE OF CASING USED: ✓ Steel □ PVC □ Other CASING JOINTS: □ Glued □ Clamped ✓ Welded □ Threaded								
Casing diameter 16 in to 260 ft., Diameter in to ft., Diameter in to ft.								
Casing height above land surface. 12 in., Weight 42.05 lbs./ft., Wall thickness or gauge No250								
TYPE OF SCREEN OR PERFORATION MATERIAL:								
✓ Steel ☐ Stainless Steel ☐ PVC ☐ Other (Specify)								
☐ Brass ☐ Galvanized Steel ☐ None used (open hole) SCREEN OR PERFORATION OPENINGS ARE:								
☐ Continuous slot								
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)								
SCREEN-PERFORATED INTERVALS: From								
GRAVEL PACK INTERVALS: From 20 ft. to 485 ft., From ft. to ft.								
From								
6 GROUT MATERIAL: ☐ Neat cement								
Grout Intervals: From ft. to ft., From ft. to ft., From ft. ft. ft. ft. ft. ft. ft.								
What is the nearest source of possible contamination: Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (specify below)								
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well								
Watertight sewer lines	Seepage	pit 🗌 Feedyard	Fertilizer s	torage [_] Oil from well10	l well/ga			
Direction from well SOUTEROM TO	LITHOLOG	PICLOG	FROM				UGGING INTERVALS	
rrow 10	LITTOLOG	JIC LOG	TROW	10 111	110. 1.	00 (cont.) <u>or</u> 1 E.	OGGING INTERVIES	
		,						
SEE ATTA	CHED LOC	}						
					ata ta Ata Ata Ata Ata Ata Ata Ata Ata A			
					·····			
AND THE PROPERTY OF THE PROPER		ye., dankarahanna						
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ✓ constructed, ☐ reconstructed, or ☐ plugged								
under my jurisdiction and was completed on (mo/day/year) .3-21-11 and this record is true to the best of my knowledge and belief.								
Kansas Water Well Contractor's License No. 208 This Water Well Record was completed on (mo/day/year) 3-22-11								
under the business name of MINTER-WILSON DRILLING CO., INC. by (signature) Mara Keller								
(white, blue, pink) to Kansas Depar	tment of Healt	h and Environment, Bureau	of Water, Geol	ogy Section, 1000	00 SW Ja	ackson St., Suite 420	, Topeka, Kansas 66612-1367.	
Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell/index.html.								
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy								

27,460

The Irrigation and Domestic Water Systems Professionals Winter-Wilson Drilling Co. Water Systems Complete Installation and Repairing

and Repairing

INCORPORATED

GARDEN CITY, KANSAS 67846 P.O. Box A • Phone 620-276-8269

NAME

BOB NIGHTENGALE

COUNTY

HASKELL

DATE

3-26-09

LOCATION:

NE 1/4 18-27-32 - FROM GEORGETOWN - 1 MILE EAST

& 1/4 OF A MILE SOUTH

- APPROX. 100 FT. NORTH OF EXISTING WELL

STATIC WATER LEVEL -

TEST #1

0' TO 35' - TOP SOIL & SANDY CLAY

35' TO 135' - SAND & GRAVEL - MEDIUM TO COARSE

135' TO 143' - BROWN CLAY

143' TO 170' - SAND & GRAVEL - MEDIUM TO COARSE

170' TO 183' - BROWN CLAY

183' TO 197' - GRAY CLAY

197' TO 240' - BLUE CLAY & CALICHE STREAKS

240' TO 260' - BLUE SAND, MEDIUM TO COARSE & A LITTLE CLAY

260' TO 320' - SAND, MEDIUM TO COARSE & SMALL GRAVEL

320' TO 380' - SAND, MEDIUM TO COARSE & SMALL GRAVEL & A LITTLE CLAY

380' TO 400' - SAND, MEDIUM TO COARSE & SMALL GRAVEL-20% CLAY

400' TO 460' - SANDY CLAY

460' TO 480' - SANDY CLAY & 5' MEDIUM SAND

480' TO 494' - SANDY CLAY

494' TO 496' - GRAY ROCK - VERY HARD

496' TO 500' - GRAY CLAY

500' TO 520' - SHALE