USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

| | County | Paction | | Section n | umber | Township number | Range number | |
|--|----------------|-------------|-------|--|-------|--|---|------------------|
| 1. Location of well: | Haskell County | 1/45/11/4 1 | ₩ 1/4 | 6 | | T 27 | 33 R | |
| 2. Distance and direction from nearest town or city: 6 West, 3 South, 2 South, 2 West of TV 11 Street address of well location if in city: | | | | 3. Owner of well: R.R. or street: City, state, zip code: | | Fern Batchelder 1706 B Garden City, KS 67846 | | |
| . Locate with "X" i | | Sketch map: | | | | 6. Bore hole dia 364 in Well depth 364 ft. | n. Completion date 4= | 29-79 |
| - X NW | - | | | | | 7 Cable tool Rotary Hollow rod Jettec | y DrivenDug | |
| W ! | E | | | | | Lawn (| Air conditioning Stoc Oil field water Oth | k er |
| | | | | | | 9. Casing: Material Ste Threaded Welded _ X RMP PVC | Surface 1 ft. Weight 36.87 | in. lbs./ft. |
| i. Type and color of material | | | | From | То | Dia 16 in. to 364ft. de | p 3-3- 1 to 1 | 9 or |
| | | | | | | 10. Screen: Manufacturer's Type Johnson Gal | | |
| | | | | | | Slot/gauz 0-180 Pla Set between 230-260 280-300 Screen | inen180-230 P | erf. O Perf |
| | | | | | | Gravel pack? | ange of material 2 to | 5/8 day/yr. |
| | | | | | | 139 ft. below land so | nd surfaces | |
| | | | | | | 153 ft. after 2 156 ft. after 4 Estimated maximum yield — | hrs. pumping 1200 1500 | g.p.m. g.p.m. |
| | | | | | | 13. Water sample submitted: | mo./ | day/yr. |
| | | | | | | 14. Well head completion: Pitless adapter | Inches above g | rade |
| | | | 4 | | | 15. Well grouted? | Bentonite X Co | oncrete - |
| | | | | | | 16. Nearest source of possible ft Direction Well disinfected upon comp | N/A Type | No |
| | | | | | | 17. Pump: Manufacturer's name Gons | Not installed | JHC B |
| | | | | | | Model number Length of drop pipe 220_ Type: | HP 125 Volts ft . capacit 1000 s | |
| | 4. | | | | | Submersible Jet | X Turbine Reciproc | ating |
| (Use a second sheet if needed) 19. Remarks: | | | | | | Centrifugal 20. Water well contractor's This well was drilled under | certification: | eport 0 |
| pography: | | | | | | is true to the best of my known Minter Wilson | owledge and belief. Drilling Co. | 208 ≤ |
| Hill Slope Upland | | | | | c | Business name Address Box A. Ga: | rien City, K | 5 6 8 2 2/2 |
| Valley | | | | | | Authorized re | epresentotive | 7//\\$ |

SON DRILLING CO. Complete histallation and Repairing

INCORPORATED

· 我们的自然的现在分词是有关的事情。

irrigation and Domestic

P.O. Box A . GARDEN CITY, KANSAS 67846 Phone 276-8269 March 1, 1979

Fern Batchelder Hackell County

Location: NWt 6-27-33 Offset 300' West of Pivot

Static Water Level - 140

Test M

5.50

| 1 194 | | |
|-------------|-------------|---|
| و ا | 18 | Tep Soil and the second |
| 18 | 62 | Brown Clay |
| 62 | 96 | Med. coarse gravel (loose) |
| 96 | 123 | Coarse gravel (loose) |
| 123 | 135 | Fine to med. sand and gravel (loose) |
| 135 | 167 | Med. coarse gravel |
| 167 | 173 | Brown Sandy Clay |
| 173 | 198 | Fine to med. sand and gravel streak of med coarse gravel (loose) |
| 198 | 21 7 | Brown Sandy Clay |
| 217 | 228 | Fine to med. sand and gravel 10% Clay |
| 228 | 254 | Yellow Gray Black Clay |
| 254 | 261 | Blue Clay |
| 2 61 | 26 6 | Fine to med. sand and gravel |
| 26 6 | 27 4 | Blue Clay |
| 2 | 30 9 | Fine to med. sand and gravel streak of med. coarse gravel |
| 3 09 | 327 | Fine to med. sand and gravel streak of med. coarse gravel hard streak |
| 327 | 341 | Brown Sandy Clay (hard) |
| 341 | 35 7 | Fine to med. sand and gravel tight 10% Clay |
| 3 57 | 364 | Fine to med. sand and fine gravel |
| 3 64 | 382 | Brown Sandy Clay |
| 3 82 | 425 | Brown Sandy Clay White Rock hard |
| | | |