USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

| | County | Fraction | | | Section | number | Township number | Range number | | |
|--|--------------------------------------|---------------------------------------|-------------|-----|----------|--------|--|-------------------------------------|---------------------------------------|------------|
| 1. Location of well: | Haskell | N ¹ ⁄2 1X# | NW1/4 NW | 1/4 | 22 | ! | т 27 s | r 33 | E.W | |
| 2. Distance and direction from nearest town or city: | | | | | | | Francis Marcotte 607 N. 10th St. Garden City, KS 67846 | | | • |
| 4. Locate with "X" | | ketch map: | | | | | 6. Bore hole dia. 26 in. Well depth 395 ft. | | <u>-3</u> -76 | |
| X NW | NE | | | | | | 7 Cable tool Rotary Hollow rod Jetted | | e rotary | |
| * * * * * * * * * * * * * * * * * * * | E E | | | | | | Lawn Oi | r conditioning Stock | k er | |
| 1 | s . | | | | | : | 9. Casing: Material <u>Stee</u> Threaded WeldedX RMP PVC | Surface 12 Weight 36 | in. lbs./ft. | |
| 5. Type and color of | f material | | | | From | То | Dia. <u>16</u> in. t <u>395</u> ft. dep Dia. <u>in.</u> to <u>ft. dep</u> | | 9 | |
| | See attach | ment | | | | | 10. Screen: Manufacturer's n | ame <u>Brown</u> | | |
| | | | | | | | Type Louvered Slot/gauze 080 Set between 395-375 265-245 ft. a | Length 120' | 5_ft. | |
| | | | | | <u> </u> | | Gravel pack? YesSize ran | nge of material | <u>≂"</u> /8 | |
| | | | | | | | 11. Static water level:164_ft. below land sur | | _{day/yr} . 5 <u>- 7</u> 6 | |
| | | · · · · · · · · · · · · · · · · · · · | | | | | 12. Pumping level below land 182 ft. after | I surfaces: nrs. pumping 1420 | g.p.m. | |
| | | | | | | | ft. after h | nrs. pumping | | |
| | | | | | | | 13. Water sample submitted: | mo./e | day/yr. | |
| | | | | | | | Yes No 14. Well head completion: | Date | | |
| | | | | | | | | 12 Inches above gr | | |
| | | | | | | | 15. Well grouted? Yes With: Neat cement X Depth: From ft. to . | 10 # | 1 7 | となっ |
| | | | | | | | 16. Nearest source of possible ft Direction | None contamination: obs | served | 7 |
| | | | | | | | Well disinfected upon comple | Yes X | | J |
| | | | | | | | Manufacturer's name | HP Volts | | J) |
| | | | | | | | Length of drop pipe | | |) ' |
| | | | | | | | Type: Submersible | Turbine | | , |
| | (Use a second s | heet if needed | i) | | | | Jet Centrifugal | Reciproc Other | ر کا | |
| 18. Elevation: | 19. Remarks: | | | | | | 20. Water well contractor's of This well was drilled under m | | eport | S |
| Flat | | | | | | | is true to the best of my know | | 45 5 | 1 |
| Topography: Hill | | | | | | J | Business name Add. BOX 639, 0 | <u>& Supply l</u> Garden Cit | nse No. | , ' |
| Slope Upland Valley | | | | | | | Address OX 639, C | hwell Date 1 | 1-9-7 | 144 4 |
| | ue and nink copies to the Department | of Health and | Environment | | | | | Form WWC | | 1 |

DRILLERS TEST LOG

| | STREET AI | DRESS | . | TEST # 2 E. Log 420' | | |
|----|--------------|--|-----------|--|--|--|
| | | | | rden City, KS 67846 DRILLER Rector | | |
| | | | | TER NW SECTION 22 TOWNSHIP 27 RANGE 33 | | |
| | CCATION | 940 | 'E. of N. | W. corner of 1/4 | | |
| | | <u> </u> | | | | |
| | | | | WELL LOCATION | | |
| | DRILLED | | FOOTAGE | Static Water Level | | |
| | From | Pay | To | Description of Strata Proposed Well Depth | | |
| - | 0, | 1 | 2 | Top soil | | |
| - | 2 | | 65 | Brown sandy clay and fine sand | | |
| | 65 | 60 | 220 | Sand fine med. coarse, small gravel, large, and | | |
| _ | | - | | cobblestones, rough and ragged, used lots of wa | | |
| _ | | | | Mud heavy | | |
| | 220 | 33 | 253 | Sand fine med. coarse, small to large gravel and | | |
| - | | | | fine sandy clay mixed | | |
| - | 253 | | 260 | Brown clay | | |
| | 260 | 35 | 295 | Sand fine med. coarse and small gravel and smal | | |
| _ | | | | cemented ledge, used water | | |
| 4 | 295 | 10 | 305 | Brown sandy clay and sand and gravel mixed | | |
| 4 | 305 | 35 | 340 | Sand fine med. coarse, small gravel and very sm | | |
| _} | | | | clay and lime rock sts. | | |
| 4 | 340 | 9 | 349 | Brown sandy clay and sand coarse and small | | |
| - | 349 | | 384 | Brown clay and lime rock and small sts. of sand | | |
| 4 | 384 | 8 | 392 | Sand fine med. coarse and med. to small gravel, | | |
| 4 | | | | loose, used water | | |
| + | 392 | | 464 | Brown clay and lime rock and very few fine sand | | |
| | 464 | | 480 | Yellow clay and soapstone, firm, used pull down | | |
| Ļ | • | 190 | | | | |
| | | - | | TOTAL DEPTH OF WELL 395 FT. | | |
| | | | | Set up west: pit on north | | |
| | | | | 10 sacks Quik-Gel | | |
| | | | | 5 lb. lime | | |
| | | | | | | |
| | | | | | | |
| I | | | · | | | |
| I | | | | | | |
| | | | | | | |
| | | | | | | |
| J | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| ſ | | | | | | |
| | | | | | | |
| ተ | | | | | | |

T HOLES*******STOCK WELLS*************IRRIGATION AND INDUSTRIAL WELLS****