LOCATION OF WATER WELL:			4 / A BE	4 28	; Section No	umber	: Township	Number	: Range	Number
COUNTY: 041 HASKELL		1/4 	1/4 SE	1/4	; 25		; 1 2/	5	; H 33	
Distance and direction from APPROX. 12.5 MILES NORTH A			OF SUBLETTE	i .	of well if l		•			
WATER WELL OWNER: RR#, St. Address, Box # :					Boa	rd of Agr:	iculture, Di	vision of	Water Res	sources
City, State, ZIP code :	WICHITA,	KS 6	57204-		Арр	lication 1	Number:			
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:								2. 0 1	t. 3.	. 0 fi
\	! ! !	i i	'S STATIC WA Pump t		266 ft. bo Well water o					
1 ! !			mated Yield	0 gpm	Well water	was () ft. after	0 hour	s pumping	g O g
₩	l i	f t				o 0 f	t., and	in. to	0 ft.	
SW SI	<u> </u>	; WELL	WATER WAS:	01 DOMEST!	C					i i
/ ! ! !	i i	¦ Was a	a chemical/b	pacteriolog	ical sample vas submitter				ell disint	fected? Ye
Blank casing diameter Casing height above land so	01 STEEL 5 in. urface -	to 29 36 in.,	CASIN 30 ft., Dia weight	16 JOINTS:	to 0 f	t., Dia	in. to	0 ft.		
Blank casing diameter Casing height above land so TYPE OF SCREEN OR PERFORATI SCREEN OR PERFORATION OPEN	01 STEEL 5 in. urface -: ION MATERIA INGS ARE:	to 28 36 in., AL: 01 S UNKN From From From	CASIN 30 ft., Dia weight STEEL NOWN 0 ft. to 0 ft. to	## JOINTS: 1	WELDED to Of /ft. Wall , From , From , From	t., Dia thickness Oft. to Oft. to	in. to or gauge No 0 ft. 0 ft. 0 ft.	0 ft.		
Blank casing diameter Casing height above land so TYPE OF SCREEN OR PERFORATI SCREEN OR PERFORATION OPEN SCREEN PERFORATED INTERVALS GRAVEL PACK INTERVALS GROUT MATERIAL 02 CEMENT Grout Intervals: From What is the nearest source	O1 STEEL 5 in. urface -: ION MATERIA INGS ARE: G: G: T GROUT 3 ft. to	to 28 36 in., AL: 01 S UNKN From From From From	CASIN 30 ft., Dia weight STEEL 40WN 0 ft. to 0 ft. to 0 ft. to	O ft. to	WELDED to Of /ft. Wall , From , From , From , From	t., Dia thickness Oft. to Oft. to Oft. to	in. to or gauge No 0 ft. 0 ft.	0 ft.		
	01 STEEL 5 in. urface -: ION MATERIA INGS ARE: 6: 6: 7 GROUT 3 ft. to of possib	to 28 36 in., AL: 01 S UNKN From From From From	CASIM 30 ft., Dia weight STEEL NOWN 0 ft. to 0 ft. to 0 ft. to 0 ft. to	O ft. to	WELDED to 0 f /ft. Wall , From , From , From 0 ft. FROM 0 of 4	t., Dia thickness Oft. to Oft. to Oft. to From TO 4	in. to or gauge No O ft. O ft. O ft. O ft. TOPSOIL CEMENT 6	0 ft. O ft. PLUGGING	low many 1	feet?
Blank casing diameter Casing height above land so TYPE OF SCREEN OR PERFORATI SCREEN OR PERFORATION OPEN SCREEN PERFORATED INTERVALS GRAVEL PACK INTERVALS GROUT MATERIAL O2 CEMENT Grout Intervals: From What is the nearest source Direction from well? SOUTH	01 STEEL 5 in. urface -: ION MATERIA INGS ARE: 6: 6: 7 GROUT 3 ft. to of possib	to 28 36 in., AL: 01 S UNKN From From From From 13 ft	CASIM 30 ft., Dia weight STEEL NOWN 0 ft. to 0 ft. to 0 ft. to 0 ft. to	O ft. to	WELDED to 0 f /ft. Wall , From , From , From , From 0 ft. FROM 0 1 4 254 0 1 0	t., Dia thickness Oft. to ft.	in. to or gauge No 0 ft. 0 ft. 0 ft. 0 ft. 1 TOPSOIL CEMENT 6	0 ft. O ft. PLUGGING	low many 1	feet?
Blank casing diameter Casing height above land so TYPE OF SCREEN OR PERFORATI SCREEN OR PERFORATION OPEN SCREEN PERFORATED INTERVALS GRAVEL PACK INTERVALS GROUT MATERIAL O2 CEMENT Grout Intervals: From What is the nearest source Direction from well? SOUTH	01 STEEL 5 in. urface -: ION MATERIA INGS ARE: 6: 6: 7 GROUT 3 ft. to of possib	to 28 36 in., AL: 01 S UNKN From From From From 13 ft	CASIM 30 ft., Dia weight STEEL NOWN 0 ft. to 0 ft. to 0 ft. to 0 ft. to	O ft. to	WELDED to 0 f /ft. Wall , From , From , From , From 0 ft. FROM 0 4 254 0	t., Dia thickness Oft. to Oft	in. to or gauge No 0 ft. 0 ft. 0 ft. 0 ft. 1 TOPSOIL CEMENT 6 CHLORINA	0 ft. O ft. PLUGGING	low many 1	feet? ;

under the business name of HENKLE DRILLING & SUPPLY by (signature)