

LOCATION OF WATER WELL		Fraction	Section Number	Township Number	Range Number
County: Haskell		SE $\frac{1}{4}$ NW $\frac{1}{4}$ NE $\frac{1}{4}$	1	T 27 S	R 34 EW
Distance and direction from nearest town or city? Satanta 20$\frac{1}{2}$ North Finney Co. Line - $\frac{1}{2}$ West - 65' West of Pivot			Street address of well if located within city?		
WATER WELL OWNER: Fern Batchelder			Board of Agriculture, Division of Water Resources		
R#, St. Address, Box #: 1706 B			Application Number:		
City, State, ZIP Code: Garden City, KS 67846					
DEPTH OF COMPLETED WELL: 380 ft. Bore Hole Diameter: 26 in. to 380 ft., and in. to ft.					
Well Water to be used as:					
1 Domestic		3 Feedlot		5 Public water supply	
2 Irrigation		4 Industrial		6 Oil field water supply	
				7 Lawn and garden only	
				8 Air conditioning	
				9 Dewatering	
				10 Observation well	
				11 Injection well	
				12 Other (Specify below)	
Well's static water level: 160 ft. below land surface measured on August month 25 day 1979 year					
Pump Test Data					
st. Yield 1500 gpm:		Well water was 171 ft. after 2 hours pumping 1000 gpm		Well water was 176 ft. after 3 hours pumping 1500 gpm	
TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)		5 Wrought iron	
2 PVC		4 ABS		6 Asbestos-Cement	
				7 Fiberglass	
				8 Concrete tile	
				9 Other (specify below)	
				Casing Joints: Glued <input type="checkbox"/> Clamped <input checked="" type="checkbox"/>	
				Welded <input checked="" type="checkbox"/>	
				Threaded <input type="checkbox"/>	
Blank casing dia: 16 in. to 380 ft., Dia in. to ft., Dia in. to ft.					
Casing height above land surface: 12 in., weight 36.4 lbs./ft. Wall thickness or gauge No. 219					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel		3 Stainless steel		5 Fiberglass	
2 Brass		4 Galvanized steel		6 Concrete tile	
				7 PVC	
				8 RMP (SR)	
				9 ABS	
				10 Asbestos-cement	
				11 Other (specify)	
				12 None used (open hole)	
Screen or Perforation Openings Are:					
1 Continuous slot		3 Mill slot		5 Gauzed wrapped	
2 Louvered shutter		4 Key punched		6 Wire wrapped	
				7 Torch cut	
				8 Saw cut	
				9 Drilled holes	
				10 Other (specify)	
				11 None (open hole)	
Screen-Perforation Dia: 16 in. to 380 ft., Dia in. to ft., Dia in. to ft.					
Screen-Perforated Intervals:					
From 190 ft. to 355 ft.		From 375 ft. to 380 ft.		From 355 ft. to 375 ft.	
From 375 ft. to 380 ft.		From 380 ft. to 380 ft.		From 380 ft. to 380 ft.	
Gravel Pack Intervals:					
From 10 ft. to 380 ft.		From 380 ft. to 380 ft.		From 380 ft. to 380 ft.	
GROUT MATERIAL:					
1 Neat cement		2 Cement grout		3 Bentonite	
4 Other					
Grouted Intervals: From 0 ft. to 10 ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank		4 Cess pool		7 Sewage lagoon	
2 Sewer lines		5 Seepage pit		8 Feed yard	
3 Lateral lines		6 Pit privy		9 Livestock pens	
				10 Fuel storage	
				11 Fertilizer storage	
				12 Insecticide storage	
				13 Watertight sewer lines	
				14 Abandoned water well	
				15 Oil well/Gas well	
				16 Other (specify below)	
Direction from well: How many feet? Water Well Disinfected? Yes <input checked="" type="checkbox"/> No <input type="checkbox"/>					
Was a chemical/bacteriological sample submitted to Department? Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> If yes, date sample was submitted month day year					
Pump Installed? Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> Yes: Pump Manufacturer's name Goulds 6 Stage Model No. 12 JMC HP 125 Volts					
Depth of Pump Intake 220 ft. Pumps Capacity rated at 800 gal./min.					
Type of pump:					
1 Submersible		2 Turbine		3 Jet	
4 Centrifugal		5 Reciprocating		6 Other	
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on August month 29 day 1979 year					
and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 208					
This Water Well Record was completed on December month 16 day 1980 year under the business name of Minter Wilson Drilling Co., Inc. by (signature) <i>M. Irene DeKeyser</i>					
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		FROM TO LITHOLOGIC LOG		FROM TO LITHOLOGIC LOG	
		<p style="text-align: center;">Test log attached</p>			
ELEVATION:		FROM TO LITHOLOGIC LOG		FROM TO LITHOLOGIC LOG	
Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. 4. ft.				(Use a second sheet if needed)	

OFFICE USE ONLY

T R27

R

34

EW

SEC. 1

SE $\frac{1}{4}$ NW $\frac{1}{4}$ NE $\frac{1}{4}$

INSTRUCTIONS: Use typewriter or ball point pen, please press firmly and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Water Well Contractors, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

Phone 276-9789 • P.O. Box A • GARDEN CITY, KANSAS 67844

May 7, 1979

Fern Batchelder
Haskell County

Location: NE $\frac{1}{4}$ 1-27-34 -A- Approx. 65' West of Pivot

Static Water Level - 140

Test #

0	13	Sand
13	67	Sand & Clay
67	140	Med. to coarse gravel (loose)
140	230	Fine to med. sand and gravel streaks of coarse gravel (loose)
230	264	Brown Sandy Clay 30% Gravel (loose)
264	311	Fine to med. sand and gravel 10% Clay (loose)
311	322	Brown Sandy Clay
322	380	Fine to med. sand and gravel 10% Clay (loose)
380	395	Brown Sandy Clay

T. D. 380'