

1 LOCATION OF WATER WELL		Fraction		Section Number		Township Number		Range Number	
County: <u>Haskell</u>		<u>NE 1/4</u> <u>NW 1/4</u> <u>SW 1/4</u>		<u>9</u>		<u>T 27 S</u>		<u>R 34 EW</u>	
Distance and direction from nearest town or city? <u>14 N., 9 W., 2 N., 1/2 W., 1/2 N. of Sublette</u>					Street address of well if located within city?				
2 WATER WELL OWNER:		<u>Tommy Lewis</u>			<u>North Well</u>				
RR#, St. Address, Box # :		<del>XXXXXX</del> <u>Lewis &amp; Decker Cattle</u>			Board of Agriculture, Division of Water Resources				
City, State, ZIP Code :		<u>Satanta, Kansas 67870</u>			Application Number: <u>----</u>				
3 DEPTH OF COMPLETED WELL		<u>400</u> ft. Bore Hole Diameter			<u>9.7/8</u> in. to <u>400</u> ft. and ..... in. to ..... ft.				
Well Water to be used as:		5 Public water supply			8 Air conditioning				
1 Domestic 3 Feedlot		6 Oil field water supply			9 Dewatering				
2 Irrigation 4 Industrial		7 Lawn and garden only			10 Observation well				
Well's static water level		<u>139</u> ft. below land surface measured on			<u>April</u> month <u>9</u> day <u>1980</u> year				
Pump Test Data		Well water was			ft. after ..... hours pumping ..... gpm				
Est. Yield <u>40-50</u> gpm:		Well water was			ft. after ..... hours pumping ..... gpm				
4 TYPE OF BLANK CASING USED:		5 Wrought iron			8 Concrete tile				
1 Steel		3 RMP (SR)			9 Other (specify below)				
<del>XXX</del> PVC		4 ABS			7 Fiberglass				
Blank casing dia		<u>5</u> in. to <u>320</u> ft., Dia			in. to ..... ft., Dia				
Casing height above land surface		<u>24</u> in., weight			<u>3.92</u> lbs./ft. Wall thickness or gauge No. <u>375</u>				
TYPE OF SCREEN OR PERFORATION MATERIAL:		1 Steel			3 Stainless steel				
2 Brass		4 Galvanized steel			6 Concrete tile				
Screen or Perforation Openings Are:		5 Gauzed wrapped			XXX 8 Saw cut				
1 Continuous slot		3 Mill slot			6 Wire wrapped				
2 Louvered shutter		4 Key punched			7 Torch cut				
Screen-Perforation Dia		<u>5</u> in. to <u>400</u> ft., Dia			in. to ..... ft., Dia				
Screen-Perforated Intervals:		From <u>320</u> ft. to <u>400</u> ft.			From ..... ft. to ..... ft.				
Gravel Pack Intervals:		From <u>10</u> ft. to <u>400</u> ft.			From ..... ft. to ..... ft.				
5 GROUT MATERIAL:		XX Neat cement			2 Cement grout				
Grouted Intervals: From		<u>0</u> ft. to <u>10</u> ft.			3 Bentonite				
What is the nearest source of possible contamination:		1 Septic tank			4 Cess pool				
2 Sewer lines		5 Seepage pit			8 Feed yard				
3 Lateral lines		6 Pit privy			9 Livestock pens				
Direction from well		<u>Southwest</u>			How many feet <u>300</u> ?				
Was a chemical/bacteriological sample submitted to Department? Yes		No			XXX				
If Yes: XXXX Manufacturer's name		<u>Aermotor Mill</u>			10' Model No. .... HP .... Volts ....				
Depth of Pump Intake		<u>189</u> ft.			Pump Capacity rated at <u>3</u> gal./min.				
Type of pump:		1 Submersible			2 Turbine				
3 Jet		4 Centrifugal			XXX 6 Reciprocating				
6 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on		<u>April</u> month <u>17</u> day <u>1980</u> year			and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>252</u>				
This Water Well Record was completed on		<u>5</u> month <u>9</u> day <u>1980</u> year			under the business name of <u>Friesen Windmill &amp; Supply, Inc.</u> by (signature) <u>[Signature]</u>				
7 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		FROM		TO		LITHOLOGIC LOG		LITHOLOGIC LOG	
		0		30		Fine Sand			
		30		52		Clay			
		52		70		Med. to Lar. Sand & Gravel			
		70		140		Med. to Lar. Sand, Gravel with Rocks			
		140		318		Med. to Lar. Sand & Gravel			
		318		348		Dakota Clay			
ELEVATION: <u>Valley</u>									
Depth(s) Groundwater Encountered		1. Not available		ft. 3		ft. 4		(Use a second sheet if needed)	

OFFICE USE ONLY

T

2-7

R

3-4

EW

SEC.

9

NE 1/4

NW 1/4

SW 1/4

SE 1/4