


USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:		County Haskell County	Section 1/4 SE 1/4 CSE 1/4	Section number 11	Township number T 27 S	Range number R 34
2. Distance and direction from nearest town or city: Street address or well location if in city:		17 South, 7 West, 1/4 North, 1/4 West of Garden City ON THE		3. Owner of well: R.R. or street: City, state, zip code:		
4. Locate with "X" in section below: Sketch map:				6. Bore hole dia. 26 in. Completion date 4-29-79 Well depth 435 ft.		
5. Type and color of material				7. <input type="checkbox"/> Cable tool <input type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input checked="" type="checkbox"/> Reverse rotary		
				8. Use: <input type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input checked="" type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other		
				9. Casing: Material Steel Height: Above or below Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface 1 ft. in. RMP <input type="checkbox"/> PVC <input type="checkbox"/> Weight 36.87 lbs./ft. Dia 16 in. to 435 ft. depth Wall Thickness: inches or Dia. <input type="checkbox"/> in. to <input type="checkbox"/> ft. depth gage No. 219		
				10. Screen: Manufacturer's name Johnson Type Johnson Galy. 100-16" Slot/gauze 0-170 Plain 170-270 Perf. Set between 270-290 Screen 290-350 Perf. 350-390 Plain and 390-435 Perf. Gravel pack? yes Size range of material 1 to 5/8		
				11. Static water level: <input type="checkbox"/> mo./day/yr. 127 ft. below land surface Date 4-16-79		
				12. Pumping level below land surfaces: 132.5 ft. after 2 hrs. pumping 1200 g.p.m. 133.5 ft. after 4 hrs. pumping 1500 g.p.m. Estimated maximum yield 1500 g.p.m.		
				13. Water sample submitted: <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Date <input type="checkbox"/>		
				14. Well head completion: <input type="checkbox"/> Pitless adapter 1 ft. inches above grade		
				15. Well grouted? yes With: <input type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input checked="" type="checkbox"/> Concrete Depth: From 0 ft. to 10 ft.		
				16. Nearest source of possible contamination: ft. <input type="checkbox"/> Direction N/A Type <input type="checkbox"/> Well disinfected upon completion? <input type="checkbox"/> Yes <input type="checkbox"/> No		
				17. Pump: <input type="checkbox"/> Not installed Manufacturer's name Could 6 stg. 12" JHC Bowl Model number <input type="checkbox"/> HP 125 Volts <input type="checkbox"/> Length of drop pipe 220 ft. capacity 1000 g.p.m. Type: <input type="checkbox"/> Submersible <input checked="" type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other		
18. Elevation:		19. Remarks:		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Minter Wilson Drilling Co. 208 Business name License No. 1/4 CSE Address Box A, Garden City, KS 67846 Signature Deane DeLeon Date 4/27/79 Authorized representative		

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5

MINTER-WILSON DRILLING CO.
INCORPORATED

Irrigation
and Domestic
Water Systems
Complete Installation
and Repairing

Phone 276-8269

P.O. Box A

GARDEN CITY KANSAS 67841

February 9, 1979

**Fern Batchelder
Haskell County**

Location: S. E. $\frac{1}{4}$ 11-27-34 30' North of Well stake

Static Water Level -

Test #1

0	4	Top Soil
4	15	Brown Clay
15	73	Brown Sandy Clay
73	112	Fine to med. sand and gravel (loose)
112	122	Fine to med. sand and gravel hard pull down
122	138	Med. coarse gravel
138	292	Med. coarse gravel (loose)
292	339	Brown Sandy Clay small gravel streak
339	347	Fine to med. sand and gravel
347	406	Brown Sandy Clay
406	430	Fine to med. sand and gravel (loose)
430	440	Yellow Clay

T.D. 435'