

1 LOCATION OF WATER WELL: County: Haskell		Fraction NW 1/4 NW 1/4 SW 1/4		Section Number 15		Township Number T 27 S		Range Number R 34 E	
Distance and direction from nearest town or city street address of well if located within city? Sublette Jct. HWY 83 and HWY 56, 14 North, 9 West, 1 1/2 North, East side of road									
2 WATER WELL OWNER: Helmerich & Payne RR#, St. Address, Box #: 2606 Fleming City, State, ZIP Code: Garden City, KS 67846					Board of Agriculture, Division of Water Resources Application Number:				
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: <div style="text-align: center;"> </div>					4 DEPTH OF COMPLETED WELL: 360 ft. ELEVATION: Depth(s) Groundwater Encountered 1. _____ ft. 2. _____ ft. 3. _____ ft. WELL'S STATIC WATER LEVEL: 202 ft. below land surface measured on mo/day/yr 01/21/92 Pump test data: Well water was _____ ft. after _____ hours pumping _____ gpm Est. Yield _____ gpm: Well water was _____ ft. after _____ hours pumping _____ gpm Bore Hole Diameter: 10 5/8 in. to 360 ft., and _____ in. to _____ ft. WELL WATER TO BE USED AS: <div style="display: flex; justify-content: space-between;"> <div> 1 Domestic 2 Irrigation </div> <div> 3 Feedlot 4 Industrial </div> <div> 5 Public water supply 6 Oil field water supply 7 Lawn and garden only </div> <div> 8 Air conditioning 9 Dewatering 10 Monitoring well </div> <div> 11 Injection well 12 Other (Specify below) </div> </div> Was a chemical/bacteriological sample submitted to Department? Yes _____ No X ; If yes, mo/day/yr sample was submitted _____ Water Well Disinfected? Yes X No _____				
5 TYPE OF BLANK CASING USED: <div style="display: flex; justify-content: space-between;"> <div> 1 Steel 2 PVC Blank casing diameter: 5 in. to SEE BELOW Casing height above land surface: 12 in., weight SEE BELOW </div> <div> 3 RMP (SR) 4 ABS </div> <div> 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass </div> <div> 8 Concrete tile 9 Other (specify below) </div> </div> Casing joints: Glued X Clamped _____ Welded _____ Threaded _____					TYPE OF SCREEN OR PERFORATION MATERIAL: <div style="display: flex; justify-content: space-between;"> <div> 1 Steel 2 Brass SCREEN OR PERFORATION OPENINGS ARE: <div style="display: flex; justify-content: space-between;"> <div> 1 Continuous slot 2 Louvered shutter </div> <div> 3 Mill slot 4 Key punched </div> <div> 5 Fiberglass 6 Concrete tile </div> </div> </div> <div> 7 PVC 8 RMP (SR) 9 ABS </div> <div> 10 Asbestos-cement 11 Other (specify) 12 None used (open hole) </div> </div> SCREEN-PERFORATED INTERVALS: From 210 ft. to 220 ft., From 240 ft. to 250 ft. From 290 ft. to 310 ft., From 330 ft. to 360 ft. GRAVEL PACK INTERVALS: From 169 ft. to 360 ft., From _____ ft. to _____ ft.				
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 5 ft. to 25 ft., From 25 ft. to 169 ft., From _____ ft. to _____ ft. What is the nearest source of possible contamination: <div style="display: flex; justify-content: space-between;"> <div> 1 Septic tank 2 Sewer lines 3 Watertight sewer lines </div> <div> 4 Lateral lines 5 Cess pool 6 Seepage pit </div> <div> 7 Pit privy 8 Sewage lagoon 9 Feedyard </div> <div> 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage </div> <div> 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below) </div> </div> Direction from well? _____ How many feet? N/A					FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS 0' to 210' Plain Casing SDR21 Weight 2.81 lbs./ft. .265 wall 210' to 220' Perf Casing SDR21 220' to 240' Plain Casing SDR21 240' to 250' Perf Casing SDR21 250' to 290' Plain Casing SDR21 290' to 310' Perf Casing SDR21 310' to 330' Plain Casing SDR17 Weight 3.43/lbs./ft. .327 wall 330' to 360' Perf Casing SDR17 SEE ATTACHED LOG				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, 2 reconstructed, or 3 plugged under my jurisdiction and was completed on (mo/day/year) January 23, 1992 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 208 This Water Well Record was completed on (mo/day/yr) February 7, 1992 under the business name of Minter-Wilson Drilling Company, Inc. by (signature) Nora Keller									