

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Haskell		$\frac{1}{4}$ $\frac{1}{4}$ SE $\frac{1}{4}$	16	T 27 S	R 34 E
Distance and direction from nearest town or city street address of well if located within city? Highway 83 - 8 West - 1 North From Garden City 20 South on					
2 WATER WELL OWNER: Tommy Lewis			Board of Agriculture, Division of Water Resources		
RR#, St. Address, Box #: Satanta, KS 67870			Application Number:		
City, State, ZIP Code:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 369 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 175 ft. 2. 369 ft. 3. 369 ft.			
		WELL'S STATIC WATER LEVEL X 175 ft. below land surface measured on mo/day/yr			
		None Pump test data: Well water was _____ ft. after _____ hours pumping _____ gpm			
		Est. Yield _____ gpm: Well water was _____ ft. after _____ hours pumping _____ gpm			
Bore Hole Diameter 10 5/8 in. to 369 ft., and _____ in. to _____ ft.					
WELL WATER TO BE USED AS:		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well			
Was a chemical/bacteriological sample submitted to Department? Yes _____ No X _____; If yes, mo/day/yr sample was submitted _____		Water Well Disinfected? Yes _____ No X _____			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued _____ Clamped _____			
1 Steel 3 RMP (SR) 2 PVC 4 ABS		5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below) 10 Asbestos-cement 11 Other (specify) 12 None used (open hole)			
Blank casing diameter 6 5/8 in. to 310 ft., Dia. _____ in. to _____ ft.		Casing height above land surface 12 in., weight 12.8 lbs./ft. Wall thickness or gauge No. .188			
TYPE OF SCREEN OR PERFORATION MATERIAL:		1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) 9 ABS 12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:		1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)			
PERFORATED INTERVALS: From 310 ft. to 370 ft., From _____ ft. to _____ ft.					
GRAVEL PACK INTERVALS: From 10 ft. to 369 ft., From _____ ft. to _____ ft.					
6 GROUT MATERIAL:		3 Bentonite 4 Other _____			
Grout Intervals: From 0 ft. to 10 ft., From _____ ft. to _____ ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well 11 Fuel storage 15 Oil well/Gas well 12 Fertilizer storage 16 Other (specify below) N/A 13 Insecticide storage			
1 Septic tank 4 Lateral lines 7 Pit privy 2 Sewer lines 5 Cess pool 8 Sewage lagoon 3 Watertight sewer lines 6 Seepage pit 9 Feedyard		How many feet? _____			
FROM	TO	LITHOLOGIC LOG		FROM	TO
		Test log attached			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) May 11, 1982 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 208 This Water Well Record was completed on (mo/day/yr) August 30, 1982 under the business name of Minter Wilson Drilling Co., Inc. by (signature) <i>Blaine DeKemper</i>					
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					

The
Professionals

MINTER-WILSON DRILLING CO.

INCORPORATED

Irrigation
and Domestic
Water Systems
Complete Installation
and Repairing

Phone 276-8269 • P.O. Box A • GARDEN CITY, KANSAS 67846

TOMMY LEWIS
Haskell County
May 7, 1982

Location: East of Tommy's House, House Well

Static Water Level -

Test #

0	1	Top Soil
1	80	Brown Clay
80	211	Fine to Medium Sand & Gravel with Coarse Gravel
211	230	Brown & Gray Clay
230	260	Brown Clay 35% Gravel
260	275	Fine to Medium Sand & Gravel 20% Clay (Loose)
275	285	Brown Sandy Clay
285	335	Fine to Medium Sand & Gravel 10% Clay (Loose)
335	350	Fine to Medium Sand & Gravel (35% Clay Streaks Loose)
350	356	Brown Sandy Clay
356	373	Fine to Medium Sand & Gravel 10% Clay (Loose)
373	425	Brown Clay (Tight)

TD 375'

Drill 10 5/8" Hole to 375'

Set 6 5/8" Pipe to 370'

60' Perf