		WATER WI	ELL RECORD	Form WWC-5	KSA 82a-	1212				
LOCATION OF WAT	ER WELL: Fra	action		Sec	tion Number	Township N	lumber	1	ge Num	_
ounty: Haskell		SE ¼		SE 1/4	23	т 27	S	F84	34	<u> </u>
istance and direction	from nearest town or cit	y street addres	ss of well if locate	d within city?						
	iles north of									
WATER WELL OW		У								
R#, St. Address, Box		(7070				Board of A	Agriculture,	Division of	Water F	Resource
ity, State, ZIP Code	: Satanta,						n Number:			
LOCATE WELL'S LO	CATION WITH DEF	TH OF COMP	LETED WELL	4.85!	ft. ELEVA	TION:				
AN "X" IN SECTION	Depth(r Encountered 1							
	WELL'	S STATIC WAT	TER LEVEL 23	33,! ft. b	elow land surf	ace measured or	n mo/day/yr			
			data: Well water							
NW	NE Est. Yi		gpm: Well water							
.			9 . 7 /.8 .in. to							
w - 		WATER TO BE		5 Public water		B Air conditioning		Injection w		
	1 1 1	Domestic_	3 Feedlot	6 Oil field wa	ter supply	9 Dewatering	•	•		ow)
sw	SE 2	Irrigation				0 Observation w			-	
		•	riological sample s		•					
	mitted		morogroui oumpio o			er Well Disinfecte	-	_	o lo	was sub
TYPE OF BLANK C			Vrought iron	8 Concre		CASING JO				
			•							
1 Steel 2 PVC	3 RMP (SR) 4 ABS		Asbestos-Cement		(specify below	•		led		
2 PVC	5"in. to .	485' '	iberglass					aded		
ank casing diameter			. ft., Dia							
	nd surface12".		weight 2						D,⊃∵₩	
	R PERFORATION MATE			_ 7.PV			bestos-ceme			
1 Steel	3 Stainless steel		iberglass		IP (SR)	11 Oth	ner (specify)			
2 Brass	4 Galvanized stee	1 60	Concrete tile	9 AB	S	12 No	ne used (op	en hole)		
REEN OR PERFOR	ATION OPENINGS ARI	= :	5 Gauz	ed wrapped		8 Saw cut		11 None	(open h	ole)
1 Continuous slot	3 Mill slot	<u> </u>	6 Wire	wrapped		9 Drilled holes				
2 Louvered shutte	er 4 Key punc	hed	7 Torch	cut		10 Other (specif	y)			
CREEN-PERFORATE			5 ft. to							
	Fro	m405-48	5 ft. to		ft., Fron	1	ft. 1	to		ft.
GRAVEL PAG	K INTERVALS: Fro	m 10-485	ft. to		ft., Fron	1 <i></i>	ft. 1	to		ft.
	Fro		ft. to		ft., Fron					ft.
GROUT MATERIAL	1 Neat cement	2 Ce	ement grout	3 Bento	nite 4	Other				
rout Intervals: Fron	0-10!ft. to .		ft., From	<i>.</i> ft.	to	ft., From		ft. to .		ft.
	urce of possible contam				10 Livest		14 A			
1 Septic tank 4 Lateral lines			7 Pit privy		11 Fuel storage		15 C	15 Oil well/Gas well		
2 Sewer lines	5 Cess pool		8 Sewage lagoon		12 Fertilizer storage		16 Other (specify below			Λ
	er lines 6 Seepage pit		9 Feedyard			icide storage		(0)	.,	,
rection from well?					How man	•	ONE OBSI	RRVED		
ROM TO	LITH	OLOGIC LOG		FROM	то	y 1001.	LITHOLOG			
10										
					<u> </u>					*****
	See attach	ed log								
					 					
				+						
				-	ļ					
		-								
CONTRACTOR'S	AD LANDOWNED'S OF	TIEICATION:	This water well	ae (1) senst-	Mad (2)	netructed of (0)	olugeed	dos	alietie -	
	R LANDOWNER'S CER									
	year) 10-21-86								nd belief	. Kansas
	License No 145							- MO . //		<i> </i>
der the business nar	ne of Henkle Dril	ling & Su	ipply Co.,	inc.	by (signat	ure) //	J Ke	Mm	utt	
MO I MUU I IUNS: USB TY	pewriter or ball point pen. PL	LAGE PRESS FIL	THILI WIN LUNI CIO	any. Mease till in	DIRECTOR UNDER THE	or circle the correct	ыяswers. Se	na top tnree c	opies to F	\ansas
Department of Health an	d Environment, Office of Oil F	ield and Environn	nental Geology, Regu	lation and Permit	ting Section. Ton	eka, Kansas 66620.	7500. Teleph	one: 913-862	-9360 Se	nd one

DRILLERS TEST LOG

			_	Dame 10-21-86	
CUSI	OMERS	MAM	E Fr	TEST # 1 E. LOG Yes	
STRE	ET AD	DKES	S	tanta, KS 67870 DRILLER Livingston	
CITY	& ST	ATE _	Sa	UARTER SE SECTION 23 TOWNSHIP 27 RANGE 34	
COUN	TY_H	askel	1 Q	WARTER SE SECTION 20 TOWNSHIT	
LOCA	MOIT			TO COMMON	
				WELL LOCATION	
%	FC	OTAC	E	Static Water Level	
	From	Pay	To	DESCRIPTION OF STRATA Proposed Well Depth	
	0		2	Top Soil	
	2		110	Brown sandy clay and caliche and sand streaks	ent
	110		207	Sand, fine to medium, small to large graver, drills rough com	icii c
	207		237	Sand, fine to medium, small to medium gravel, drills tough	
	237		257	Brown clay	
	257		320	1 - 1 for fine and atks	
15		07		Sand, fine and limerock and sandy clay	
	327				
<u>20</u> 25	340	17			
	357		425	The state of the s	
40	425				
40	438		465		
40	465	21		and the state of t	
40	486	+	500		
	480	1-	300	nimescone and sorp	
	 	 	1		
	 	+		TOTAL DEPTH: 485'	
	 	┼─	 	TOTAL DEFIL. 403	•
	 	 	 	5" PVC CASING	
	 	1-	 	PERF PLAIN	
	 	┼─	 	485' - 405' 80'	
	1	 	 	405' - 345'	
-	1	1-	+	345' - 325' 20'	-
	1	1-	1	325' - 0' 325'	
	1	┪		323	
 	1	┪—		TOTAL 100' 385	
 	 	-	+		
	 	-		250 lb. Celca	
	 	 		17 lb. HDH	
	1	1-		50 lb. Gel	
	 	1-	1	30 20. 002	
-	-	-	- 		
	-	+-			
-	 				1
-			+		1
-					
-					1
-					1
-					+

GARDEN CITY, KS Phone 276-3278

HENKLE DRILLING & SUPPLY CO., INC. IRRIGATION HEADQUARTERS TEST HOLES * * * * * * IRRIGATION & INDUSTRIAL WELLS * * * * STOCK WELLS

SUBLETTE, KS Phone 675-4311