WATER WELL RECORD Form WWC-5 KSA 82a-1212 Fraction Township Number Range Number R 34 R Section Number 1 LOCATION OF WATER WELL: COUNTY: 041 HASKELL SE 1/4 SE 1/4 SW 1/4 23 Distance and direction from nearest town or city street address of well if located within city? FROM SUBLETTE; APPX 13 MILES NORTH & 2 1/2 MILES EAST 2 WATER WELL OWNER: HITCH FEEDERS II, INC. RR#, St. Address, Box # : 521 50TH ROAD Board of Agriculture, Division of Water Resources City, State, ZIP code : SATANTA, KS 67870- Application Number: 21,214 3 LOCATE WELL'S LOCATION WITH 4 DEPTH OF COMPLETED WELL 535ELEVATION: 0
AN "X" IN SECTION BOX: Depth(s) Groundwater Encountered 1. 0 ft. 2. 0 ft. 3. 0 ft. | | | WELL'S STATIC WATER LEVEL 293 ft. below land surface measured on mo/day/yr 08/21/04

		Pump testdata:	Well water wa	s 448 ft.	after 4 hou	rs pumping 800	gpm
NW	NĒ	Estimated Yield 0 gpm:	Well water w	as 0 ft.	after 0 hou	rs pumping 0	gpı
	E	Bore Hole Diameter	24 in. to	535 ft., an	d in. to	0 ft.	
CM	CP.	WELL WATER TO BE USED AS:	02 IRRIGATION				
	C -	Was a chemical/bacteriolog If yes, mo/day/yr sample w	ical sample s as submitted	ubmitted to d	epartment? No ; Water w	ell disinfected?	Yes
casing diam height abo F SCREEN OR	eter .250 in. ve land surface PERFORATION MATERI	to 535 ft., Dia in. 42 in., weight 12 lbs AL: 01 STEEL	wRLDRD to 0 ft. /ft. Wall th	, Dia ickness or ga	in. to 0 ft uge No250		
		From 500 ft. to 530 ft. From 20 ft. to 535 ft.	, From 0	ft. to 0 ft. to 0	ft. ft.		
Intervals: is the neare	From 0 ft. to st source of possib	20 ft., From 0 ft. to le contamination: 14 ABAND. W	0 ft.,	From 0 ft		How many feet?	7
56 68 94 237 241 258	02 SILT 01 CLAY 05 SAND 04 SANDY 04 SANDY CLAY 05 05 SAND 11 GRAVE 04 SANDY CLAY 05 SAND 11 GRAVE 04 SANDY CLAY	CLAY SAND 20 LIMESTONE L	FROM	TO	PLUGGING	INTERVALS	
	OF BLANK CAS casing diam height abo F SCREEN OR N OR PERFORATED GRAVEL PACK MATERIAL Intervals: is the neare tion from we TO 1 56 68 94 237 241 258	OF BLANK CASING USED: 01 STEEL casing diameter .250 in. g height above land surface OF SCREEN OR PERFORATION MATERI N OR PERFORATION OPENINGS ARE: WERFORATED INTERVALS: GRAVEL PACK INTERVALS: MATERIAL 03 BENTONITE Intervals: From 0 ft. to is the nearest source of possib cion from well? SOUTHWEST TO 1 02 SILT 56 01 CLAY 68 05 SAND 04 SANDY 94 04 SANDY CLAY 05 237 05 SAND 11 GRAVE 241 04 SANDY CLAY 258 05 SAND 11 GRAVE	Bore Hole Diameter WELL WATER TO BE USED AS: Was a chemical/bacteriolog If yes, mo/day/yr sample wown and incompleted and surface and incompleted and surface are incomp	BStimated Yield 0 gpm: Well water w Bore Hole Diameter 24 in. to WELL WATER TO BE USED AS: 02 IRRIGATION WELL WATER TO BE USED AS: 02 IRRIGATION WEIGHT ABOUT STEEL CASING JOINTS: WELDED Casing diameter .250 in. to 535 ft., Dia in. to 0 ft., height above land surface 42 in., weight 12 lbs/ft. Wall the SCREEN OR PERFORATION MATERIAL: 01 STEEL WOR PERFORATION OPENINGS ARE: 01 CONT. SLOT WERFORATED INTERVALS: From 407 ft. to 447 ft., From 0 From 500 ft. to 530 ft., From 0 GRAVEL PACK INTERVALS: From 20 ft. to 535 ft., From 0 From 0 ft. to 0 ft., From 0	BStimated Yield 0 gpm: Well water was 0 ft. Bore Hole Diameter 24 in. to 535 ft., an WELL WATER TO BE USED AS: 02 IRRIGATION WAS a Chemical/bacteriological sample submitted to d If yes, mo/day/yr sample was submitted OF BLANK CASING USED: 01 STEEL CASING JOINTS: WELDED casing diameter 250 in. to 535 ft., Dia in. to 0 ft., Dia y height above land surface 42 in., weight 12 lbs/ft. Wall thickness or galls SCREEN OR PERFORATION MATERIAL: 01 STEEL VOR PERFORATION OPENINGS ARE: 01 CONT. SLOT OF PERFORATED INTERVALS: Prom 407 ft. to 447 ft., From 0 ft. to 0 From 500 ft. to 530 ft., From 0 ft. to 0 GRAVEL PACK INTERVALS: Prom 20 ft. to 535 ft., From 0 ft. to 0 From 0 ft. to 0 ft., From 0 ft. to 0 ft. o 1 ft. o 0 ft. o 1	BStimated Yield 0 gpm: Well water was 0 ft. after 0 hou Bore Hole Diameter 24 in. to 535 ft., and in. to WELL WATER TO BE USED AS: 02 IRRIGATION WAS a chemical/bacteriological sample submitted to department? No; If yes, mo/day/yr sample was submitted Water w OF BLANK CASING USED: 01 STERL CASING JOINTS: WELLDED casing diameter .250 in. to 535 ft., Dia in. to 0 ft., Dia in. to 0 ft, height above land surface 42 in., weight 12 lbs/ft. Wall thickness or gauge No250 FSCREEN OR PERFORATION MATERIAL: 01 STEEL OR PERFORATED INTERVALS: From 407 ft. to 447 ft., From 0 ft. to 0 ft. From 500 ft. to 530 ft., From 0 ft. to 0 ft. GRAVEL PACK INTERVALS: From 20 ft. to 535 ft., From 0 ft. to 0 ft. From 0 ft. to 0 ft., From 0 ft. to 0 ft. From 0 ft. to 0 ft., From 0 ft. to 0 ft. THERPORATE OF THE WASTER OF THE WAST	Bestimated Yield 0 gpm: Well water was 0 ft. after 0 hours pumping 0 Bore Hole Diameter 24 in. to 535 ft., and in. to 0 ft. WELL WATER TO BE USED AS: 02 IRRIGATION Was a chemical/bacteriological sample submitted to department? No; If yes, mo/day/yr sample was submitted Water well disinfected? DF BLANK CASING USED: 01 STEEL CASING JOINTS: WELDED Casing diameter 250 in. to 535 ft., Dia in. to 0 ft., Dia in. to 0 ft. JR DEGREEN OR PERFORATION MATERIAL: 01 STEEL OR PERFORATION OPENINGS ARE: 01 CONT. SLOT IF PERFORATION OPENINGS ARE: 01 CONT. SLOT IF PERFORATED INTERVALS: From 407 ft. to 447 ft., From 0 ft. to 0 ft. From 500 ft. to 535 ft., From 0 ft. to 0 ft. From 0 ft. to 0 ft., From 0 ft. to 0 ft. From 0 ft. to 0 ft., From 0 ft. to 0 ft. From 0 ft. to 0 ft., From 0 ft. to 0 ft. HATERIAL 03 BENTONITE Intervals: From 0 ft. to 20 ft., From 0 ft. to 0 ft. St he nearest source of possible contamination: 14 ABAND. WELL TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS 1 02 SILT 56 01 CLAY 68 05 SAND 04 SANDY CLAY 94 04 SANDY CLAY 05 SAND 20 LIMESTONE 237 05 SAND 11 GRAVEL 210 04 SANDY CLAY 211 04 SANDY CLAY 212 05 SAND 11 GRAVEL 213 05 SAND 11 GRAVEL 214 04 SANDY CLAY 215 05 SAND 11 GRAVEL

Water Well Contractor's License No. 145 This Water Well Record was completed on (mo/day/yr) 08/29/05 under the business name of HENKLE DRILLING & SUPPLY by (signature)

(Contin	ued)		V	ATER WELL RECO	RD Form WWC-	5 KSA 82a-1212		-1	
	N OF WATER 041 HASK		Fraction SE 1/4	SB 1/4 SW	1/4	Section Number 23	Township Number	Range Number R 34 K	
RR#, St	ELL OWNER: . Address, tate, ZIP	Box # :	HITCH FEEDERS 521 50TH ROAL SATANTA, KS)		Board of Agriculture, Division of Water Resources Application Number: 21,214			
FROM 289 302 314 328 346 357 397 407 417 432 437 500 507 512 524 527 530	TO 302 314 328 346 357 397 407 417 432 437 500 507 512 524 527 530 530	04 SAN 05 SAN 01 CLA 07 FIN 04 SAN 07 FIN 01 CLA 07 FIN 04 SAN 07 FIN 05 SAN 23 SAN 20 LIN	IE SAND 20 LIMI IDY CLAY 07 FII ID 20 LIMESTONI IY IE SAND 20 LIMI IDY CLAY 01 CLAY IE SAND 05 SAN IE SAND 08 MED: INDY CLAY 05 SAN IE SAND 08 MED: INDSTONE 28 ROCK INDSTONE	R 04 SANDY CLAY RSTONE 01 CLAY RY RD 28 ROCK RUM SAND RD 20 LIMESTONE					

⁷ CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was Constructed under my jurisdiction and was completed on (mo/day/year) 08/18/04 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 145

This Water Well Record was completed on (mo/day/yr) 08/29/05 under the business name of HENKLE DRILLING & SUPPLY

by (signature)