

1 LOCATION OF WATER WELL: County: GRANT	Fraction NW 1/4 NW 1/4 SE 1/4	Section Number 11	Township Number T 27 S	Range Number R 35 EW
---------------------------------------------------	--------------------------------------	--------------------------	-------------------------------	-----------------------------

Distance and direction from nearest town or city street address of well if located within city?

FROM ULYSSES, 12 EAST, 10 NORTH, 1 1/2 EAST, 1/2 NORTH INTO LOC.

2 WATER WELL OWNER: RON ENSZ.	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: 4120 N ROAD V	Application Number:
City, State, ZIP Code: ULYSSES, KS 67880	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 500 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. 238 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 238 ft. below land surface measured on mo/day/yr 2-9-95 Pump test data: Well water was 255 ft. after 1 hours pumping 90 gpm Est. Yield 90 gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter: 9 1/2 in. to 500 ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded
Blank casing diameter 5 in. to 500 ft., Dia			Threaded
Casing height above land surface 24 in., weight 2,902 lbs./ft. Wall thickness or gauge No. 280 SDR 21			
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	9 Drilled holes	
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS: From 360 ft. to 500 ft., From ft. to ft.			
GRAVEL PACK INTERVALS: From 340 ft. to 500 ft., From ft. to ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other HOLE PLUG
Grout Intervals: From ft. to ft., From ft. to ft., From ft. to ft.				
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
	2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage
	3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage
				13 Insecticide storage
				14 Abandoned water well
				15 Oil well/Gas well
				16 Other (specify below)

Direction from well?		How many feet?	
FROM	TO	FROM	TO
0	7	408	433
7	68	433	446
68	102	446	465
102	184	465	472
184	189	472	487
189	204	487	496
204	214	496	500
214	275		
275	285		
285	305		
305	315		
315	355		
355	368		
368	375		
375	408		

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2-9-95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. KWCL-430 This Water Well Record was completed on (mo/day/yr) 2-9-95 under the business name of HOWARD DRLG. CO. BOX 806 BEAVER, OK 73932 by (signature) <i>[Signature]</i>

INSTRUCTIONS: Use typewriter or ball point pen PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.