USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD KSA 82a-1201-1215

		1 1		
T	R	EW	sec 1/4	1/4 1/4 No.

Kansas State Dept. Of Health (Water Well Contractors) Forbes-Bldg. 740 Topeka, Kansas 66620

1 Location of well:	County	Township name	Fraction Center	SEL	Section	n number		Town number	Range number	
	Grant		Center	T	L			12/3	WCCN	
7 mi . N . , Street address of we	on from nearest town or cit 9 3/4 Mi . E . 11 location if in city:	of Ulysses & N.E. in fie	¼ mi. ld	3 Owner		S		McCormick , Kansas 6786	0	
Locate with "X" in section below: Sketch map:					X		II depth: <u>485</u> ft. De	ate of completion 1-23	-76	
*7 ₄ [1 1 1	<u>9 3</u>	/4 Mi.	East		2	5 🔲	Cable tool Rotary	Driven Dug Bored Reverse rotary	
Senter of SEL						6 Use: Domestic Public supply Industry X Irrigation Air conditioning Commercia Test well				
a i i i i i i i i i i i i i i i i i i i						7 Casing: Material Stee Height: above/b stow Threaded Welded Surface 12 in. Diam. Weigh 14 lbs./ft.				
2	1 Mile	<u> </u>	ysses	7	-		16	in. to 485 ft. depth D	rive shoe? Yes No	
	Тур	e and color of material			From	То	8 Scr	een:		1
Surface	& Fine Sand				0	15	Typ	nufacturer <u>Johnso</u> pe <u>Galvanized</u> o pt/g azz- 100x100 L	ia. 16 in.	
Fine San	nd		<u> </u>		15	60	Set	between 405 ft. and tings: * See Rema	£25_ ft	
Medium t	o Coarse Sand				60	28 5	Gre	avel pack 🔁 Yes 🗌 No :	Size range of material 15	down
Coarse S	and				285	425		tic water level: 20_ft. below land surface	Date 1-23-76	
Brown Clay with a Good 15' Strip of Sand				425	485	10 Pur 24	nping level below land surf 0 ft. after 2 hrs.	faces: pumping 000 g.p.m.		
	(465	- 480)					l <u> </u>	ft. after hrs.	pumping g.p.m.	
							_	ter sample submitted: Yes 🗷 No Date		
							12 We	Il head completion:	12 in. K Inches above grade	20
							K	Il grouted? X Yes Neat cement X Bentoni pth: From 0 ft. to	□ No te □	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \
	•						ft.	parest source of possible co Direction DOI	<u>ne in fÿeld</u>	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\
								anufacturer's nameGOI	Not installed 11 ds 12 200 Volts	
							Le Ty	ngth of drop pipe 300 f pe:	t. capacity1000g.m.p.	`
	(us	e a second sheet if needed)				-	Jet [
16 Remarks: eleva	i	ing Sub-Contra);				ater well contractor's certif] (
	Minter-Wilson Drilling Co. License #208					/ 208	1	is well was drilled under m port is true to the best of m	, ·	'
Topography: Garden City, Kansas 67846 ☑ Hill * Lakewood Perf Slot - 125 X 66 ☐ Slope Set Between 285' & 405' and 425' & 485'					1	K	I. Drilling siness name daress Box 669. U	Co., Inc. 263 License No. Lysses, Kan.	·	
Slope Upland	2et RetMe	en 205' & 409	o and 4	1 27' &	4 05'			gned M. Jack B. Authorized represe	Date 2-4-	76