USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD KSA 82a-1201-1215

	<u> </u>		
T	R	EW	sec 1/4 1/4 1/4 No.

Kansas State Dept. Of Health (Water Well Contractors) Forbes-Bldg. 740 Topeka, Kansas 66620

								•		
1 Location of well:	County	Township name	Fraction	Sectio	n number		Town number	Range number		
1 Location of Well:	Grant	NW 1/2 NE1/2 SE1/4		<u> </u>	35		T-27-\$	R-35-W		
Distance and direction from nearest town or city: 3 Owner of well:										
6 miles East-6 north and 4 west of Hickok Glen Kochn										
Locate with "X" in section below: Sketch map:				4		4 Well depth: <u>525</u> ft. Date of completion Well diameter <u>26</u> in.				
X/4 mile						5 Cable tool Rotary Driven Dug Hollow rod Jetted Bored X Reverse rotary				
W E NW4 NE 4 SE 4 Wickok 6 miles East						6 Use: Domestic Public supply Industry Irrigation Air conditioning Commercial				
Hickok 6 miles East						7 Casing: Material Size Height: above/betow Threaded Welded XISurface 12 in.				
S 1 Mile						Diam. Weight 34.25 bs./ft 16 in. to 525 ft. depth Drive shoe? Yes No				
2	Тур	e and color of material		From	То	in. to ft. depth				
Surface &	Brown Sandy	Clay		0	120	Manufacturer Johnson Type Galvanized Dia. 16 Slot/gazze 100x100 Length 40 Set between 380 ft. and 400 ft. 415-435 Fittings: See Remarks Gravel pack X Yes No Size range of material				
Sand				120	135					
	y & Brown San	dy Clay		135	165					
Sand				165	18 0	9 Static water level: 220_ft. below land surface Date 5/10/76				
Brown San	dy Clay			180	240	10 Pumping level below land surfaces: 240 ft. after 4 hrs. pumping 1200 g.p.m.				
Blue Clay				240	255	ft. after hrs. pumping g.p.m. Estimated maximum-yield 1800_ g.p.m.				
Sand				255	270	11 Water sample submitted:				
Blue Clay				270	285	12 Well head completion: Pitless adapter 12 Inches above grade				
Coarse Sand				285	405	13 Well grouted? K Yes No				
Sand fine to medium				405	435		Neat cement K Bentoni pth: From _O_ ft. to			
Brown & gray Clay				435	465	14 Ne ft.	earest source of possible co	Field Type		
Brown Caa	ıy			465	495		ell disinfected upon comple		1 6	
Brown & Gray Clay				495	506	15 Pump: Not installed Manufacturer's name Goulds Model number 14 M HP 150 Volts Length of drop pipe 300 ft. capacity 600 g.m.p. Type:				
Dakota & gray Clay				506	518					
Yellow chalk & Brown Clay				518	535			Turbine Reciprocating		
Blue Shal		e a second sheet if needed	-	535	540			Other	ļ (
16 Remarks: elevation Drilling Sub Contracted to Minter-Wilson Drilling.					17 Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.					
Topography: *Lakewood-slot 125x66 set between 280 to 380, Hill Kolope 400 to 415, 435 to 525.					K.I.Drilling Co., Inc. 263 Business name AddressBox 669 Ulysses, Ks.					
Upland						Signed M. Sance Barrelle Date 5/25/76 Authorized representative				

Forward the white, blue and pink copies to the Kansas State Dept. Of Health.

Form WWC-5