TOURITY. AZA COANT	raction				_	
jo	E 1/4 SE 1/4 SW 1/4	; 15	; 1 27 	S	; R 36	
istance and direction from near PPROX. 6.0 MILES EAST AND 7.0 M.	ILES NORTH OF ULYSSES.	s of well if locate	d within city?			
NATER WELL OWNER: DALE	CORLEYXERDENE CORLEY	D	A:14	n::-:f	Water Car	
R#, St. Address, Box # : 811 M	HONULIH	DUATU UI	Agriculture,	D141210U 01	water nest	Jurces
ity, State, ZIP code : GARDE	N CITY, KS 67846-	Applicat	ion Number: 4	,780 & 7,89	? 3	
OCATE WELL'S LOCATION WITH				2. 0	ft. 3.	0
NW NE	WELL'S STATIC WATER LEV	VEL 276 ft. below : Well water was				
	•	pm: Well water was	0 ft. afte	er O hou	rs pumping	0
1	:	74 :- :			0.71	
w ;;;	-; E ; Bore Hole Dlameter	24 in. to 5	01 ft., and	in. to	O Tt.	
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	WELL WATER TO BE USED F	S: 02 IRRIGATION				1
¦ S₩¦ SE	-1 1					
1 1 1 1	: : Was a chemical/bacterio					
<u>x</u>	: If yes, mo/day/yr samp	le was submitted		Water w	ell disinf	ected?
YPE OF BLANK CASING USED: 01 ST lank casing diameter 16 asing height above land surface YPE OF SCREEN OR PERFORATION MA	in. to 501 ft., Dia 12 in., weight 42 STERIAL: 01 STEEL	rs: welded in. to 0 ft.,		to 0 ft		*****
TYPE OF BLANK CASING USED: 01 ST Blank casing diameter 16 Casing height above land surface TYPE OF SCREEN OR PERFORATION MA SCREEN OR PERFORATION OPENINGS A	o in. to 501 ft., Dia 12 in., weight 42 MTERIAL: 01 STEEL MRE: 01 CONT, SLOT	TS: WELDED in. to 0 ft., lbs/ft. Wall thick	Dia in. Eness or gauge	to 0 ft		500 Sin
TYPE OF BLANK CASING USED: 01 ST Blank casing diameter 16 Casing height above land surface TYPE OF SCREEN OR PERFORATION MA SCREEN OR PERFORATION OPENINGS A	o in. to 501 ft., Dia 12 in., weight 42 STERIAL: 01 STEEL SRE: 01 CONT, SLOT From 322 ft. to 402	rs: WELDED in. to 0 ft., lbs/ft. Wall thick ft., From 491 ft.	Dia in. eness or gauge	to 0 ft		~ ~ ~ ~ ~ ~ ~
YPE OF BLANK CASING USED: 01 ST Slank casing diameter 16 Casing height above land surface YPE OF SCREEN OR PERFORATION MA CREEN OR PERFORATION OPENINGS A	in. to 501 ft., Dia 12 in., weight 42 NTERIAL: 01 STEEL NRE: 01 CONT, SLOT From 322 ft. to 402 From 455 ft. to 475	fs: WELDED in. to 0 ft., lbs/ft. Wall thick ft., From 491 ft., ft., From 0 ft.	Dia in. ness or gauge to 501 ft. to 0 ft.	to 0 ft		
YPE OF BLANK CASING USED: 01 ST lank casing diameter 16 asing height above land surface YPE OF SCREEN OR PERFORATION MA CCREEN OR PERFORATION OPENINGS A	From 322 ft. to 402 From 20 ft. to 501	rs: WELDED in. to 0 ft., lbs/ft. Wall thick ft., From 491 ft.	Dia in. ness or gauge to 501 ft. to 0 ft. to 0 ft.	to 0 ft		
TYPE OF BLANK CASING USED: 01 ST Blank casing diameter 16 Casing height above land surface TYPE OF SCREEN OR PERFORATION MA SCREEN OR PERFORATION OPENINGS A SCREEN PERFORATED INTERVALS: GRAVEL PACK INTERVALS: GROUT MATERIAL 03 BENTONITE Grout Intervals: From 0 ft. What is the nearest source of po	From 322 ft. to 402 From 455 ft. to 475 From 0 ft. to 0 From 0 ft. to 0 From 0 ft. to 0	fs: WELDED in. to 0 ft., lbs/ft. Wall thick ft., From 491 ft., ft., From 0 ft., ft., From 0 ft. ft., From 0 ft.	Dia in. ness or gauge to 501 ft. to 0 ft. to 0 ft.	to 0 ft No250		
YPE OF BLANK CASING USED: 01 ST lank casing diameter 16 asing height above land surface YPE OF SCREEN OR PERFORATION MA CREEN OR PERFORATION OPENINGS A CREEN PERFORATED INTERVALS: GRAVEL PACK INTERVALS: FROUT MATERIAL 03 BENTONITE FROUT Intervals: From 0 ft. What is the nearest source of popirection from well? SOUTH	From 322 ft. to 402 From 455 ft. to 475 From 0 ft. to 0 From 0 ft. to 0 From 0 ft. to 0	fs: WELDED in. to 0 ft., lbs/ft. Wall thick ft., From 491 ft., ft., From 0 ft., ft., From 0 ft. ft., From 0 ft.	Dia in. ness or gauge to 501 ft. to 0 ft. to 0 ft.	to 0 ft No250		eet?
YPE OF BLANK CASING USED: 01 ST lank casing diameter 16 asing height above land surface YPE OF SCREEN OR PERFORATION MA CREEN OR PERFORATION OPENINGS A CREEN PERFORATED INTERVALS: GRAVEL PACK INTERVALS: FROUT MATERIAL 03 BENTONITE irout Intervals: From 0 ft. What is the nearest source of popular control of the control o	in. to 501 ft., Dia 12 in., weight 42 PTERIAL: 01 STEEL PRE: 01 CONT, SLOT From 322 ft. to 402 From 455 ft. to 475 From 20 ft. to 501 From 0 ft. to 0 to 20 ft., From 0 ft Describe contamination: 04 LATE	in. to 0 ft., lbs/ft. Wall thick ft., From 491 ft., ft., From 0 ft., ft., From 0 ft. ft., From 0 ft. ft., From 0 ft.	Dia in. ness or gauge to 501 ft. to 0 ft. to 0 ft. to 0 ft.	to 0 ft No250	How many f	eet?
YPE OF BLANK CASING USED: 01 ST Flank casing diameter 16 Flasing height above land surface FOR SCREEN OR PERFORATION OPENINGS A FOREER PERFORATED INTERVALS: FROUT MATERIAL 03 BENTONITE FROUT Intervals: From 0 ft. What is the nearest source of popirection from well? SOUTH FROM TO O 2 01 CLAY O 2 04 SANDY CLAY	in. to 501 ft., Dia 12 in., weight 42 PTERIAL: 01 STEEL PRE: 01 CONT, SLOT From 322 ft. to 402 From 455 ft. to 475 From 20 ft. to 501 From 0 ft. to 0 to 20 ft., From 0 ft Describe contamination: 04 LATE	in. to 0 ft., lbs/ft. Wall thick ft., From 491 ft., ft., From 0 ft., ft., From 0 ft. ft., From 0 ft. ft., From 0 ft.	Dia in. ness or gauge to 501 ft. to 0 ft. to 0 ft. to 0 ft.	to 0 ft No250	How many f	eet?
YPE OF BLANK CASING USED: 01 ST Flank casing diameter 16 Flasing height above land surface FROM PERFORATION OPENINGS A FOREEN OR PERFORATION OPENINGS A FOREEN PERFORATED INTERVALS: FROUT MATERIAL 03 BENTONITE FROM To the nearest source of poping of the series of the	in. to 501 ft., Dia 12 in., weight 42 PTERIAL: 01 STEEL PRE: 01 CONT, SLOT From 322 ft. to 402 From 455 ft. to 475 From 20 ft. to 501 From 0 ft. to 0 to 20 ft., From 0 ft pssible contamination: 04 LATE LITHOLOGIC LOG	in. to 0 ft., lbs/ft. Wall thick ft., From 491 ft., ft., From 0 ft., ft., From 0 ft. ft., From 0 ft. ft., From 0 ft.	Dia in. ness or gauge to 501 ft. to 0 ft. to 0 ft. to 0 ft.	to 0 ft No250	How many f	eet?
YPE OF BLANK CASING USED: 01 ST Flank casing diameter 16 Flasing height above land surface FOR SCREEN OR PERFORATION OPENINGS ASSERTED INTERVALS: GRAVEL PACK INTERVALS: GRAVEL PACK INTERVALS: FROUT MATERIAL 03 BENTONITE FROM 1 TO 1 O 2 1 O1 CLAY O 2 1 O1 CLAY O 1 O4 SANDY CLA 16 87 05 SAND 01 CL 87 1 09 04 SANDY CLA	in. to 501 ft., Dia 12 in., weight 42 FERIAL: 01 STEEL RE: 01 CONT, SLOT From 322 ft. to 402 From 455 ft. to 475 From 20 ft. to 501 From 0 ft. to 0 to 20 ft., From 0 ft pssible contamination: 04 LATE LITHOLOGIC LOG AY 07 FINE SAND CLAY AY 05 SAND	in. to 0 ft., lbs/ft. Wall thick ft., From 491 ft., ft., From 0 ft., ft., From 0 ft. ft., From 0 ft. ft., From 0 ft.	Dia in. ness or gauge to 501 ft. to 0 ft. to 0 ft. to 0 ft.	to 0 ft No250	How many f	eet?
YPE OF BLANK CASING USED: 01 ST Flank casing diameter 16 Flasing height above land surface FOR SCREEN OR PERFORATION OPENINGS ASSERTED INTERVALS: GRAVEL PACK INTERVALS: GRAVEL PACK INTERVALS: GROUT MATERIAL 03 BENTONITE FROM I TO I O I 2 OI CLAY O I 2 OI CLAY O I 2 OF SAND OF CASING INTERVALS O I 2 OF CLAY O I 16 OF SAND OF CASING INTERVALS O I 109 OF SAND OF CASING INTERVALS O I 2 OF CLAY O I 2 OF CLAY O I 2 OF CLAY O I 109 OF SAND OF CLAY	in. to 501 ft., Dia 12 in., weight 42 RE: 01 STEEL RE: 01 CONT, SLOT From 322 ft. to 402 From 455 ft. to 475 From 20 ft. to 501 From 0 ft. to 0 to 20 ft., From 0 ft Dissible contamination: 04 LATE LITHOLOGIC LOG AY 07 FINE SAND GRAVEL 01 CLAY	in. to 0 ft., lbs/ft. Wall thick ft., From 491 ft., ft., From 0 ft., ft., From 0 ft. ft., From 0 ft. ft., From 0 ft.	Dia in. ness or gauge to 501 ft. to 0 ft. to 0 ft. to 0 ft.	to 0 ft No250	How many f	eet?
YPE OF BLANK CASING USED: 01 ST Clank casing diameter 16 Casing height above land surface TYPE OF SCREEN OR PERFORATION MARKEREN OR PERFORATION OPENINGS A CORREEN PERFORATED INTERVALS: GRAVEL PACK INTERVALS: GROUT MATERIAL 03 BENTONITE Grout Intervals: From 0 ft. What is the nearest source of popirection from well? SOUTH FROM TO 0	in. to 501 ft., Dia 12 in., weight 42 RE: 01 STEEL RE: 01 CONT, SLOT From 322 ft. to 402 From 455 ft. to 475 From 20 ft. to 501 From 0 ft. to 0 to 20 ft., From 0 ft Dissible contamination: 04 LATE LITHOLOGIC LOG AY 07 FINE SAND GRAVEL 01 CLAY	in. to 0 ft., lbs/ft. Wall thick ft., From 491 ft., ft., From 0 ft., ft., From 0 ft. ft., From 0 ft. ft., From 0 ft.	Dia in. ness or gauge to 501 ft. to 0 ft. to 0 ft. to 0 ft.	to 0 ft No250	How many f	eet?
TYPE OF BLANK CASING USED: 01 ST Blank casing diameter 16 Casing height above land surface TYPE OF SCREEN OR PERFORATION MARKEREN OR PERFORATION OPENINGS A SCREEN PERFORATED INTERVALS: GRAVEL PACK INTERVALS: GROUT MATERIAL 03 BENTONITE Grout Intervals: From 0 ft. What is the nearest source of popirection from well? SOUTH FROM : TO : 0 : 2 : 01 CLAY 2 : 16 : 04 SANDY CLA 16 : 87 : 05 SAND 01 CLA 109 : 134 : 05 SAND 11 CLA 109 : 134 : 05 SAND 11 CLA 134 : 143 : 04 SANDY CLA 143 : 146 : 05 SAND	in. to 501 ft., Dia 12 in., weight 42 PTERIAL: 01 STEEL PRE: 01 CONT, SLOT From 322 ft. to 402 From 455 ft. to 475 From 20 ft. to 501 From 0 ft. to 0 At 20 ft., From 0 ft DITHOLOGIC LOG AY 07 FINE SAND CLAY AY 05 SAND GRAVEL 01 CLAY AY 05 SAND	in. to 0 ft., lbs/ft. Wall thick ft., From 491 ft., ft., From 0 ft., ft., From 0 ft. ft., From 0 ft. ft., From 0 ft.	Dia in. ness or gauge to 501 ft. to 0 ft. to 0 ft. to 0 ft.	to 0 ft No250	How many f	eet?
TYPE OF BLANK CASING USED: 01 ST Blank casing diameter 16 Casing height above land surface TYPE OF SCREEN OR PERFORATION MARKEREN OR PERFORATION OPENINGS A SCREEN PERFORATED INTERVALS: GRAVEL PACK INTERVALS: GRAVEL PACK INTERVALS: GROUT MATERIAL 03 BENTONITE Grout Intervals: From 0 ft. What is the nearest source of popirection from well? SOUTH FROM	in. to 501 ft., Dia 12 in., weight 42 PTERIAL: 01 STEEL PRE: 01 CONT, SLOT From 322 ft. to 402 From 455 ft. to 475 From 20 ft. to 501 From 0 ft. to 0 At 20 ft., From 0 ft DITHOLOGIC LOG AY 07 FINE SAND CLAY AY 05 SAND GRAVEL 01 CLAY AY 05 SAND	in. to 0 ft., lbs/ft. Wall thick ft., From 491 ft., ft., From 0 ft., ft., From 0 ft. ft., From 0 ft. ft., From 0 ft.	Dia in. ness or gauge to 501 ft. to 0 ft. to 0 ft. to 0 ft.	to 0 ft No250	How many f	eet?
TYPE OF BLANK CASING USED: 01 ST Blank casing diameter 16 Casing height above land surface TYPE OF SCREEN OR PERFORATION MARK SCREEN OR PERFORATION OPENINGS A SCREEN PERFORATED INTERVALS: GRAVEL PACK INTERVALS: GRAVEL PACK INTERVALS: GROUT MATERIAL 03 BENTONITE Grout Intervals: From 0 ft. What is the nearest source of popurection from well? SOUTH FROM	in. to 501 ft., Dia 12 in., weight 42 PTERIAL: 01 STEEL PRE: 01 CONT, SLOT From 322 ft. to 402 From 455 ft. to 475 From 20 ft. to 501 From 0 ft. to 0 At 20 ft., From 0 ft DITHOLOGIC LOG AY 07 FINE SAND CLAY AY 05 SAND GRAVEL 01 CLAY AY 05 SAND	in. to 0 ft., lbs/ft. Wall thick ft., From 491 ft., ft., From 0 ft., ft., From 0 ft. ft., From 0 ft. ft., From 0 ft.	Dia in. ness or gauge to 501 ft. to 0 ft. to 0 ft. to 0 ft.	to 0 ft No250	How many f	eet?
TYPE OF BLANK CASING USED: 01 ST Blank casing diameter 16 Casing height above land surface TYPE OF SCREEN OR PERFORATION MARK SCREEN OR PERFORATION OPENINGS A SCREEN PERFORATED INTERVALS: GRAVEL PACK INTERVALS: GROUT MATERIAL 03 BENTONITE Grout Intervals: From 0 ft. What is the nearest source of popurection from well? SOUTH FROM TO 0	in. to 501 ft., Dia 12 in., weight 42 PTERIAL: 01 STEEL PRE: 01 CONT, SLOT From 322 ft. to 402 From 455 ft. to 475 From 20 ft. to 501 From 0 ft. to 0 The state of the state	in. to 0 ft., lbs/ft. Wall thick ft., From 491 ft., ft., From 0 ft., ft., From 0 ft. ft., From 0 ft. ft., From 0 ft.	Dia in. ness or gauge to 501 ft. to 0 ft. to 0 ft. to 0 ft.	to 0 ft No250	How many f	eet?

Water Well Contractor's License No. 145

This Water Well Record was completed on (mo/day/yr) 05/27/92

under the business name of HENKLE DRILLING & SUPPLY

by (signature)

The let

COUNTY:	034 GRANT	; SE	1/4 SE	1/4 SW	1/4	; Section Number ; 15	T 27		; Range Numbe ; R 36 W	?r
	L OWNER: Address, Box			CORLEY		Board of A	Agriculture, Di	vision of	f Water Resource	25
City, Sta	State, ZIP code : GARDEN CITY, KS 67846- Application Number: 4,780 & 7,893							393		
FROM : 274 : 280 : 289 : 317 : 322 : 330 : 336 : 343 : 351 : 366 : 402 : 457 : 465 : 474 : 483 : 1	TB : 280 : 05 289 : 04 317 : 07 322 : 04 330 : 05 336 : 05 343 : 04 351 : 07 366 : 05 402 : 05 457 : 04 465 : 05 474 : 23 483 : 15 491 : 15 498 : 25	5 SAND 4 SANDY CLAY 7 FINE SAND CLAY 5 SAND 28 ROC 5 SAND 4 SANDY CLAY 7 FINE SAND CLAY 7 FINE SAND CLAY 5 SAND 28 ROC 5 SAND 28 ROC 5 SAND 28 ROC 6 SAND 27 FINE SAND CLAY 7 SAND 13 FINE 8 SAND 13 FINE 9 SHALE 20 L1	LITHOLOGIC 05 SAND 8 MEDIUM SE K 05 SAND 8 MEDIUM SE K K 13 FINE 05 SAND 16 GRAVEL 2 19 SHALE MIDSTONE (MESTONE 19 SHALE	E LOG AND 01 CLAY AND 01 CLAY		Application	on Number: 4,	780 & 7,8	393	

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was Constructed under my jurisdiction and was completed on (mo/day/year) 02/26/92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 145

This Water Well Record was completed on (mo/day/yr) 05/27/92

under the business name of HENKLE DRILLING & SUPPLY

(signature) Dougla R. Harple