
USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD KSA 82a-1201-1215



Kansas State Dept. Of Health (Water Well Contractors) Forbes-Bldg. 740 Topeka, Kansas 66620

										_
1 1	County	Township name Fraction			Section number			Town number	Range number]
1 Location of well:	Grant							T27S	R36W	
Distance and direction from nearest town or city: 6 mi. North, 5 mi East, 1 3/4 Mi. North & Street address of well location if in city: 1/2 mi. West of Ulysses						ess: Edna B. Petro 4712 W. 6th, Apt. 262 Topeka, Kansas 66606				
Locate with "X" in section below: Sketch map:						Ť	•		Date of completion 1-25	-75
CNE ¹ 4								diameter _26_ in.	7.	1
							5 Cable tool Rotary Driven Dug Hollow rod Jetted Bored Reverse rotary			
3/1						l		: Domestic Publi		1
w € <u>5 mi • E • </u>] _									onditioning 🔲 Commercial	
						ŀ	7 Cas	ing: Material Steel	Height: above	1
							Thr	eaded Welded X	Surface 12 in.	
S S III Veses							Die _C	m. 1611 Lip. to 420 ft. depth	Weight 344 lbs./ft Drive shoe? ☐ Yes 🕱 No	
2						To		_ in. to ft. depth		
Type and color of material					From		8 Scr		con	
Surface & Fine Sand					0	15		nufacturer <u>John</u> e <u>Galvanized</u>		
Fine Sand					15	75	Slo	1/90020 100x100	Length <u>20'</u> 370 ft. 50 1b。p	
					. 13		Fit	rings: 🥸 See Rem	arks '	1.
Brown Clay					75_	90_			Size range of material	down
Sand					90	105		tic water level: 4 ft. below land surface	e Date 1-30-75	
Brown Clay					105	135	10 Pur	nping level below land su 15 ft. after2 hrs	rfaces: . pumping 1300g.p.m.	
Blue Clay					135	195	_		. pumping g.p.m.	
Fine Sand & Clay Strips					195	210	11 Wa	ter sample submitted:		1
Blue Clay					210	225			1 211	1
Fine Sand					225	240			1 211 Inches above grade	4
Fine Sand								Il grouted? 🗶 Yes Neat cement 🔀 Bentor	☐ No nite ☐	.]
Blue Clay					240	260	Dep	oth: FromO_ft. to	10_ft.	1
Sand - Med. to Fine					260	300	ft.	Direction	ontamination: in fie	1
Brown Clay					300	315	We	II disinfected upon comp	etion? Yes X No	-
Coarse Sand					315	385		nufacturer's name	Not installed	
								odel number <u>used</u>	HP 150 Volts	
Brown Sandy Clay 20%					385	420	Ty	pe:		
Brown Clay & Lava Rock					420	465	. =	Submersible Jet	Turbine Reciprocating	
Brown Caay & Blue Shale second in print needed)					465	480		Certrifugal	Other	
16 Remarks: elevation Drilling Sub-contracted to:								ter well contractor's cert		
Minter-Wilson Drilling Co. Licens						#208		s well was drilled under r ort is true to the best of i	ny jurisdiction and this ny knowledge and belief.	
Topography: Garden City, Kn. 67846						K. I. Drilling Co.				
★ Lakewood Perf Slot125 X 66 Set between 260' & 350'							Bus An	iness name	License No.	
□ Upland and 370' to 420'							l	aned Som	1 -27.	75
Volley								Authorized repre	eniative -	1