VATER WELL REC	CORD	Form WWC	C- 5	Division of V	Water Resources; App. No.	25,941
1 LOCATION OF WA	w	Fraction		Section Number	er Township Number	Range Number
County: Grant	from nearest town or c	SE 1/4 SE 1/4		12 Clobal Position	T 27 S ning Systems (decimal d	R 36 EW
located within city?		- 2 miles eas				
10 miles north, 2,975 ft. west & 140 ft. north				Latitude:		
2 WATER WELL OW RR#, St. Address, Box	•	arms LC-Mel Cr	ist	Elevation: _		
City, State, ZIP Code		Antler Ridge ity, KS 67846		Datum:		
3 LOCATE WELL'S	4 DEPTH OF COM	•	445	Data Collecti		
LOCATION	4 DEI III OI COM	I DETER WEEE				
WITH AN "X" IN	Depth(s) Groundwater	Encountered (1)		ft. (2)	ft. (3)	ft.
SECTION BOX:					face measured on mo/da hours pumping	
					hours pumping	
NW NE	WELL WATER TO E	BE USED AS: 5 Pu	blic water s	supply 8	Air conditioning 11 In	njection well
V E						Other (Specify below)
	(2) Irrigation 4 Inc	iustriai / Domes	stic (lawn c	x garden) 10 i	Monitoring well .	
SW SE	Was a chemical/bacter	riological sample sul	mitted to	Department? Y	es No X ;	If yes, mo/day/yrs
<u> </u>	Sample was submitted	l	Wate	er well disinfect	ed? Yes No?	K
S						
TYPE OF CASING U	SED: 5 Wrought P (SR) 6 Asbestos	Iron 8 Con	ncrete tile	below)	SING JOINTS: Glued	Clamped
2 PVC 4 ABS		s			Thread	
Blank casing diameter						
Casing height above land			.05	lbs./ft. Wall	thickness or guage No.	. 250
TYPE OF SCREEN OR I			9.4	ARS	11 Other (Specify	`
	vanized Steal 6 Cond					
SCREEN OR PERFORA	TION OPENINGS ARI	E:	,		` -	
1 Continuous slot	3Mill slot	Gauzed wrapped 7	Torch cut	9 Drilled ho	oles 11 None (open ecify)	hole)
2 Louvered snutter SCREEN-PERFORATEI	4 Key punched 6 V	vire wrapped 8	Saw Cut 445	10 Otner (sp	ecity) ft to	ft
GRAVEL PACK	INTERVALS: From.	20 ft. to	260	ft., Fron	n ft. to n ft. to	445 ft.
	From.	ft. to		ft., Fron	n ft. to	ft.
GROUT MATERIAL	: 1 Neat cement (2)	Cement grout 3 B	entonite	4 Other		
			260	ft. to 320	ft., From	ft. toft.
What is the nearest source			10 Livest	a als mana 13	Incasticida Staroga	16 Other (specify
1 Septic tank 2 Sewer lines	4 Lateral lines 5 Cess pool	8 Sewage lagoon	10 Liveste 11 Fuel st	-	3 Insecticide Storage 4 Abandoned water well	` •
3 Watertight sewer					5 Oil well/gas well	,
Direction from well?						
ROM TO	LITHOLOGIC	CLOG	FROM	TO	PLUGGING IN	ΓERVALS
					A. Vella	
	See attached	log				
CONTRACTOR'S OF	R LANDOWNER'S C	ERTIFICATION:	This water	well was (1) co	onstructed, (2) reconstru	cted, or (3) plugged
under my jurisdiction and	was completed on (mo	/day/year)5-16-	08 and	this record is t	rue to the best of my know	owledge and belief.
Kansas Water Well Contr					eted on (mo/day/year) . AOra Kellen	
under the business name of INSTRUCTIONS: Use typew	riter or ball point pen. PLE	ASE PRESS FIRMLY and	PRINT clear	rly. Please fill in b	lanks, underline or circle the	correct answers. Send to
hree copies to Kansas Departm	ent of Health and Environme	ent, Bureau of Water, Geo	logy Section	, 1000 SW Jackson	St., Suite 420, Topeka, Kans \$5.00 for each construct	as 66612-1367. Telephon
http://www.kdheks.gov/waterwe		TEX and retain one	ioi youi it	cords. Tee of	45.00 for each construc	wen. visit us d

MINTER-WILSON DRILLING CO. Water Systems Complete Installation

Irrigation and Domestic and Repairing

INCORPORATED

Phone 276-8269 P.O. Box A **GARDEN CITY, KANSAS 67846**

Corley Farms Grant County 12-6-07

Location: SW 12-27-36 - Lakin Lane - South to the county line, 1 mile south, 3 miles east, 1 mile south, $\frac{1}{2}$ mile west, 333 ft. west & 150 ft. north

Static Water Level 290 ft.

Test #3

- 2' Top soil
- 7' Brown clay
- 7' to 94' Brown sandy clay
- 94' to 124' Brown clay small streak of gravel
- 124' to 134' Fine to medium sand & gravel
- 134' to 192' Fine to medium sand & gravel some coarse
- 192' to 198' Fine to medium sand & gravel-coarse rock cemented
- 198' to 249' Fine to medium sand & gravel some coarse
- 249' to 254' Brown clay
- 254' to 279' Fine to medium sand & gravel
- 279' to 290' Brown sandy clay
- 290' to 307' Fine to medium sand & gravel
- 307' to 330' Brown clay
- 330' to 401' Fine to medium sand & gravel
- 401' to 430' Brown clay sticky
- 430' to 438' Yellow clay and brown rock and sand stone mix
- 438' to 439' Sand stone hard pull down
- 439' to 445' Yellow clay 445' to 460' Gray shale
- 460' to 470' Red bed