					Hollma	n ATI) Wi	<u>/</u>	
WATE	R WELI	RECORD	Form WWC	C- <b>5</b>	Division of Wat	er Resources; App. No	20080326	
		F WATER WELL:	Fraction		Section Number			
	ity: Gra	nt rection from nearest town or ci	NE 1/4 NE 1/4 1		9 Clabal Basitiania	T 27 S	R 36 EW legrees, min. of 4 digits)	
	ed within c		o/t, 1W on Hit	ch				
Feeders Rd., 2.8N & W into w/w					Latitude: Longitude:			
		L OWNER: OXV USA IT	nc. Hoffman A	TU "K"	Ælevation:			
	, St. Addre	ss, Box # : P.O. Box 2			Datum:			
	, State, ZIF	Addison, I	TX 75001-2768		Data Collection Method:			
	3 LOCATE WELL'S 4 DEPTH OF COMPLETED WELL							
	LOCATION WITH AN "X" IN Depth(s) Groundwater Encountered (1)27.6 ft. (2) ft. (3)							
1	SECTION BOX: WELL'S STATIC WATER LEVEL276 ft. below land surface measured on mo/day/yr8/03/4							
N Pump test data: Well water was286ft. after1 hours pumping							g 100 gpm	
	Est. Yield 100gpm: Well water was							
	WELL WATER TO BE USED AS: 5 Public water supply  8 Air conditioning 11 Injection well  1 Domestic 3 Feedlot 6 Oil field water supply  9 Dewatering 12 Other (Specify below							
w		1 L5 1						
	SW SE   W							
Sample was submitted								
c TVDI	S	INC HEED. 5 Wassale	I 9 Can	4:1.	CACIN	IC IODITC: Cl1	Y C11	
		ING USED: 5 Wrought 3 RMP (SR) 6 Asbestos-	Cement 9 Other	crete tile er (specify	below)		X Clamped	
1 _	1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded							
Blank ca	asing diam	eter6 in. to320	ft., Diameter	i	n. to ft	., Diameter	in. toft.	
		e land surface24		704	lbs./ft. Wall th	ickness or guage No	SDR.21.316	
TYPE OF SCREEN OR PERFORATION MATERIAL:								
1 Steel 3 Stainless Steel 5 Fiberglass								
2 Brass 4 Galvanized Steal 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE:								
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 7 Torch cut 9 Drilled holes 11 None (open hole)								
2 Louvered shutter 4 Key punched 6 Wire wrapped Saw cut 10 Other (specify)								
SCREEN-PERFORATED INTERVALS:         From								
GRAVEL PACK INTERVALS: From200								
From								
( CDO	TITE NA A TEL	EDIAL ONLAS ASSESSED 2	Compant amount 2 B	amtamita (	10than hole	nlug		
Grout Ir		ERIAL: ONeat cement 2 From .1 ft. to	Cement grout 3 B	entonite	ft to	ft From	ft to ft	
		source of possible contaminat			11. 10	10., 1 10111		
	Septic tank	4 Lateral lines	7 Pit privy	10 Livest	ock pens 13 Ir	secticide storage	16 Other (specify	
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 14 Abandoned water well below)								
		sewer lines 6 Seepage pit						
FROM	TO	ll?East LITHOLOGIO		FROM		PLUGGING IN		
0	3	Surface	200	TROM	10	TECCONTO II	(TERVILE)	
3	43	Sandy Clay						
43	197	Sand						
197	200	Sand & Clay Streaks	Blue					
_200	215	Clay Blue						
215	320	Sand & Clay Streaks						
320	400	Sand & Clay Blue						
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, (2) reconstructed, or (3) plugged								
under my jurisdiction and was completed on (mo/day/year) 8/03/08 and this record is true to the best of my knowledge and belief.								
Kansas Water Well Contractor's License No. KWWCL. 430 This Water Well Record was completed of (mo/day/year) 8/103/08 under the business name of Howard Drilling Box 806 Beaver, Okby (signature)								
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in branks, underlike of circle the gorrect answers. Send top								
three copi	es to Kansas	Department of Health and Environment	nt, Bureau of Water, Geo	logy Section	, 1000 SW Jackson St.	, Suite 420, Topeka, Kan	sas 66612-1367. Telephone	
785-296-5 http://www		l one to WATER WELL OWN /waterwell/index.html.	en and retain one	or your re	corus. ree oi \$3	o.00 for each constru	<u>cted</u> well. Visit us a	