WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

| | | | | | | | aka, kalisas 000 | 20 | |
|--|----------|---------------------------------------|-----|--|---|---|--------------------|------------------------|--|
| 1. Location of well: | County | Fraction | | Section | number | Township number | Range number | · | |
| | Stanton | NW 1/4 NW 1/4 | SW4 | | 30 | т 27 s | _R 39 | E/W | |
| | | | | | ner of well: Carson Floyd | | | | |
| Service station at Ulysses 15 miles west, R.R. or street | | | | | itreet: 6538 East Exter | | | | |
| O'2 HOTCH City, state, zip o | | | | | code: Sc | "Scottsdale, Ariz. 85251 | | | |
| 4. Locate with "X" in section below: Sketch map: | | | | | | 6. Bore hole dia. 27 in . Completion date | | | |
| N N | | | | | | Well dep 631.1 ft. 3-6-76 | | | |
| | | | | | | 7 Cable tool X_ Rotary Driven Dug | | | |
| NW NE | | | | | | Hollow rod Jetted Bored Reverse rotary | | | |
| | | | | | | 8. Use: Domestic Public supply Industry | | | |
| 1. 1 1 1 1 | | | | | | X Irrigation Air conditioning Stock Lawn Oil field water Other | | | |
| SW SE | | | | | | Lawn Oil field water Other 9. Casing: Material St 1 Height: Above or below Threaded Welded Surface 12 in. | | | |
| | | | | | | | | | |
| S | | | | | | RMP PVC Weight 42.5 lbs./fr. | | | |
| I < 1 Mile | | | | | | Dia. 16 in. to 254 ft. depth Wall Thickness: inches or | | | |
| 5. Type and color of | material | | | From | То | Dia in. to ft. dep | th gage No | .250 | |
| CC | _ | · · · · · · · · · · · · · · · · · · · | | 0 | 2 | 10. Screen: Manufacturer's r Pipe of Texa | | | |
| Surfac | ;e | | | | | | _ Dia | 16" | |
| Sandy clay | | | | 2 | 93 | Slot/gauze 3/16 | | 77.1' | |
| - Januy Clay | | | | | | Set betweenft. andft. | | | |
| Brown and gray clay | | | | 93 | 135 | Gravel pack? X Size range of material 2 X 5/8 | | | |
| Sandy clay w/sand strips | | | | 135 | 218 | 11. Static water level: mo./day/yr. 81 4 ft. below land surface Date 2-24-76 | | | |
| | | | | | | | | | |
| Sandy clay w/sand strips 2-2 | | | | 218 | 242 | 12. Pumping level below land surfaces: 265. ft. after 63. &rs. pumping 1400 g.p.m. | | | |
| Coarse sand 17 ft | | | | 242 | 259 | ft. after hrs. pumping g.p.m. | | | |
| Fine to medium sand w/clay breakers | | | | 259 | 277 | 13. Water sample submitted: mo./day/yr. | | | |
| Yellow chalk, gray clay & loose sandstone | | | | 277 | 353 | Yes Y No Date | | | |
| | | | | 252 | 371 | 14. Well head completion: NA | | | |
| Red, gray & yellow clay w/tightstrips of sandsto | | | | ness | 3/1 | | | | |
| Rtue Shale | | | | 371 | 405 | | | | |
| Blue shale w/sandstone strips lost circulation | | | | 405 | 478 | 16. Nearest source of possible contamination: | | | |
| Shale & sandstone | | | | 478 | 535 | ft Direction TypeNA Well disinfected upon completion? Yes No | | | |
| Cheyenne sandstone | | | | 535 | 632 | 17. Pump: X Not installed | | | |
| oney come canadecine | | | | | | Manufacturer's name Model number | HP | _ Volts | |
| | | | | | | Length of drop pipe | | | |
| | | | | | | Type: Submersible | | whine | |
| | | | | | | Jet | | urbine eciprocating | |
| (Use a second sheet if needed) | | | | | | Centrifugal | | other | |
| 18. Elevation: 19. Remarks: | | | | | | 20. Water well contractor's certification: | | | |
| | | | | | This well was drilled under my jurisdiction and this report | | | • | |
| Tapography: | | | | | is true to the best of my knowledge and belief. | | | | |
| Hill | | | | | | Houck Bros Dr. | Lg. Co. | 164 | |
| X Slope | | | | | | Address Box 487, | Jlysses, | License No. KS. | |
| Upland | | | | | | Signed M. Bear | | Date 4-30- | |
| Valley | | | | | | Authorized rep | resentative | | |