WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Taneka, Kansas 66620

				Topeka, Karsas 00020						
1. Location of well:	County	Fraction		Section number		. Township number		Ran	ge number	
	Stanton	SE 1/4 SE 1/4 SE		8		т 27	S	R	40	E/W
					er of well: Archie Nairn					
1 S., of Hwy Jct., at Johnson, Ks. R.R. or				street:		Johnson, Ks. 67855				
City, ste					code:					
4. Locate with "X" in section below: Sketch map:						6. Bore hole dia. 27 in. Completion date Well depth 571. Gt. 10/30/76				
						7 Cable tool X Rotary Driven Dug Hollow rod Jetted Bored Reverse rotary				
						8. Use: Domestic Public supply Industry X Irrigation Air conditioning Stock				
f						Lawn Oil field water Other				
5W SE						9. Casing: Material S	teel	Hei	aht Above or	below
<u> </u>						Threaded				
S !→ 1 Mîle										
5. Type and color of material					То	Dia. 16 in. to 440 rl. Lepth Wall Thickness: inches or Diain. to ft. depth gage No 219				
J. Type and color of				From		10. Screen Manufact				ood
]				4 4 4 4 4	
Surface					2	Type Steel		_ Dia	16"	71
Very fine sand & clay breakers				2	30	Slot/gauze 3/16 Set between 240				
Walium to compa and				70	61		ft.ar	nd		ft.
Medium to coarse sand				30	61	Gravel pack? X Size range of material 4 X 5/8				
Brown, gray and sandy clay w/very fine strips				61	208	11. Static water level: mo./day/yr99ft. below land surface Date				
Medium to coarse sand w/lime shells				208	227	12. Pumping level balg	24 land	surfac	ces: mping 195	0 0 0 0 0
Sandy clay w/very fine sand strips				227	242	12. Pumping level below land surfaces: 240ft. after hrs. pumping 1250 g.p.m ft. after hrs. pumping g.p.m.				
						Estimated maximum yie		300	0	g.p.m.
Very fine to medium sand					268	13. Water sample subm			me	o./day/yr.
Sandrock, brown shale & yellow chalk					311	Yes X N		ate _		
				311		14. Well head complet Pitless adapter	ion:		NA _ Inches above	e orode
Blue & brown shale & Dakota					384	15. Well grouted?				- St and
Blue & brown shale & Dakota					402	With: Neat cement X Bentonite Concrete				Concrete
					402	Depth: From 0				
Rock				402	403	16. Nearest source of				NA
False red bed, blue & brown shale & Dakota				403	464	ft Direction Well disinfected upon				
						17. Pump:			Not installed	
Blue shale, gray clay, Cheyenne & Dakota			464	507	Manufacturer's name _					
Blue shale, gray clay, Cheyenne & Dakota			507	522	Model number Length of drop pipe			sanasity		
Blue shale, Gray clay, Cheyenne & Dakota w/ 4				522		Type:		- 1T.	сарасту	—g.p.m.
ft. tight and/strip			322	3/1	Submersible			Turbia		
(Use a second sheet if needed)						Jet Centrifugal			Recip	rocating
18 Flaustian. 19 Parambr.							ntaria co	nedi El -		
4 1 1 1 1 1 1 1 1 1						20. Water well contractor's certification: This well was drilled under my jurisdiction and this report				
Topography: Hill as soon as corn isket.						is true to the best of my knowledge and belief.				
Hill as soon as corn is let.						Houck Bros. Drlg. Co. 164				
X Slope						Business name Box 487, Ulysses, License No. Address				
Upland	i						M.	Ba	ad	10/2
Valley		•				Signed	ad rang	esen in	Date	وحجع