ATER WELL OWNER: H & C FA	
R#, St. Address, Box # : RT. 1	RMS Board of Agriculture, Division of Water Resources
•	
ity, State, ZIP code : JOHNSON,	KS 67855- Application Number: 19,180
	4 DEPTH OF COMPLETED WELL 603 ELEVATION: 0
N "X" IN SECTION BOX:	Depth(s) Groundwater Encountered 1. 0 ft. 2. 0 ft. 3. 0 ft
	Pump testdata: Well water was 326 ft. after 4 hours numning 1523 on
NW	
	Estimated Yield O gpm: Well water was O ft. after O hours pumping O gp
W	E 'Bore Hole Diameter 24 in. to 604 ft., and in. to 0 ft.
! ! ! ! ! ! ! ! ! ! ! ! ! ! ! ! ! ! !	WELL WATER TO BE USED AS: 02 IRRIGATION ;
	; Was a chemical/bacteriological sample submitted to department? No ;
	: If yes, mo/day/yr sample was submitted Water well disinfected? No
lank casing diameter 16 in asing height above land surface /PE OF SCREEN OR PERFORATION MATER CREEN OR PERFORATION OPENINGS ARE:	01 CONT. SLOT From 250 ft. to 290 ft., From 310 ft. to 390 ft.
lank casing diameter 16 in asing height above land surface YPE OF SCREEN OR PERFORATION MATER CREEN OR PERFORATION OPENINGS ARE: CREEN PERFORATED INTERVALS: GRAVEL PACK INTERVALS:	. to 603 ft., Dia in. to 0 ft., Dia in. to 0 ft. 12 in., weight 42 lbs/ft. Wall thickness or gauge No250 IAL: 01 STEEL 01 CONT. SLOT From 250 ft. to 290 ft., From 310 ft. to 390 ft. From 290 ft. to 310 ft., From 390 ft. to 480 ft.
lank casing diameter 16 in asing height above land surface YPE OF SCREEN OR PERFORATION MATER CREEN OR PERFORATION OPENINGS ARE: CREEN PERFORATED INTERVALS: GRAVEL PACK INTERVALS: ROUT MATERIAL 02 CEMENT GROUT	. to 603 ft., Dia in. to 0 ft., Dia in. to 0 ft. 12 in., weight 42 lbs/ft. Wall thickness or gauge No250 IAL: 01 STEEL 01 CONT. SLOT From 250 ft. to 290 ft., From 310 ft. to 390 ft. From 290 ft. to 310 ft., From 390 ft. to 480 ft. From 20 ft. to 300 ft., From 0 ft. to 0 ft. From 0 ft. to 0 ft., From 0 ft. to 0 ft.
lank casing diameter 16 in asing height above land surface YPE OF SCREEN OR PERFORATION MATER CREEN OR PERFORATION OPENINGS ARE: CREEN PERFORATED INTERVALS: GRAVEL PACK INTERVALS: ROUT MATERIAL 02 CEMENT GROUT rout Intervals: From 0 ft. to hat is the nearest source of possi	. to 603 ft., Dia in. to 0 ft., Dia in. to 0 ft. 12 in., weight 42 lbs/ft. Wall thickness or gauge No250 IAL: 01 STEEL
lank casing diameter 16 in asing height above land surface YPE OF SCREEN OR PERFORATION MATER CREEN OR PERFORATION OPENINGS ARE: CREEN PERFORATED INTERVALS: GRAVEL PACK INTERVALS: ROUT MATERIAL 02 CEMENT GROUT rout Intervals: From 0 ft. to hat is the nearest source of possi	. to 603 ft., Dia in. to 0 ft., Dia in. to 0 ft. 12 in., weight 42 lbs/ft. Wall thickness or gauge No250 IAL: 01 STEEL
lank casing diameter 16 in asing height above land surface PPE OF SCREEN OR PERFORATION MATER CREEN OR PERFORATION OPENINGS ARE: CREEN PERFORATED INTERVALS: GRAVEL PACK INTERVALS: ROUT MATERIAL 02 CEMENT GROUT rout Intervals: From 0 ft. to nat is the nearest source of possifirection from well? NORTHWEST	. to 603 ft., Dia in. to 0 ft., Dia in. to 0 ft. 12 in., weight 42 lbs/ft. Wall thickness or gauge No250 IAL: 01 STEEL
lank casing diameter 16 in asing height above land surface YPE OF SCREEN OR PERFORATION MATER CREEN OR PERFORATION OPENINGS ARE: CREEN PERFORATED INTERVALS: GRAVEL PACK INTERVALS: ROUT MATERIAL 02 CEMENT GROUT rout Intervals: From 0 ft. to hat is the nearest source of possi irection from well? NORTHWEST FROM : TO : 0 : 23 : 01 CLAY	. to 603 ft., Dia in. to 0 ft., Dia in. to 0 ft. 12 in., weight 42 lbs/ft. Wall thickness or gauge No250 IAL: 01 STEEL
lank casing diameter 16 in asing height above land surface YPE OF SCREEN OR PERFORATION MATER CREEN OR PERFORATION OPENINGS ARE: CREEN PERFORATED INTERVALS: GRAVEL PACK INTERVALS: ROUT MATERIAL 02 CEMENT GROUT rout Intervals: From 0 ft. to hat is the nearest source of possifirection from well? NORTHWEST FROM : TO : 0 : 23 : 01 CLAY 05 SAND 23 : 45 : 01 CLAY 05 SAND	. to 603 ft., Dia in. to 0 ft., Dia in. to 0 ft. 12 in., weight 42 lbs/ft. Wall thickness or gauge No250 IAL: 01 STEEL
lank casing diameter 16 in asing height above land surface PPE OF SCREEN OR PERFORATION MATER CREEN OR PERFORATION OPENINGS ARE: CREEN PERFORATED INTERVALS: GRAVEL PACK INTERVALS: ROUT MATERIAL 02 CEMENT GROUT rout Intervals: From 0 ft. to nat is the nearest source of possifirection from well? NORTHWEST FROM : TO : 0 : 23 : 01 CLAY 23 : 45 : 01 CLAY 23 : 45 : 01 CLAY 05 SAND 45 : 78 : 05 SAND 13 FINE	. to 603 ft., Dia in. to 0 ft., Dia in. to 0 ft. 12 in., weight 42 lbs/ft. Wall thickness or gauge No250 IAL: 01 STEEL
lank casing diameter 16 in asing height above land surface YPE OF SCREEN OR PERFORATION MATER CREEN OR PERFORATION OPENINGS ARE: CREEN PERFORATED INTERVALS: GRAVEL PACK INTERVALS: ROUT MATERIAL 02 CEMENT GROUT rout Intervals: From 0 ft. to hat is the nearest source of possi irection from well? NORTHWEST FROM : TO : 0 : 23 : 01 CLAY 23 : 45 : 01 CLAY	. to 603 ft., Dia in. to 0 ft., Dia in. to 0 ft. 12 in., weight 42 lbs/ft. Wall thickness or gauge No250 IAL: 01 STEEL
lank casing diameter 16 in asing height above land surface YPE OF SCREEN OR PERFORATION MATER CREEN OR PERFORATION OPENINGS ARE: CREEN PERFORATED INTERVALS: GRAVEL PACK INTERVALS: ROUT MATERIAL 02 CEMENT GROUT rout Intervals: From 0 ft. to hat is the nearest source of possification from well? NORTHWEST FROM : TO : 0 : 23 : 01 CLAY 23 : 45 : 01 CLAY 25 : 78 : 05 SAND 13 FINE 278 : 85 : 23 SANDSTONE 285 : 140 : 01 CLAY	. to 603 ft., Dia in. to 0 ft., Dia in. to 0 ft. 12 in., weight 42 lbs/ft. Wall thickness or gauge No250 IAL: 01 STEEL
lank casing diameter 16 in asing height above land surface YPE OF SCREEN OR PERFORATION MATER CREEN OR PERFORATION OPENINGS ARE: CREEN PERFORATED INTERVALS: GRAVEL PACK INTERVALS: ROUT MATERIAL 02 CEMENT GROUT rout Intervals: From 0 ft. to hat is the nearest source of possi irection from well? NORTHWEST FROM : TO : 0 : 23 : 01 CLAY 23 : 45 : 01 CLAY 05 SAND 45 : 78 : 05 SAND 13 FINE 78 : 85 : 23 SANDSTONE 85 : 140 : 01 CLAY	. to 603 ft., Dia in. to 0 ft., Dia in. to 0 ft. 12 in., weight 42 lbs/ft. Wall thickness or gauge No250 IAL: 01 STEEL
lank casing diameter 16 in asing height above land surface YPE OF SCREEN OR PERFORATION MATER CREEN OR PERFORATION OPENINGS ARE: CREEN PERFORATED INTERVALS: GRAVEL PACK INTERVALS: ROUT MATERIAL 02 CEMENT GROUT rout Intervals: From 0 ft. to hat is the nearest source of possifirection from well? NORTHWEST FROM : TO : 0 : 23 : 01 CLAY 23 : 45 : 01 CLAY 05 SAND 45 : 78 : 05 SAND 13 FINE 78 : 85 : 23 SANDSTONE 85 : 140 : 01 CLAY 140 : 185 : 01 CLAY	. to 603 ft., Dia in. to 0 ft., Dia in. to 0 ft. 12 in., weight 42 lbs/ft. Wall thickness or gauge No250 IAL: 01 STEEL
lank casing diameter 16 in asing height above land surface YPE OF SCREEN OR PERFORATION MATER CREEN OR PERFORATION OPENINGS ARE: CREEN PERFORATED INTERVALS: GRAVEL PACK INTERVALS: ROUT MATERIAL 02 CEMENT GROUT rout Intervals: From 0 ft. to hat is the nearest source of possifirection from well? NORTHWEST FROM : TO : 0 : 23 : 01 CLAY 23 : 45 : 01 CLAY 05 SAND 45 : 78 : 05 SAND 13 FINE 78 : 85 : 23 SANDSTONE 85 : 140 : 01 CLAY 140 : 185 : 01 CLAY 185 : 210 : 01 CLAY	. to 603 ft., Dia in. to 0 ft., Dia in. to 0 ft. 12 in., weight 42 lbs/ft. Wall thickness or gauge No250 IAL: 01 STEEL

OUNTY	:	OF WATER	ITON		į	NW	1/4 N	W	1/4 SE	1/4		Sect: 33	ion Nu	⊕ber		Towns	ship No	umber S	; Ran ; R 4	ge Numbe O W
ATER	WEL	L OWNER:	;		H &	C FA														
R#, S	t.	Address,	Box	# :	RT.	1							Boar	d of	Agri	culture	, Div	ision o	f Water	Resource
ity,	Sta	te, ZIP	code	:			KS						Appl	icati	ion N	umber:	19,18	0		
CREEN	PE	RFORATEI) INTE	RVAL	5:		From	48	80 ft.	to 60	00 ft.	, From	0	ft.	to	0 ft				
							From		0 ft.	to	0 ft.	, From	0	ft.	to	0 ft				
FROM	!	TO	! i				LITHOLO	61C (_06			!								
240				SAN	D 13		GRAVEL					; ;								
290							20 LIM					; •								
							MEDIUM	SAN	0			1								
	!		04									i								
	i						7 FINE				(D	\$ \$								
358	; ; ;						MEDIUM					i 1								
371 390	:						SAND () ESTONE	o ne	VIUM SA	M)		i								
448	:						DSTONE					1								
480	i						DSTONE					i !								
505	1		23									: :								
581	i		20									; ;								
585	í	600	; 23	SAN	OSTOI	NE						í t								
600	į	610	; 20	LIM	ESTO	NE						E E								
	i		1									1								
	:		1									i i								
	i		i									i								
	i		•									i								
	1		:									i :								
	!		i									:								
	!		i																	
	1		1									i								
	;		1									i								
	i		1									!								
	i		i																	
	i		1									i								
	!		i									í i								
	i		ī t									i								
	i		1									i E								
	:		:									i								
	:		1									i i								
	i		i									:								
	1		i i									í								
	1		i t																	
	i		: :									(;								
	1		i									: :								
	i		:									i i								
	!		i f									i I								
	i		i									i i								

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was Constructed under my jurisoicion and completed on (mo/day/year) 03/25/92 and this record is true to the best of my knowledge and belief. Kansas

Mater Well Contractor's License No. 145

This Water Well Record was completed on (mo/day/yr) 06/06/92

by (signature)

Designation

This Water Well Record was completed on (mo/day/yr) 06/06/92

by (signature)