				R WELL RECORD	Form WWC-5	KSA 82	a-1212			
1 LOCATI	ON OF WAT	TER WELL:	Fraction		Sec	tion Numbe	r Township Nu	mber	Range Number	
County:	STANTON		V C ¼		SW 1/4	3	T 27.	S	R 41W E(W)	
Distance a	and direction	from nearest town	or city street a	address of well if loca	ated within city?					
FROM	JOHNSON	10 NORTH ON	27 TO RD	2-10, 1½ MI	LE WEST, 5	NORTH,	34 SOUTH & W	EST IN	TO LOC.	
		NER: VESS OI								
		# : 8100 E.		N RIJG 300			#1-3 F	LOYD	Division of Water Resources	
	, ZIP Code	WICHITA							<i>a</i>	
			-				Application	Huilibel.	950427	
AN "X"	IN SECTION	UROX. ⊢								
		1 De							3	
WELL'S STATIC WATER LEVEL 119 ft. below land surface measured o										
	NW	\ \.\.	Pum	p test data: Well w	ater was	ft.	after	hours pu	ımping gpm	
	- 1744	Es							ımping gpm	
	- i 1							•	. to	
* w -	WELL WATER USED AS: 5 Public water supply 8 Air conditioning 11 Injection well									
- 1	-i X I	i '		WAS _{3 Feedlot}	_				Other (Specify below)	
-	- SW	SE	2 Irrigation	4 Industrial			•			
1 1	!	!	_		-					
<u> </u>	1			bacteriological sampl	e submitted to De	•			, mo/day/yr sample was sub-	
		······································	itted				ater Well Disinfected		No	
		CASING USED:		5 Wrought iron				NTS: Glue	d Clamped	
1 St		3 RMP (SR)		6 Asbestos-Cemer	nt 9 Other	(specify belo	ow)	Weld	led <i>.</i>	
(2) °\		4 ABS		7 Fiberglass					aded	
				ft., Dia	in. to		ft., Dia		in. to ft.	
Casing he	ight above la	and surface5.	BELOW	.in., weight		Ibs	./ft. Wall thickness o	r gauge N	lo	
		R PERFORATION N			7 PV			stos-ceme		
1 Steel 3 Stainless steel				5 Fiberglass 8 RMP (SR)						
2 Br	ass	4 Galvanized	steel	6 Concrete tile 9 ABS			12 None used (open hole)			
		RATION OPENINGS		5 Gauzed wrapped			8 Saw cut 11 None (open hole)			
	ontinuous sio				e wrapped 9 Drilled holes					
								1	/A	
	uvered shutt		punched (3 99 ()°	rch cut aca		10 Other (specify)	· · · · · · · · · · · · · · · · · · ·	toft.	
SCHEEN-	PERFORATI	ED INTERVALS:								
									toft.	
(GRAVEL PA	CK INTERVALS:	From			ft., Fr	om	ft. !	toft.	
			From	ft. to		ft., Fr				
6 GROUT	MATERIAL	.: 1 Neat cen	nent (2 Cement grout	3 Bento	nite 4	Other			
Grout Inte	rvals: From	n. 8.9 ft.	to	ft., From	ft.	to	ft., From	• • • • • • •	ft. to	
								bandoned water well		
1 Septic tank 4 Lateral lin			lines	s 7 Pit privy 1			uel storage ij well/Gas well			
2 Sewer lines 5 Cess poo			ool	8 Sewage lagoon			12 Fertilizer storage 16 Other (specify below)			
3 Watertight sewer lines 6 Seepage							secticide storage			
Direction 1	=	· -		o . 000yu.u			•			
FROM	TO	SOUTHEAST	LITHOLOGIC	LOG	FROM	TO	nany feet? 210 PLUGGING INTERVALS			
1110111			EITHOLOGIC	200	300	.	CHLORINATED			
					104		HOLE PLUG	CINTAIN	4	
-1x.										
					89		CEMENT GROUT	<u>[</u>		
					5	0	BACKFILL			
	<u> </u>									
	 					_				
Т						I				
7 CONTI	RACTOR'S	OR LANDOWNER'S	CERTIFICAT	ION: This water well	l was (1) constru	cted, (2) red	constructed, or (3) of	ugged un	der my jurisdiction and was	
completed	on (mo/day/	_(year) 06-1	1-96			and this red	ord is true to the bes		nowledge and belief. Kansas	
Water We	ll Contractor'	s License No	KWWCL-43	30 This Water	Well Record wa	s completed	d on (mo/da <u>v</u> /yr)	_ 06-1		
				X 806 BEAVER			ature)	Who at	tes	
		I AMOUNT D		THE TAIL	· · · · · · · · · · · · · · · · · · ·	-, (-,3,,	a series			