WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

							•	•		
1. Location of well:	County	Fraction		Section number		Township number		Range number		
	Stanton	NE 1/4 SE 1/4 SE	1/4	2	2	т 27	s	R	41	€€
160 & 270 10 miles north R.R. or				wher of well: or street: Dave Weaver state, zip code: RFD 1, Milford, Ks. 66514						
4. Locate with "X" in section below: N						6. Bore hole dia. 27 in. Completion date Well depth 412 ft. 11-9-77				
NW NE						7 Cable toolXRotary Driven Dug Hollow rod Jetted Bored Reverse rotary				
E - SW SE - 1						8. Use:Domestic Public supply Industry X Irrigation Air conditioning Stock Oil field water Other Other 9. Casing: Material Stee1 Height Above of below Threaded Welded X Surface in. RMP PVC Weight 36.8 lbs./ft Dia. 16 in. to 195 depth Wall Thickness: inches or				
<u> </u>										
5. Type and color of material					То	Dia in. to ft. depth gage No1219				
Surface				0	2	10. Screen: Manufacturer's name Lakewood Pipe of Texas Typestee1				
Fine to medium sand w/clay breakers				2	56	Slot/gauze3/ Set between195	<u>,6</u>	ft. and	312.	<u>1ft</u> .
Brown sandy clay				56	93	Gravel pack? X	ft.an Size rang	ge of n	naterial 4X	5/8""·
Fine to medium sand w/clay breakers& embedded sand strips				93	157	11. Static water level:			mo	o./day/yr.
Brown and blue clay					182	12. Pumping level belo	w land	surface	95:	
Fine to coarse sand w/clay breakers 14				182	219					
Brown clay w/embedded sand strips					231	13. Water sample subm	itted:)ate		./day/yr.
Yellow chalk & Dakota Sandstone				231	275	14. Well head completion:				
Y&llow chalk w/fight sandstone strips				275	293	Pitless adapter 15. Well grouted?			inches above	grade
Brown & blue shalew/medium sandstone strips				293	346	With: X Neat cement Bentonite Concrete Depth: From 0 ft. to 10 ft.				
Blue sahle, w/loose sandstone strips				346	374	16. Nearest source of p	possible on	contan	nination: Type fie	1d
Blue shale, & tight sandstone				374	381	Well disinfected upon	complet	ion?_	Yes	<u>X No</u>
-Sandstone loose				381	394	17. Pump: Manufacturer's name _ Model number			Not installed	
Sandstone (lost circulation & dry drilled to			412	394	405	Length of drop pipe — Type:				
(Use a second sheet if needed)						Submersible Jet Centrifugal			Turbin Recipe Other	rocating
19. Remarks: 40 feet W. A. Brown set between 209.8' and 249.8' 120 feet W. A. Brown set between 449.8 and 569.8'						20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. HOUCK Bros. Drlg. Co. 164 Business name Box 487, Ulysses, Ks. Signed Date Market				
Valley						Authoriz	ed repre	esèntat	ive Date	, <u>, , , , , , , , , , , , , , , , , , </u>