

USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:	County Stanton	Fraction SW 1/4 SW 1/4 NW 1/4	Section number 1	Township number T 27 S	Range number R 42 E/W
----------------------	--------------------------	---	----------------------------	----------------------------------	---------------------------------

2. Distance and direction from nearest town or city: 10 miles north, 5 west, of Hwy Jct. at Johnson, Kansas Street address of well location if in city:	3. Owner of well: Lawrence Herrmann R.R. or street: % Duran Bros. City, state, zip code: Johnson, Ks. 67855
--	---

4. Locate with "X" in section below: Sketch map:

N

S

E

W

6. Bore hole dia. 27 in. Completion date _____
Well depth 575 ft. 8/27/76

7. Cable tool Rotary Driven Dug
 Hollow rod Jetted Bored Reverse rotary

8. Use: Domestic Public supply Industry
 Irrigation Air conditioning Stock
 Lawn Oil field water Other

9. Casing: Material steel Height: Above or below
Threaded Welded Surface 14 in.
RMP PVC Weight 36.8 lbs./ft.
Dia. 26 in. to 216 ft. depth Wall Thickness: inches or
Dia. _____ in. to _____ ft. depth gage No. 219

5. Type and color of material	From	To
Surface	0	2
Very fine sand w/clay breakers	2	29
Fine to medium sand	29	47
Sandy clay w/fine sand strips	47	63
Medium to coarse sand w/clay breakers	63	92
Brown gummy clay w/sandy clay & fine sand strips	92	164
Fine to medium sand w/clay breakers	164	181
Sandy clay & lime shale	181	219
Medium to coarse sand 6 ft.	219	226
Sandy clay	226	239
Medium to coarse sand 16 ft.	239	255
Fine to medium sand w/clay breakers	255	271
Dakota 80%	271	282
YELLOW CHALK, GRAY CLAY, SANDROGE, Dakota 40%	282	296
Blue shale & Dakota 5%	296	382
Blue shale, white clay, Dakota & Cheyenne 80%	382	428
Blue & brown shale, white clay, Dakota & Cheyenne	428	465
Blue & Brown shale, white clay, Dakota & Cheyenne	465	532
Blue & brown shale, white clay & Dakota & Cheyenne	532	575

10. Screen: Manufacturer's name Lakewood
Lakewood Pipe of Texas
Type steel Dia. 16"
Slot/gauze 3/16 Length 359'
Set between 216 ft. and 575 ft.
_____ ft. and _____ ft.
Gravel pack? Size range of material 1/2 x 5/8"

11. Static water level: _____ mo./day/yr.
97 ft. below land surface Date 9/1/76

12. Pumping level below land surfaces:
220 ft. after 12 hrs. pumping 850 g.p.m.
300 ft. after 18 hrs. pumping 1300 g.p.m.
Estimated maximum yield 1300 g.p.m.

13. Water sample submitted: _____ mo./day/yr.
Yes No Date _____

14. Well head completion: NA
 Pitless adapter _____ Inches above grade

15. Well grouted?
With: Neat cement Bentonite Concrete
Depth: From 0 ft. to 10 ft.

16. Nearest source of possible contamination: NA
ft. _____ Direction _____ Type _____
Well disinfected upon completion? Yes No

17. Pump: Not installed
Manufacturer's name _____
Model number _____ HP _____ Volts _____
Length of drop pipe _____ ft. capacity _____ g.p.m.
Type:
 Submersible Turbine
 Jet Reciprocating
 Centrifugal Other

18. Elevation: _____

19. Remarks:
cheyenne

Topography:
 Hill
 Slope
 Upland
 Valley

20. Water well contractor's certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Houck Bros. Drig. Co. 164

Business name _____ License No. _____
Address Box 487, Ulysses, Ks.
Signed Mellio M. Beard Date 10/15/76
Authorized representative

27 42 E
R
1
SUSUNW
1/4 1/4 1/4