

USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD  
KSA 82a-1201-1215

T R EW sec 1/4 1/4 1/4 No.

Kansas State Dept. Of Health  
(Water Well Contractors)  
Forbes-Bldg. 740  
Topeka, Kansas 66620


1 Location of well:	County Stanton	Township name	Fraction SW 1/4 NE 1/4 NE 1/4	Section number 11	Town number T 27 S	Range number R 42 W
---------------------	-------------------	---------------	-------------------------------------	----------------------	-----------------------	------------------------

Distance and direction from nearest town or city:  
13 miles North of Manter  
Street address of well location if in city:

3 Owner of well: Bill Hoff  
Address: Syracuse, Kansas

Locate with "X" in section below:

Sketch map:



4 Well depth: 618 ft. Date of completion 1-7-75  
Well diameter 26 in.

5  Cable tool  Rotary  Driven  Dug  
 Hollow rod  Jetted  Bored  Reverse rotary

6 Use:  Domestic  Public supply  Industry  
 Irrigation  Air conditioning  Commercial  
 Test well

7 Casing: Material Steel Height: above/below  
Threaded  Welded  Surface 12 in.  
Diam. Weight 36 lbs./ft.  
16 in. to 618 ft. depth Drive shoe?  Yes  No

2	Type and color of material	From	To
	See attached Log Top soil	0	4
	Clay, brown, with fine sand stringers	4	19
	Sand, f-m-c, v.loose, few clay stringers	19	40
	Clay, brown	40	52
	Sand, f-m-c, small gravel, loose	52	60
	(dito) but with clay stringers	60	73
	Sand, f-m-c, Small gravel, v.loose, some clay st.	73	98
	Clay, brown, fairly sticky	98	130
	Sand, f-m-c, m-gravel, brown with white rk.	130	183
	Clay, brown, sticky, some limerk. ledges	183	228
	Sand, f-m-c, drlg loose	228	233
	Clay, brown, some limerk ledges, sticky, sand st.	233	244
	Sand, f-m-c, m-gravel, brown, loose, used H2O,	244	265
	Sand, f-m, some c, some cem. ledges, loose, H2O	265	282
	Soapstone, white and yellow	282	290
	Shale and limestone (use a second sheet if needed) ledges,		

8 Screen: Manufacturer Johnson  
Type Continuous Dia. 16"  
Slot/gauge 150 Length 30'  
Set between 170 ft. and 185 ft. 250 & 265'  
Fittings:  
Gravel pack  Yes  No Size range of material 1/8 to 1/8

9 Static water level:  
144 ft. below land surface Date 1-6-75

10 Pumping level below land surfaces:  
205 ft. after hrs. pumping 1450 g.p.m.  
ft. after hrs. pumping g.p.m.  
Estimated maximum yield g.p.m.

11 Water sample submitted:  
 Yes  No Date

12 Well head completion: 12  
 Pitless adapter  Inches above grade

13 Well grouted?  Yes  No  
 Neat cement  Bentonite   
Depth: From 0 ft. to 10 ft.

14 Nearest source of possible contamination: None  
ft. Direction Type  
Well disinfected upon completion?  Yes  No

15 Pump:  Not installed  
Manufacturer's name  
Model number HP Volts  
Length of drop pipe ft. capacity g.m.p.  
Type:  
 Submersible  Turbine  
 Jet  Reciprocating  
 Centrifugal  Other

16 Remarks: elevation weathered, few Dak. SS. St. 290 345

Topography:  
 Hill Flat  
 Slope  
 Upland  
 Valley

17 Water well contractor's certification:  
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.  
Henkle Drilling & Supply Co., Inc.  
Business name License No. 145  
Address Box 639 Garden City, Ks.  
Signed Richard Henkle Date 1-23-75  
Authorized representative

