Casing height above land surface TYPE OF SCREEN OR PERFORATION 1 Steel 3 Stainle 2 Brass 4 Galvan Screen or Perforation Openings Are: 1 Continuous slot 3 2 Louvered shutter 4 Screen-Perforation Dia 8 5/8 Screen-Perforated Intervals: From. Gravel Pack Intervals: From. From.	473 5 Public w 6 Oil field 7 Lawn ar 1t. belo Well water w Well water w 1: SR) in to 213 18 ON MATERIA pss steel nized steel Mill slot Key punched in to 47 21 10	Travis South F Syracus .ft. Bore Hole vater supply water supply md garden only w land surface was 5 Wron 6 Asbe 7 Fibeftftftftftft.	Walker Route Se, Ks. Diameter measured on ft. after ft. after ught iron estos-Cement erglass Dia weight reglass crete tile 5 Gauz 6 Wire 7 Torch ft. Dia to 47.3 to 47.3 to 47.3	Street address 67878 15 in. to 8 Air condition 9 Dewatering 10 Observation Sept 8 Concrete 9 Other (specific points) 7 PVC 8 RMP (9 ABS red wrapped wrapped wrapped or cut in. to ft., ft., ft.,	473 A73 A73 Aning well	Application Number ft., and	ire, Division of Water Resourcer: in. to well pecify below) day 1980 yea gpr gpr Glued Clamped Velded X Threaded in. to inge No sement cify) I (open hole) 11 None (open hole)
Distance and direction from nearest to Johnson, Ks. 12 miles w Water Well OWNER: RR#, St. Address, Box # City, State, ZIP Code 3 DEPTH OF COMPLETED WELL. Well Water to be used as: 1 Domestic 3 Feedlot 2 Irrigation 4 Industrial Well's static water level 165. Pump Test Data Est. Yield gpm: 4 TYPE OF BLANK CASING USED 1 Steel 3 RMP (2 PVC 4 ABS) Blank casing dia 8 5/8. Casing height above land surface. TYPE OF SCREEN OR PERFORATION 1 Steel 3 Stainle 2 Brass 4 Galvant Screen or Perforation Openings Are: 1 Continuous slot 3 2 Louvered shutter 4 Screen-Perforated Intervals: From. Gravel Pack Intervals: From. 5 GROUT MATERIAL: 1 Near	473 5 Public w 6 Oil field 7 Lawn ar 1 tt. belo Well water w 8 SR) in. to 213 in. to 213 in. to 213 in. to 213 Key punched in. to 47 21 10	270-160 Jorth Travis South F Syracus If. Bore Hole vater supply water supply and garden only ow land surface was 5 Wrone 6 Asbee 7 Fibe In. AL: 5 Fibe 6 Conditions ft. If. ft. If. ft.	Walker Route Se, Ks. Diameter measured on ft. after ft. after ught iron estos-Cement erglass Dia weight erglass crete tile 5 Gauz 6 Wire 7 Torch ft. Dia to 473 to 473 to 473	Street address 67878 15 in. to 8 Air condition 9 Dewatering 10 Observation Sept 8 Concrete 9 Other (specific points) 7 PVC 8 RMP (9 ABS 8 ded wrapped 9 cut in. to ft., ft., ft.,	473 well month hou hou tile ecify below) lbs./ft. \ SR) 8 9 10 From	Board of Agricultu Application Numb ft., and 11 Injection 12 Other (Sp 19 urs pumping Casing Joints: G V T ft., Dia Wall thickness or gau 10 Asbestos-c 11 Other (spe 12 None used Saw cut Drilled holes Other (specify) ft., Dia ft., ft.	ire, Division of Water Resourcer: in to
Johnson, Ks. 12 miles w 2 WATER WELL OWNER: RR#, St. Address, Box # City, State, ZIP Code 3 DEPTH OF COMPLETED WELL. Well Water to be used as: 1 Domestic 3 Feedlot 2 Irrigation 4 Industrial Well's static water level 165 Pump Test Data Est. Yield gpm: 4 TYPE OF BLANK CASING USED 1 Steel 3 RMP (2 PVC 4 ABS) Blank casing dia 8 5/8 Casing height above land surface. TYPE OF SCREEN OR PERFORATION 1 Steel 3 Stainle 2 Brass 4 Galvan Screen or Perforation Openings Are: 1 Continuous slot 3 2 Louvered shutter 4 Screen-Perforated Intervals: From. From. Gravel Pack Intervals: From. 5 GROUT MATERIAL: 1 Near	473 5 Public w 6 Oil field 7 Lawn ar 1t. belo Well water w Well water w 1: SR) in to 213 18 ON MATERIA pss steel nized steel Mill slot Key punched in to 47 21 10	Travis South F Syracus .ft. Bore Hole vater supply water supply md garden only w land surface was 5 Wron 6 Asbe 7 Fibeftftftftftft.	Walker Route Se, Ks. Diameter measured on ft. after ft. after ught iron estos-Cement erglass Dia weight reglass crete tile 5 Gauz 6 Wire 7 Torch ft. Dia to 47.3 to 47.3 to 47.3	67878 15 in. to 8 Air condition 9 Dewatering 10 Observation Sept 8 Concrete 9 Other (sponsor) in. to 16,90 7 PVC 8 RMP (9 ABS red wrapped wrapped or cut in. to ft., ft.,	473 well month hou hou tile ecify below) lbs./ft. \ SR) 8 9 10 From	Board of Agricultu Application Number ft., and 11 Injection 12 Other (Sp 19 urs pumping Casing Joints: 6 V T ft., Dia Wall thickness or gau 10 Asbestos-c 11 Other (specify) ft., Dia ft., Dia Other (specify) ft., Dia ft., ft.	well pecify below) day 1980 yea gpr Glued Clamped Nelded X Threaded in to ge No 188 Description 188 Description 1980 yea year gpr Glued Octobro 1980 year g
WATER WELL OWNER: RR#, St. Address, Box # City, State, ZIP Code DEPTH OF COMPLETED WELL. Well Water to be used as: 1 Domestic 3 Feedlot 2 Irrigation 4 Industrial Well's static water level 165 Pump Test Data Est. Yield gpm: 4 TYPE OF BLANK CASING USED 1 Steel 3 RMP (2 PVC 4 ABS) Blank casing dia 8 5/8. Casing height above land surface. TYPE OF SCREEN OR PERFORATION 1 Steel 3 Stainle 2 Brass 4 Galvant Screen or Perforation Openings Are: 1 Continuous slot 3 2 Louvered shutter 4 Screen-Perforated Intervals: From. Gravel Pack Intervals: From. 5 GROUT MATERIAL: 1 Neat Grouted Intervals: From. 5 GROUT MATERIAL: 1 Neat Grouted Intervals: From. 0 What is the nearest source of possible	5 Public w 6 Oil field 7 Lawn ar ft. belo Well water w Well water w 12 SR) in. to 213 in. to 213 in. to 213 in. to 213 Key punched in. to 47 21 10	Travis South F Syracus .ft. Bore Hole vater supply water supply mad garden only was 5 Wron 6 Asbe 7 Fibe	Route Se Ks Piameter measured on ft. after ft. after ught iron estos-Cement erglass Dia weight erglass crete tile 5 Gauz 6 Wire 7 Torch ft. Dia to 473 to 473 to 473	8 Air condition 9 Dewatering 10 Observation Sept 8 Concrete 9 Other (sponsor) in to 16,90 7 PVC 8 RMP (9 ABS red wrapped wrapped or cut in to ft.,	wellmonthhou hou tile ecify below)	Application Number ft., and	well pecify below) day 1980 yea gpr Glued Clamped Nelded X Threaded in to ge No 188 Description 188 Description 1980 yea year gpr Glued Octobro 1980 year g
City, State, ZIP Code 3 DEPTH OF COMPLETED WELL. Well Water to be used as: 1 Domestic 3 Feedlot 2 Irrigation 4 Industrial Well's static water level 165 Pump Test Data Est. Yield gpm: 4 TYPE OF BLANK CASING USED 1 Steel 3 RMP (2 PVC 4 ABS) Blank casing dia 8 5/8. Casing height above land surface. TYPE OF SCREEN OR PERFORATION 1 Steel 3 Stainle 2 Brass 4 Galvant Screen or Perforation Openings Are: 1 Continuous slot 3 2 Louvered shutter 4 Screen-Perforated Intervals: From. Gravel Pack Intervals: From. 5 GROUT MATERIAL: 1 Near Grouted Intervals: From. Grouted Intervals: From. 0 What is the nearest source of possible	5 Public w 6 Oil field 7 Lawn ar ft. belo Well water w Well water w 18 SR) In. to 213 18 ON MATERIA Ses steel hized steel Mill slot Key punched in. to 47 21 10 it cement	South F Syracus .ft. Bore Hole vater supply water supply md garden only w land surface was 5 Wron 6 Asbe 7 Fibe	Route Se Ks Piameter measured on ft. after ft. after ught iron estos-Cement erglass Dia weight erglass crete tile 5 Gauz 6 Wire 7 Torch ft. Dia to 473 to 473 to 473	8 Air condition 9 Dewatering 10 Observation Sept 8 Concrete 9 Other (sponsor) in to 16,90 7 PVC 8 RMP (9 ABS red wrapped wrapped or cut in to ft.,	wellmonthhou hou tile ecify below)	Application Number ft., and	well pecify below) day 1980 yea gpr Glued Clamped Nelded X Threaded in to ge No 188 Description 188 Description 1980 yea year gpr Glued Octobro 1980 year g
Well Water to be used as: 1 Domestic 3 Feedlot 2 Irrigation 4 Industrial Well's static water level	5 Public w 6 Oil field 7 Lawn ar ft. belo Well water w Well water w 18 SR) In. to 213 18 ON MATERIA Ses steel hized steel Mill slot Key punched in. to 47 21 10 it cement	Syracus .ft. Bore Hole vater supply water supply md garden only water supply water supply water supply water supply water supply water supply for a comparison 6 Asbe 7 Fibeftftftftftft.	e measured on ft. after ft. after ught iron estos-Cement erglass rete tile 5 Gauz 6 Wire 7 Torch ft. Dia	8 Air condition 9 Dewatering 10 Observation Sept 8 Concrete 9 Other (sponsor) in to 16,90 7 PVC 8 RMP (9 ABS red wrapped wrapped or cut in to ft.,	wellmonthhou hou tile ecify below)	Application Number ft., and	well pecify below) day 1980 yea gpr Glued Clamped Nelded X Threaded in to ge No 188 Description 188 Description 1980 yea year gpr Glued Octobro 1980 year g
Well Water to be used as: 1 Domestic 3 Feedlot 2 Irrigation 4 Industrial Well's static water level	5 Public w 6 Oil field 7 Lawn ar ft. belo Well water w Well water w 18 SR) In. to 213 18 ON MATERIA Ses steel hized steel Mill slot Key punched in. to 47 21 10 it cement	water supply water supply nd garden only water supply nd garden only was 5 Wrote 6 Asbe 7 Fibe	e measured onft. after ft. after ught iron estos-Cement erglass ., Dia ., weight erglass crete tile 5 Gauz 6 Wire 7 Torch ft., Dia to47.3 to to47.3	8 Air condition 9 Dewatering 10 Observation Sept 8 Concrete 9 Other (sponsor) in to 16,90 7 PVC 8 RMP (9 ABS red wrapped wrapped or cut in to ft.,	wellmonthhou hou tile ecify below)	11 Injection of 12 Other (Sp. 19 ors pumping	well pecify below) day 1980 yea gpr gpr Glued Clamped Nelded X Threaded in to ge No 188 cement cify) d (open hole) 11 None (open hole) in to
Well Water to be used as: 1 Domestic 3 Feedlot 2 Irrigation 4 Industrial Well's static water level	5 Public w 6 Oil field 7 Lawn ar ft. belo Well water w Well water w 18 SR) In. to 213 18 ON MATERIA Ses steel hized steel Mill slot Key punched in. to 47 21 10 it cement	water supply water supply nd garden only water supply nd garden only was 5 Wrote 6 Asbe 7 Fibe	e measured onft. after ft. after ught iron estos-Cement erglass ., Dia ., weight erglass crete tile 5 Gauz 6 Wire 7 Torch ft., Dia to47.3 to to47.3	8 Air condition 9 Dewatering 10 Observation Sept 8 Concrete 9 Other (sponsor) in to 16,90 7 PVC 8 RMP (9 ABS red wrapped wrapped or cut in to ft.,	wellmonthhou hou tile ecify below)	11 Injection of 12 Other (Sp. 19 ors pumping	well pecify below) day 1980 yea gpr gpr Glued Clamped Nelded X Threaded in to ge No 188 cement cify) d (open hole) 11 None (open hole) in to
2 Irrigation 4 Industrial Well's static water level	7 Lawn ar 7 th below Well water wate	nd qarden only w land surface was 5 Wrot 6 Asbe 7 Fibe	e measured onft. after ft. after ught iron estos-Cement erglass ., Dia ., weight erglass crete tile 5 Gauz 6 Wire 7 Torch ft., Dia to47.3 to 47.3	8 Concrete 9 Other (spinion to 16,90 7 PVC 8 RMP (9 ABS red wrapped wrapped in cut in to ft., ft., ft.,	tile ecify below) lbs./ft. \ SR) 8 9 10 From	19 Urs pumping. Casing Joints: G W T ft., Dia Wall thickness or gau 10 Asbestos-c 11 Other (specify) ft., Dia Other (specify) ft., Dia ft., ft.	day 1980 year gpr gpr gpr gpr gpr gpr gpr gpr gpr gp
Well's static water level 165 Pump Test Data Est. Yield gpm: 4 TYPE OF BLANK CASING USED 1 Steel 3 RMP (2 2 PVC 4 ABS) Blank casing dia 8 5/8 Casing height above land surface. TYPE OF SCREEN OR PERFORATION 1 Steel 3 Stainle 2 Brass 4 Galvant Screen or Perforation Openings Are: 1 Continuous slot 3 2 Louvered shutter 4 Screen-Perforated Intervals: From. From. Gravel Pack Intervals: From. 5 GROUT MATERIAL: 1 Neat Grouted Intervals: From. 0 What is the nearest source of possible	ft. belo Well water v Well water v Well water v SR) in. to 213 18 ON MATERIA ess steel nized steel Mill slot Key punched in. to 47 21 10	Section Sect	e measured onft. after ft. after ught iron estos-Cement erglass ., Dia ., weight erglass crete tile 5 Gauz 6 Wire 7 Torch ft., Dia to47.3 to 47.3	8 Concrete 9 Other (spi in. to 16,90 7 PVC 8 RMP (9 ABS red wrapped wrapped wrapped in cut in. to ft., ft.,	tile ecify below) lbs./ft. \ SR) 8 9 10 From	Casing Joints: G V T ft., Dia Wall thickness or gau 10 Asbestos-c 11 Other (specify) Drilled holes Other (specify) ft., Dia ft.	gpr gpr Glued Clamped Velded Threaded in to ige No 188 cement cify) I (open hole) 11 None (open hole) in to in to in to in to
Pump Test Data Est. Yield gpm: 4 TYPE OF BLANK CASING USED 1 Steel 3 RMP (2 PVC 4 ABS) Blank casing dia 8 5/8. Casing height above land surface. TYPE OF SCREEN OR PERFORATION 1 Steel 3 Stainle 2 Brass 4 Galvant Screen or Perforation Openings Are: 1 Continuous slot 3 2 Louvered shutter 4 Screen-Perforated Intervals: From. From. Gravel Pack Intervals: From. 5 GROUT MATERIAL: 1 Neat Grouted Intervals: From. 0 What is the nearest source of possible	Well water v Well water v SSR) in. to 213 in. to 213 in. to 213 ON MATERIA ess steel nized steel Mill slot Key punched in. to 47 21 10	was	ft. after ft. after ft. after ught iron estos-Cement erglass for the first process of the first process ft. Dia ft. Di	8 Concrete 9 Other (specific to to 16,90 7 PVC 8 RMP (9 ABS red wrapped wrapped wrapped in to ft., ft.	tile ecify below)lbs./ft. \ SR) 8 9 10 From	Casing Joints: G V T ft., Dia Wall thickness or gau 10 Asbestos-c 11 Other (specify) Drilled holes Other (specify) ft., Dia ft.	gpr gpr Glued Clamped Velded Threaded in to ige No 188 cement cify) I (open hole) 11 None (open hole) in to in to in to in to
Est. Yield gpm: 4 TYPE OF BLANK CASING USED 1 Steel 3 RMP (1) 2 PVC 4 ABS Blank casing dia 8 5/8 Casing height above land surface. TYPE OF SCREEN OR PERFORATION 1 Steel 3 Stainle 2 Brass 4 Galvant Screen or Perforation Openings Are: 1 Continuous slot 3 2 Louvered shutter 4 Screen-Perforation Dia 8 5/8 Screen-Perforated Intervals: From. From. Gravel Pack Intervals: From. 5 GROUT MATERIAL: 1 Neat Grouted Intervals: From. 0 What is the nearest source of possible	Well water viscosity (SR) in. to 213 18 ON MATERIA ess steel nized steel Mill slot Key punched in. to 47 21 10	5 Wrot 6 Asbert 7 Fibe	ft. after ught iron estos-Cement erglass , Dia , weight erglass crete tile 5 Gauz 6 Wire 7 Torch ft. Dia to473 to 473	8 Concrete 9 Other (spi in. to 16.90 7 PVC 8 RMP (9 ABS red wrapped wrapped or cut in. to ft., ft.,	tile ecify below)lbs./ft. \frac{1}{2} SR) 8 9 10 From	Casing Joints: G W T ft., Dia Wall thickness or gau 10 Asbestos-c 11 Other (specify) Drilled holes Other (specify) ft., Dia ft.	gpr Glued Clamped Velded Threaded in to ige No 188 cement icify) I (open hole) 11 None (open hole) in to
1 Steel 3 RMP (1) 2 PVC 4 ABS Blank casing dia 8 5/8 Casing height above land surface. TYPE OF SCREEN OR PERFORATION 1 Steel 3 Stainle 2 Brass 4 Galvan Screen or Perforation Openings Are: 1 Continuous slot 3 Co	in. to 213 18 ON MATERIA ess steel hized steel Mill slot Key punched in. to 47 21	6 Asber 7 Fibe	estos-Cement erglass ., Dia , weight erglass crete tile 6 Wire 7 Torch ft., Dia to	9 Other (spanion to 16,90 7 PVC 8 RMP (9 ABS red wrapped wrapped in cut in. to ft., ft., ft.,	ecify below)	V T T, ft., Dia Wall thickness or gau 10 Asbestos-c 11 Other (specify) 12 None used Saw cut Drilled holes Other (specify) ft., Dia ft.	Velded X Threaded
2 PVC 4 ABS Blank casing dia 8 5/8 Casing height above land surface. TYPE OF SCREEN OR PERFORATION 1 Steel 3 Stainle 2 Brass 4 Galvan Screen or Perforation Openings Are: 1 Continuous slot 3 2 Louvered shutter 4 Screen-Perforation Dia 8 5/8 Screen-Perforated Intervals: From. From. Gravel Pack Intervals: From. 5 GROUT MATERIAL: 1 Near	in. to 213 18 ON MATERIA ess steel nized steel Mill slot Key punched in. to 47 21 10	7 Fibe	erglass ., Dia , weight erglass crete tile 5 Gauz 6 Wire 7 Torch ft., Dia to47.3 to to47.3	in. to	SR) 8 9 10 From	T. ft., Dia Wall thickness or gau 10 Asbestos-c 11 Other (specify) Language of the control of the contr	Threaded. in. to
Blank casing dia 8 5/8 Casing height above land surface. TYPE OF SCREEN OR PERFORATION 1 Steel 3 Stainle 2 Brass 4 Galvan Screen or Perforation Openings Are: 1 Continuous slot 3 2 Louvered shutter 4 Screen-Perforation Dia 8 5/8 Screen-Perforated Intervals: From. From. Gravel Pack Intervals: From. 5 GROUT MATERIAL: 1 Neat Grouted Intervals: From. 0 What is the nearest source of possible	ON MATERIA ess steel nized steel Mill slot Key punched in to 47 21	5 Fibe 6 Cond	proglass crete tile 5 Gauze 6 Wire 7 Torch ft., Dia to	in to 16.90 7 PVC 8 RMP (9 ABS ed wrapped wrapped in cut in to ft., ft.,	SR) 8 9 10 From	Mall thickness or gau 10 Asbestos-c 11 Other (specific None used) Saw cut Drilled holes Other (specify) ft., Dia ft.	in to inge No
Casing height above land surface TYPE OF SCREEN OR PERFORATION 1 Steel 3 Stainle 2 Brass 4 Galvant Screen or Perforation Openings Are: 1 Continuous slot 3 2 Louvered shutter 4 Screen-Perforation Dia 8 5/8 Screen-Perforated Intervals: From. From. Gravel Pack Intervals: From. From. 5 GROUT MATERIAL: 1 Neat Grouted Intervals: From 0 What is the nearest source of possible	ON MATERIA ess steel nized steel Mill slot Key punched in to 47 21	5 Fibe 6 Cond	erglass crete tile 5 Gauz 6 Wire 7 Torch ft. Dia to	16.90 7 PVC 8 RMP (9 ABS ed wrapped wrapped cut in. to ft., ft.,	lbs./ft. \\ SR) 8 9 10 From	Wall thickness or gau 10 Asbestos-c 11 Other (specific None used) Saw cut Drilled holes Other (specify) ft., Dia ft.	ge No
TYPE OF SCREEN OR PERFORATION 1 Steel 3 Stainle 2 Brass 4 Galvan Screen or Perforation Openings Are: 1 Continuous slot 3 2 Louvered shutter 4 Screen-Perforation Dia 8 5/8 Screen-Perforated Intervals: From From. Gravel Pack Intervals: From From 5 GROUT MATERIAL: 1 Neat Grouted Intervals: From 0 What is the nearest source of possible	ON MATERIA ess steel nized steel Mill slot Key punched in to 47 21	AL: 5 Fibe 6 Cond 7.3	erglass crete tile 5 Gauz 6 Wire 7 Torch ft., Dia to	7 PVC 8 RMP (9 ABS ed wrapped wrapped cut	8 9 10 From	10 Asbestos-c 11 Other (specific None used) Saw cut Drilled holes Other (specify) ft., Dia	tement cify) d (open hole) 11 None (open hole)in to
1 Steel 3 Stainle 2 Brass 4 Galvan Screen or Perforation Openings Are: 1 Continuous slot 3 2 Louvered shutter 4 Screen-Perforation Dia 8 5/8 Screen-Perforated Intervals: From From Gravel Pack Intervals: From From 5 GROUT MATERIAL: 1 Neat Grouted Intervals: From 0 What is the nearest source of possible	Mill slot Key punched in. to 47 21	5 Fibe 6 Cond 73	crete tile	8 RMP (9 ABS ed wrapped wrapped cut fin. to ft., ft.,	8 9 10 From	11 Other (specification of the content of the conte	t (open hole) 11 None (open hole) 11 in to
2 Brass 4 Galvan Screen or Perforation Openings Are: 1 Continuous slot 3 2 Louvered shutter 4 Screen-Perforation Dia . 8 5/8 . Screen-Perforated Intervals: From. From. Gravel Pack Intervals: From. From. 5 GROUT MATERIAL: 1 Neat Grouted Intervals: From . 0 . What is the nearest source of possible	Mill slot Key punched in. to 47 21	6 Cond 73	crete tile	9 ABS red wrapped wrapped n cut	8 9 10 From	12 None used Saw cut Drilled holes Other (specify) ft., Dia ft.	f (open hole) 11 None (open hole) in toto
Screen or Perforation Openings Are: 1 Continuous slot 2 Louvered shutter 4 Screen-Perforation Dia	Mill slot Key punched in to 47 21	173	5 Gauze 6 Wire 7 Torch ft., Dia to	ed wrapped wrapped cut fin. to ft., ft.,	9 10 From	Saw cut Drilled holes Other (specify)	11 None (open hole)in to
1 Continuous slot 3 2 Louvered shutter 4 Screen-Perforation Dia . 8 . 5/8 . Screen-Perforated Intervals: From. From. Gravel Pack Intervals: From. From. 5 GROUT MATERIAL: 1 Near Grouted Intervals: From . 0 . What is the nearest source of possible	Key punched in to 47 21 10	7.3	6 Wire 7 Torch ft., Dia to 47.3 to 47.3 to	wrapped cut ft., ft., ft.,	9 10 From	Drilled holes Other (specify) ft., Dia ft.	in to
2 Louvered shutter 4 Screen-Perforation Dia	Key punched in to 47 21 10	7.3	7 Torch ft., Dia to	n cut in. to ft., ft., ft.,	From	Other (specify) ft., Dia ft.	in to
Screen-Perforation Dia 8 . 5/8 From	. in. to . 47 	7.3	ft., Diato47.3 to47.3 to47.3	in. toft.,ft.,	From	ft., Dia	in to
Screen-Perforated Intervals: From. From. Gravel Pack Intervals: From. From 5 GROUT MATERIAL: 1 Near Grouted Intervals: From. 0 What is the nearest source of possible	21	1.3ft. 0ft. ft.	to	ft., ft., ft.,	From		to
Gravel Pack Intervals: From. From GROUT MATERIAL: 1 Near Grouted Intervals: From0. What is the nearest source of possible	1 (0	to	ft.,	From	. ft	
Gravel Pack Intervals: From. 5 GROUT MATERIAL: 1 Near Grouted Intervals: From	10	0	to 47.3 to	ft.,			to
From 5 GROUT MATERIAL: 1 Near Grouted Intervals: From	t cement	ft.	to		From		
GROUT MATERIAL: 1 Near Grouted Intervals: From	t cement			ft			to
Grouted Intervals: From0 What is the nearest source of possible		2 Como			From	ft.	
What is the nearest source of possibl							
· ·			ft., From				
1 Septic tank 4 Ces					10 Fuel store	•	4 Abandoned water well
	-		7 Sewage lag	oon	11 Fertilizer	-	15 Oil well/Gas well
	epage pit		8 Feed yard		12 Insecticid	-	6 Other (specify below)
3 Lateral lines 6 Pit Direction from well			9 Livestock pe			t sewer lines	X
Was a chemical/bacteriological sample		. How many te	нет		? water we	I Disinfected? Yes X	No
was submitted							
If Yes: Pump Manufacturer's name							
Depth of Pump Intake							
Type of pump: 1 Subm				3 Jet			
6 CONTRACTOR'S OR LANDOWN		FICATION: Th	is water well v	was (1) constructe	ed (2) reconst	ructed or (3) plugged	t under my jurisdiction and w
completed on	ept	month	19	. (<u> varan aara</u>	dov	1980	ye
Completed on	+	ne and helief K	(aneae Water !	Well Contractor's	. uay License No	164	
and this record is true to the best of this Water Well Record was complete	ed on	′ T 11	5	month		1021	year under the busine
name of Houck Bros. D	rilling	Co.		by (signature)			year under the busine
7 LOCATE WELL'S LOCATION F	ROM T	0	LITHOLOG		FROM	ТО	LITHOLOGIC LOG
├ WITH AN "X" IN SECTION () 2	Surf					
I BOX.	2 6		and sand	ly clay			
		80 Clay					
				sand strips	3		
NW NE	l l	1 7	*	o medium sa	1		
1 6 1 : 1 . 1 1				and sandsto			
7 1 9	I		shale				
3W 3E		· I		nd sandstone	e		
<u> </u>							
11 Mile							
ELEVATION: slope							
Depth(s) Groundwater Encountered	1. 165	ft. 2	ft. 3	ft. 4	ft.		d sheet if needed)
INSTRUCTIONS: Use typewriter or bacopies to Kansas Department of Health		-1	irmly and PRIN	T clearly Please	fill in blanks u	nderline or circle the o	correct answers. Send ton thre