

1 LOCATION OF WATER WELL: County Kingman Fraction NE 1/4 NE 1/4 NW 1/4 Section Number 32 Township Number T 27 S Range Number R 5 E/W

Distance and direction from nearest town or city street address of well if located within city?
12 1/2 Miles East Of Kingman, Kns. On Old 54 Hiway.

2 WATER WELL OWNER: MARK SANNY
 RR#, St. Address, Box #: 432 Arbor Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: Mulvane, Kans. 67110 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 4 DEPTH OF COMPLETED WELL: 66' ft. ELEVATION: 12' ft.
 Depth(s) Groundwater Encountered: 1. 12' ft. 2. NA ft. 3. NA ft.
 WELL'S STATIC WATER LEVEL: 10' ft. below land surface measured on mo/day/yr June 12-95
 Pump test data: Well water was NA ft. after NA hours pumping NA gpm
 Est. Yield: 25 gpm. Well water was NA ft. after NA hours pumping NA gpm
 Bore Hole Diameter: 7 7/8" in. to 66' ft., and NA in. to NA ft.
 WELL WATER TO BE USED AS:
 X1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes NA No X; If yes, mo/day/yr sample was submitted NA
 Water Well Disinfected? Yes X No NA

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped NA
 XX 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded NA
 7 Fiberglass Threaded NA
 Blank casing diameter: 5" in. to 54 ft., Dia. 160 in. to NA ft., Dia. NA in. to NA ft.
 Casing height above land surface: 12" in., weight 160 lbs./ft. Wall thickness or gauge No. Sdr26
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass XX 7 PVC 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) NA
 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped XX 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify) NA
 SCREEN-PERFORATED INTERVALS: From 66' ft. to 54' ft., From NA ft. to NA ft.
 GRAVEL PACK INTERVALS: From 66' ft. to 50' ft., From NA ft. to NA ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout XX 3 Bentonite 4 Other NA
 Grout Intervals: From 50' ft. to 42' ft., From 23' ft. to 3' ft., From NA ft. to NA ft.
 What is the nearest source of possible contamination:
 XX 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) NA
 13 Insecticide storage
 Direction from well? South east How many feet? APP 180'

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0'	4'	Sandy top soil			
4'	14'	Red Clay.			
14'	15'	Fine gravel.			
15'	20'	Brown Clay.			
20'	26'	Sandy Clay.			
26'	36'	Course Sand.			
36'	45'	F.Sand W/clay strips.			
45'	50'	Clay.			
50'	64'	Course sand & Fine Gravel.			
64'	66'	Red Bed.			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) June 12, 1995 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 112 This Water Well Record was completed on (mo/day/yr) June 29, 1995 under the business name of WELLS DRILLING CO by (signature) Dal Wells

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.