Water Well Record Form WWC-5 KSA 82a-1212									
1 LOCA	TION OF WA	TER WELL:	FRACTION			Section Number	Township Number	Range Number	
	Kingn	nan	NE 1/4	NE 1/4 SI	<u> </u>	29	T 27 s	R 5W EW	
Distance	and direction	frem nearest town or cit	y street address of well if local	ted within city?				1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	
1/2 N. of Hwy 54 on Cheney Resv. Rd. 1 m W., 1/s m. N., W. side Cheney, KS WATER WELL OWNER: HILGENTSERE, Bob									
RR#, ST. ADRESS, BOX #: 2801 Larkin Board of Agriculture, Divivsion of Water Resource									
CITY, STATE, ZIP CODE: Wichita, Kansas						4-44			
							Application Numb	er:	
	I E WELL'S L	OCATION WITH N BOX:	DEPTH OF COM		70		VATION:		
	· · · · · · · · · · · · · · · · · · ·	N .	Depth(s) groundwa		1	ft.	2 ft.	3 ft.	
			WELL'S STATIC WA			BELOW LAND SUR	FACE MEASURED ON mo/day/yr	12/16/1996	
	NW	NE	Pump test	data: Well wa	ter was	ft. a	fter hours pun	nping gpm	
٠	l ;		Est. Yield	gpm: Well wa	iter was	ft. a	fter hours pun	nping gpm	
M M	i	- - E	Bore Hole Diameter	12 in. t	o 70	ft.	and in.	to ft.	
-		1	WELL WATER TO B	E USED AS: 5	Public water	supply 8	Air conditioning 11	Injection well	
١,	sw		1 Domestic	3 Feedlot 6	Oil field wat	er supply 9	Dewatering 12	Other (Specify below)	
			2 Irrigation	4 Industrial 7	Lawn and ga	rden only 10	Monitoring well		
	₩as a chemical/bacteriological sample submitted to Department? Yes No 🗶 ; If yes, mo/day/yr sample was								
		S	submitted			Wate	r Well Disinfected? Yes	X No	
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped									
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (Specify below) Welded									
2 PVC 4 ABS 7 Fiberglass SDR-26 Threaded									
Blank casing Diameter 5 in. to 35 ft., Dia in. to ft., Dia in. to ft.									
Casing height above land surface 12 in., weight 2.35 lbs./ft. Wall thickness or gauge No									
			TION MATERIAL:	weight 23 •		PVC	10 Asbestos-cem		
1 Stee	el	3 Stainless Steel		5 Fiberglass		RMP (SR)	11 other (specif	v)	
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)									
22 Note used (open note)									
Scauzed Wilapped									
1 Continous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes									
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)									
SCREEN-PERFORATION INTERVALS: from 35 ft. to 70 ft., From ft. to ft.									
			from	ft. t	0	ft., From	ft. to	ft.	
GRAVEL PACK INTERVALS: from 24					to 70	ft., From	ft. to	ft.	
<u></u>			from	ft. 1	0	ft., From	ft. to	R.	
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other									
Grout Intervals: From 4 ft. to 24 ft. From ft. to ft. From ft. to ft.									
What is the nearest source of possible contamination:						10 Livestock pens 14 Abandon water well			
1 Septic tank 4 Lateral lines				7 Pit privy	Pit privy 11 Fuel storage		rage 15	Oil well/Gas well	
2 Sewer lines 5 Cess pool				8 Sewage lagoor	8 Sewage lagoon 12 Fertilizer st			Other (specify below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage									
Direction from well? Southeast How many feet? 200									
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS									
0	2	topsoil							
2	20	clay			1.44				
20	45		o coarse sa	and					
45	70	red shal					.,		
					***************************************			A	
									
							Address of the Addres		
							W. L. J. W. L. J. W. L. L. W.		
						 			
			7-7-7-7-4-40-40-70-7-4						
									
						LL			
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and									
was completed on (mo/day/year)									
Well C	ontractor	's License No	236	This Water Well Red	ord was co	mpleted on (mo	/day/yr)12/1	7./96	
Under the business name of HarpWell&PumpServiceInc by (signature)									
Todd S. Harp									