

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: KINGMAN	NE 1/4 NE 1/4 SE 1/4	4	T 27 S	R 5 W E(W)

Distance and direction from nearest town or city street address of well if located within city?

2 WATER WELL OWNER: City of Garden Plain	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: ATTENTION: VIRGINIA THIMESCH, CITY CLERK	Application Number:
City, State, ZIP Code: Garden Plain, KS.	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 55 ft. ELEVATION:
	Depth(s) Groundwater Encountered: 1. 17 ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL: 17 ft. below land surface measured on mo/day/yr 6-14-88
	Pump test data: Well water was ft. after hours pumping gpm
	Est. Yield gpm: Well water was ft. after hours pumping gpm
	Bore Hole Diameter: 4 1/2 in. to ft. and in. to ft.
WELL WATER TO BE USED AS:	
5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Test Well #1-88	
Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted	
Water Well Disinfected? Yes No X	

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC Sch 40	4 ABS	7 Fiberglass	Welded Metal
Blank casing diameter: 2 in. to 45 ft. Dia			Threaded Screws
Casing height above land surface: 24 in., weight 716 lbs./ft. Wall thickness or gauge No. 154			
TYPE OF SCREEN OR PERFORATION MATERIAL:			
1 Steel	3 Stainless steel	5 Fiberglass	7 PVC
2 Brass	4 Galvanized steel	6 Concrete tile	8 RMP (SR)
			9 ABS
SCREEN OR PERFORATION OPENINGS ARE:			
1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes
		7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS: From 45 ft. to 55 ft., From ft. to ft., From ft. to ft.			
GRAVEL PACK INTERVALS: From 30 ft. to 55 ft., From ft. to ft., From ft. to ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 0 ft. to 30 ft., From ft. to ft., From ft. to ft.				
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	None apparent
Direction from well?			How many feet?	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Topsoil			
2	4	Sandy Tan clay			
4	6	Very Fine to Fine Sand			
6	22	Very Fine to Coarse Sand			
		Some Fine Gravel			
22	24	Tan Clay			
24	35	Very Fine to Fine Sand			
35	45	Gray & Tan Clay			
45	55	Very Fine to Fine Sand with white Clay Stringers			
55	60	Red Shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-14-88 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 1-30-89 under the business name of Harp Well & Pump Service, Inc. by (signature) <i>Mary Arnold</i>	
---	--