

1 LOCATION OF WATER WELL: County: Kingman	Fraction NW 1/4 NW 1/4 SE 1/4	Section Number 6	Township Number T 27 S	Range Number R 5W E/W
---	---	----------------------------	----------------------------------	---------------------------------

Distance and direction from nearest town or city street address of well if located within city?
3 E of Mt. Vernon, Kansas

2 WATER WELL OWNER: Delos Smith RR#, St. Address, Box # : Route 2 City, State, ZIP Code : Kingman, Ks. 67068	Red Tiger 1720 Ks. St. Bank Bldg Wichita, Kansas 67202 Application Number: T82-372
---	---

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 80 ft.	ELEVATION: Unknown ft.	
	Depth(s) Groundwater Encountered 1. 25 ft. 2. ft. 3. ft.		
	WELL'S STATIC WATER LEVEL 25 ft. below land surface measured on mo/day/yr 7/7/82		
	Pump test data: Well water was ft. after hours pumping gpm		
	Est. Yield : 60 gpm: Well water was ft. after hours pumping gpm		
Bore Hole Diameter 8 in. to 80 ft., and in. to ft.			
WELL WATER TO BE USED AS:			
5 Public water supply		8 Air conditioning	
11 Injection well		12 Other (Specify below)	
1 Domestic		3 Feedlot	
6 Oil field water supply		9 Dewatering	
2 Irrigation		4 Industrial	
7 Lawn and garden only		10 Observation well	
Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted			
Water Well Disinfected? Yes No			

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: <u>Glued</u> Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 <u>PVC</u>	4 ABS	7 Fiberglass	Welded
Blank casing diameter 5 in. to 60 ft., Dia in. to ft., Dia in. to ft.	Casing height above land surface 12 in., weight 2.8 lbs./ft. Wall thickness or gauge No. Sch. 40		
TYPE OF SCREEN OR PERFORATION MATERIAL:			
1 Steel	3 Stainless steel	5 Fiberglass	7 <u>PVC</u>
2 Brass	4 Galvanized steel	6 Concrete tile	8 RMP (SR)
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped	8 <u>Saw cut</u>
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS: From 60 ft. to 80 ft., From ft. to ft.		From ft. to ft., From ft. to ft.	
GRAVEL PACK INTERVALS: From 10 ft. to 80 ft., From ft. to ft.		From ft. to ft., From ft. to ft.	

6 GROUT MATERIAL:	1 <u>Neat cement</u>	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 0 ft. to 10 ft., From ft. to ft., From ft. to ft.	What is the nearest source of possible contamination:			
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 <u>Oil well/Gas well</u>
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
Direction from well? South			How many feet? 60	

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	25	Clay			
25	80	Sand and Gravel			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7/7/82 and this record is true to the best of my knowledge and belief. Kansas	Water Well Contractor's License No. 186 This Water Well Record was completed on (mo/day/yr) 8/30/82
under the business name of Kellys Water Well Service by (signature) <i>Deoye Road</i>	

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY
T
27
R
5
EW
SEC: 6