Form WWC-5 WATER WELL RECORD KSA 82a-1212 1 LOCATION OF WATER WELL: SECTION NUMBER TOWNSHIP NUMBER **RANGE NUMBER** FRACTION 27 5W SE NE 1/4 NE 11 Т E/W 1/4 1/4 S R Kingman Distance and direction from nearest town or city street address of well if located within city? 15903 N.E. Countryside Cheney, Kansas LIFESTYLE HOMES WATER WELL OWNER: Board of Agriculture, Division of Water Resource 1354 S. Ridge Road RR#,ST. ADDRESS,BOX #: Wichita, Kansas CITY, STATE: ZIP CODE Application Number: 80 ELEVATION: 4 DEPTH OF COMPLETED WELL: LOCATE WELL'S LOCATION ft. WITH AN "X" IN SECTION BOX: Depth of groundwater Encountered: ft. ft. ft. N 20 WELL'S STATIC WATER LEVEL FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 7/24/12 NE Z Pump test data: Well water was ft. after hours of pumping @ gpm ft. after Est. Yield: Well water was hours of pumping @ gpm gpm to 80 ≌ 12 Bore Hole Diameter and ft. WELL WATER TO BE USED AS: 11. Injection well 5. Public water supply 7. Lawn and garden only SE SW 3. Feedlot 1. Domestic 12. Other (Specify below) 6. Oil field water supply 8. Air conditioning 10. Monitoring well 2. Irrigation 4. Industrial ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO) s (YES) submitted Was Water Well Disinfected? 5 TYPE OF CASING USED: CASING JOINTS: Glued 9. Other (Specify below) Threaded 5. Wrought Iron 7. Fiberglass 1. Steel 3. RPM (SR) Welded Clamped SDR-26 8. Concrete tile Asbestos-Cement 2. PVC 4 ABS 5 31 Dia. ft., Dia. Blank casing diameter to in. to ft. 12 2.35 Casing height above land surface: in Weight: lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 11. Other (specify) 9. ABS 1. Steel 3. Stainless Steel 5. Fiberglass 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole) 2 Brass 4. Galvanized SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 8. Saw cut 10. Other (specify) 2. Louvered shutter 4. Key punched 6. Wire wrapped SCREEN - PERFORATION INTERVAL 31 80 ft. to ft., From From ft. ft. to ft. From to ft., From ft. ft. to 24 **GRAVEL PACK INTERVALS:** ft. to 80 From ft., From ft. ft. ft. to From ft., From ft to ft. **GROUT MATERIALS:** Other bentonite hole plug 1. Neat cement 2. Cement Grout 3. Bentonite Grout Intervals: From 24 ft . From ft. From to tο ft.. ft. What is the nearest source of possible contamination: 10. Livestock pens 15. Oil well/Gas well 7. Pit privy 13. Insecticide storage 4. Lateral lines 1. Septic tank 16. Other (specify below) 11. Fuel storage 8. Sewage lagoon 14. Abandon water well 2. Sewer lines 5. Cess Pool None Yet 9. Feed yard 12. Fertilizer storage 6. Seepage pit 3. Watertight sewer line How many feet? Direction from well? LITHOLOGIC LOG From LITHOLOGIC LOG From Τо Τо A topsoil 3 10 clay 10 20 fine sand 20 35 medium sand 35 80 grey shale under my jurisdiction and Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged 7/24/2012 and this record is true to the best of my knowledge and belief. was completed on (mo/day/year) This water well record was completed on (mo/day/year) 8/3/2012 Kansas Water Well Contractor's License No. 236 Todd S. Harb by (signature) under the business name of Harp Well and Pump Service