KOLAR Document ID: 1569412

		Correction		WWC-5 ge in Well Use			ision of Wat urces App. 1			Well ID		
Original Record Correction Chang LOCATION OF WATER WELL:							ion Number Township Numl			ge Number		
County:				1/4 1/4	1⁄4	1⁄4			T S	R	□ E □ W	
Business: di						treet or Rural Address where well is located (if unknown, distance and rection from nearest town or intersection): If at owner's address, check here:						
Address: Address:												
City:			State:	ZIP:								
3 LOCAT	•	ft.	5 Latit	nqe.			(decimal degrees)					
WITH " SECTIO	·X″ IN DN BOX:	Depth(s) Gr	Pepth(s) Groundwater Encountered: 1)				ft. 5 Latitude:(decimal degrees) Longitude:(decimal degrees)					
	N DOA.		2) ft. 3) ft., or 4) Dry					Datum: WGS 84 NAD 83 NAD 27				
			WELL'S STATIC WATER LEVEL:					Source for Latitude/Longitude:				
NW	NE		□ above land surface, measured on (mo day yr)						WAAS enabled?			
		Pump test data: Well water was ft.					□ Land Survey □ Topographic Map					
W	E	after	after hours pumping gp Well water was ft.					Online Mapper:				
X - sw	SE	after		hours pumping gpm								
		Estimated Y	Estimated Yield:gpm				6 Elevation:ft. Ground Level TOC					
	S	Bore Hole I	Bore Hole Diameter: in. to f				Source: Land Survey GPS Topographic Map Other					
Imile1 mile Imile Imile 7 WELL WATER TO BE USED AS: □ Other □ Other												
1. Domestic: 5. Dublic Water Supply: well ID 10. Oil Field Water Supply: lease												
House	6. 🗆	6. Dewatering: how many wells?				11. Test Hole: well ID						
\Box Lawn			7. Aquifer Recharge: well ID				\Box Cased \Box Uncased \Box Geotechnical					
					D liation: well ID			12. Geothermal: how many bores? a) Closed Loop □ Horizontal □ Vertical				
3. ☐ Feedlot					Soil Vapor Extraction			b) Open Loop 🗌 Surface Discharge 📋 Inj. of Water				
4. Industrial Recovery Injection 13. Other (specify):												
Was a chemical/bacteriological sample submitted to KDHE? \Box Yes \Box No If yes, date sample was submitted:												
Water well disinfected? Yes No 8 TYPE OF CASING USED: Steel PVC Other CASING JOINTS: Glued Clamped Welded Threaded												
Casing diameter in. to ft., Diameter in. to ft., Diameter in. to ft.												
Casing height above land surface in. Weight lbs./ft. Wall thickness or gauge No												
TYPE OF SCREEN OR PERFORATION MATERIAL:												
Steel Steinless Steel PVC Other (Specify) Brass Galvanized Steel None used (open hole)												
SCREEN OR PERFORATION OPENINGS ARE:												
	nuous Slot	☐ Mill Slot					rilled Holes		Other (Specify)			
□ Louvered Shutter □ Key Punched □ Wire Wrapped □ Saw Cut □ None (Open Hole)												
SCREEN-PERFORATED INTERVALS: From												
9 GROUT MATERIAL: Neat cement Cement grout Bentonite Other												
Grout Intervals: From ft. to ft., From ft. to ft., From ft. to ft.												
Nearest sou		le contaminati	on: No Lateral Line	o potential source of c es			hin 200 ft. Livestock Po	ane		ide Storage		
			Cess Pool	\square Sewage			Fuel Storage					
	ight Sewer Li			☐ Feedyard	1		Fertilizer St	orage	🗌 Oil Wel	ll/Gas Well		
Direction from well? ft.												
10 FROM	TO		ITHOLO			ROM	ТО		HO. LOG (cont.) or	PLUGGIN	G INTERVALS	
					.	oto~-						
						otes:						
11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo-day-year) and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No												
under my J Kansas Wa	urisdiction a iter Well Cou	nd was compl ntractor's Lice	eted on (n ense No	no-day-year) This V	 Nater V	and Vell Rec	unis record	18 tru mple	ted on (mo-day-ve	y knowledger)	ge and belief.	
	ousiness nam	e of										
Send one copy to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. KS Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-3565.												
		eks.gov/waterwel		. mer, Geology Beelloll,	1000 D W	, succesoff	5, 5une 1 20	, 10pc			SA 82a-1212	