

1 LOCATION OF WATER WELL: County: Kingman	Fraction SW 1/4 NW 1/4 NW 1/4	Section Number 29	Township Number T 27 S	Range Number R 7 E/W
--	----------------------------------	----------------------	---------------------------	-------------------------

Distance and direction from nearest town or city street address of well if located within city?
1 mile north, 1/2 mile west, 1/4 mile south of Kingman, Kans

2 WATER WELL OWNER: Joe White
RR#, St. Address, Box #: RT#1--Kingman, Kans. 67068
City, State, ZIP Code:

Board of Agriculture, Division of Water Resources
Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL: 33' ft. ELEVATION: 6' ft.

Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL: 5' ft. below land surface measured on mo/day/yr July 27 - 95

Pump test data: Well water was NA ft. after hours pumping gpm

Est. Yield: 25 gpm; Well water was ft. after hours pumping gpm

Bore Hole Diameter: 7 7/8" in. to 33' ft., and in. to ft.

WELL WATER TO BE USED AS:

5 Public water supply	8 Air conditioning	11 Injection well
1 Domestic	3 Feedlot	6 Oil field water supply
2 Irrigation	4 Industrial	9 Dewatering
	XX Lawn and garden only	12 Other (Specify below)
	10 Monitoring well	

Was a chemical/bacteriological sample submitted to Department? Yes No XX; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes XX No

5 TYPE OF BLANK CASING USED:

1 Steel	3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued XX Clamped
X2 PVC	4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded
		7 Fiberglass		Threaded

Blank casing diameter: 5" in. to 20' ft., Dia in. to ft., Dia in. to ft.

Casing height above land surface: 14" in., weight 160 lbs./ft. Wall thickness or gauge No. SDR26

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)	10 Asbestos-cement
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS	11 Other (specify)
				12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot	3 Mill slot	5 Gauzed wrapped	XX8 Saw cut	11 None (open hole)
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	
		7 Torch cut	10 Other (specify)	

SCREEN-PERFORATED INTERVALS: From 33' ft. to 20' ft., From ft. to ft.

GRAVEL PACK INTERVALS: From ft. to ft., From ft. to ft.

6 GROUT MATERIAL:

1 Neat cement	2 Cement grout	XX8 Bentonite	4 Other
---------------	----------------	---------------	---------

Grout Intervals: From 20' ft. to 2' ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination:

XX 1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	

Direction from well? South How many feet? 135'

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0'	4'	Sandy top soil.			
4'	12'	Fine sand.			
12'	14'	Clay.			
14'	17'	Medium course sand.			
17'	18'	Clay.			
18'	20'	Fine sand.			
20'	25'	Course sand.			
25'	30'	Course sand.			
30'	33'	Red Bed.			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) July 27 - 1995 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 112 This Water Well Record was completed on (mo/day/yr) Aug 26 - 1995 under the business name of Wells Drilling Co. by (signature) Dal Wells