			WATE	R WELL RECORD	Form WWC-5	5 KSA 82	a-1212	
1 LOCATI	ON OF WAT	ER WELL:	Fraction			ction Number	Township Numbe	r Range Number
	Kingman		NE 1/4			4	т 27	s R 7 XXW
Distance a			-	address of well if locate	•			
				of Kingman, kn	s.			
2 WATE	R WELL OW		an L. Rice					
RR#, St.	Address, Box		2 - Box61				Board of Agricu	Ilture, Division of Water Resources
	, ZIP Code		gman Kans.			<u>.</u>	Application Nun	
LOCAT	E WELL'S LO	CATION WITH	4 DEPTH OF C	OMPLETED WELL	52.'	ft. ELEVA	ATION:	. ft. 3
- AN X	IN SECTION	BOX:	Depth(s) Ground	water Encountered 1	18	ft.	2	. ft. 3
7	` ! T	ı	WELL'S STATIC	WATER LEVEL $.17$	" ft. t	elow land su	rface measured on mo/o	day/yr Aug. 24-93
1 1	- NW	NE	Pum	p test data: Well wate	erwas	ft. <i>&amp;</i>	after hou	urs pumping gpm
	1444 1	, , ,						urs pumping gpm
<u>.</u> L	i		Bore Hole Diam	eterin. to			and	in. to
* w -	1	1 "	WELL WATER	TO BE USED AS:	5 Public water	er supply	8 Air conditioning	11 Injection well
7	, l	!	Domestic	3 Feedlot	6 Oil field wa	iter supply	9 Dewatering	12 Other (Specify below)
i 1	2M	st x	2 Irrigation					
1 1	- i - l		Was a chemical/					If yes, mo/day/yr sample was sub
	S		mitted				ater Well Disinfected? Y	
5 TYPE (	OF BLANK C	ASING USED:		5 Wrought iron	8 Concr	ete tile	CASING JOINTS:	: Gluedxx Clamped
1 St	eel	3 RMP (S	R)	6 Asbestos-Cement		(specify belo	w)	Welded
XX P		4 ABS		7 Fiberglass				Threaded
Blank casi	ng diameter		.in. to	ft., Dia	in. to		ft., Dia	in. to ft.
Casing he	ight above la	nd surface1;	5 <b>''</b>	in., weight	1,60	lbs.	/ft. Wall thickness or ga	uge No. SDR26
		R PERFORATIO			7 PV		10 Asbestos	-
1 St	eel	3 Stainless	s steel	5 Fiberglass	8 RM	MP (SR)		pecify)
2 Br	ass	4 Galvaniz	ed steel	6 Concrete tile	9 AB	` '	XX12 None us	• • • • • • • • • • • • • • • • • • • •
SCREEN	OR PERFOR	ATION OPENIN	IGS ARE:	5 Gauz	ed wrapped		8 Saw cut	XX11 None (open hole)
1 Cc	ontinuous slot	: 3 M	lill slot	6 Wire wrapped			9 Drilled holes	
2 Lo	uvered shutte	er 4 K	ey punched	7 Torch				
SCREEN-	PERFORATE	D INTERVALS:				ft Fro	om	. ft. toft.
								. ft. toft.
(	GRAVEL PAC	CK INTERVALS:						. ft. toft.
				ne ft. to		ft., Fro		
6 GROUT	MATERIAL:	1 Neat	cement	2 Cement grout				
Grout Inte	rvals: From	1.22!	.ft. to 3 ! .	ft., From	ft.	to	ft., From	ft. to
What is th	e nearest so	urce of possible	contamination:			10 Lives	stock pens	14 Abandoned water well
XX 1 Septic tank 4 Lateral lin			al lines	7 Pit privy		11 Fuel	storage	15 Oil well/Gas well
2 Sewer lines 5 Cess poor				8 Sewage lagoon		12 Fertilizer storage 16 Other (specify below)		16 Other (specify below)
3 W	atertight sewe	er lines 6 Seep	age pit	9 Feedyard		13 Insecticide storage		
Direction f	rom well?	East			_	How ma	any feet? App.	1200'
FROM	TO		LITHOLOGIC	LOG	FROM	то	PLUGG	ING INTERVALS
0'	16'		L & Sandy C	lay.				
16'	18'	Brown c	lay.					
<u> 18'</u>	21'		Course sand					
21'	42'	Red Bed						
42'	44.	Broken I						
44.	52'	Red Bed.	•					
7 CONT	PACTOP'S O	B I ANDOWNE	R'S CERTIEICAT	ION: This water well w	ae (1) conetru	oted (2) reco	onetruoted or (2) physics	ed under my jurisdiction and was
Completed	on (mo/day/	(Dar)	Aug 24 -93	ioia. Tilis water well w	as (1) constru	and this rose	ord is true to the best of	my knowledge and belief. Kansas
		Jear)		This Water W				t.16,-93
			ls Drilling		reli necora wa	•	7177 / 31	4
	business nan				m	by (signa		LCCU.
							e the correct answers. Send to WNER and retain one for your	p three copies to Kansas Department records.