WATER WELL RECORD ☐ Original Record ☐ Correction ☐ Change in Well Use							Division of Water Resources App. No. 12185 Well ID						
1 LOCATION OF WATER WELL: Fraction						Section Number Township Number Range Number					ige Number		
County: Kingman SE ¼ SW ¼ NW ¼ SW ¼ 26 T 27 S R 8 DE											B □ E 🛛 W		
Business: Theodore C Geisert Rev. Trust Address: P.O. Box 475 Address: City: Kingman State: KS Address: First: Street or Rural Address where well is located (if unknown, distance and direction from nearest town or intersection): If at owner's address, check here: Approximately 2 miles north and 3 miles west of Kingman. Address: Address: City: Kingman State: KS ZIP: 67068													
3 LOCATI	EWELL	4 DEPTH	OF COM	PI ETED	WEII.	54 f	5 1 54	4	37 664259		(1 : 1 1 ×)		
SECTION BOX: Depth(s) Groundwater Encountered: 1) ft. 2) ft. 3) ft., or 4) Dry Well WELL'S STATIC WATER LEVEL: 10.70 ft. Well water was not checked ft. after hours pumping gpm Well water was ft. after hours pumping gpm							Long Hori Sour Of Elev	5 Latitude: 37.664258					
S Bore Hole			e Diameter: 24 in. to 54 ft. in. to ft.				Sour	Source: Land Survey GPS Topographic Ma					
· · ·	ATER TO BE	USED AS:		III.		11.							
1. Domestic House	hold & Garden ock ion	5. [6. [7. [8. [9. E	Public Wat Dewatering Aquifer Re Monitoring Tryironmenta Air Sparge Recovery	g: how man charge: we g: well ID l Remediat	ny wells?		11. Tes 12. Geo a) (b) (st Hole Cased otherm Closed Open L	eld Water Supply: le : well ID Uncased al: how many bores Loop Surface Di specify):	Geotechnica s? tal Vert	ical Inj. of Water		
4. Industrial Recovery Injection 13. Other (specify): Was a chemical/bacteriological sample submitted to KDHE? Yes No If yes, date sample was submitted:													
Water well disinfected? Yes No													
8 TYPE OF CASING USED: Steel PVC CASING JOINTS: Glued Clamped Welded Threaded Other Casing diameter 16 in. to 37 ft., Diameter in. to ft., Diameter in. to ft. Casing height above land surface 12 in. Weight 19.75 lbs./ft. Wall thickness or gauge No													
SCREEN OR PERFORATION OPENINGS ARE: Continuous Slot Mill Slot Gauze Wrapped Torch Cut Drilled Holes Other (Specify) Louvered Shutter Key Punched Screen-Perforated Intervals: From 37 ft. to 53 ft., From ft. to ft. GRAVEL PACK INTERVALS: From 22 ft. to 54 ft., From ft. to ft.													
9 GROUT MATERIAL: Neat cement Cement grout Bentonite Other													
Grout Intervals: From 2 ft. to 22 ft., From ft. to ft., From ft. to ft. Nearest source of possible contamination: Septic Tank Lateral Lines Pit Privy Livestock Pens Insecticide Storage Sewer Lines Sewage Lagoon Fuel Storage Abandoned Water Well Watertight Sewer Lines Seepage Pit Feedyard Fertilizer Storage Oil Well/Gas Well Other (Specify) Direction from well? East Distance from well? 12 ft.													
10 FROM	ТО		LITHOLOG	·· -		FROM	TO		HO. LOG (cont.) or	PLUGGIN	G INTERVALS		
	4	Topsoil											
	32	Clay, brown						-					
		Sand & gravel, fine to medium Clay, brown						-					
		Sand & gravel, fine to medium											
	54	Shale, red											
Notes: 11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ constructed, ☐ reconstructed, or ☐ plugged													
under my jurisdiction and was completed on (mo-day-year) 08/17/17 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 185 This Water Well Record was completed on (mo-day-year) 08/18/17 under the business name of Clarke Well & Equipment, Inc.													
Mail I white copy along with a fee of \$5.00 for each constructed well to: Kansas Department of Health and Environment, Bureau of Water, GWTS Section,													
			1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Mail one to Water Well Owner and retain one for your records. Telephone 785-296-5524. Visit us at http://www.kdheks.izov/waterwell/index.html KSA 82a-1212 Revised 7/10/2015										