


USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

T R EW sec 1/4 1/4 1/4 No.

Kansas State Dept. Of Health
(Water Well Contractors)
Forbes-Bldg. 740
Topeka, Kansas 66620

1 Location of well:	County Kingman	Township name	Fraction SW 1/4	Section number 15	Town number 27 S	Range number 9 W		
Distance and direction from nearest town or city: 4 mi North & 1 West of Calista			3 Owner of well: Bruce & Sam Livingston Address: Kingman, Kansas					
Locate with "X" in section below: 			Sketch map:			4 Well depth: 195 ft. Date of completion 5/24/75 Well diameter 30 in.		
2 Type and color of material			From	To	5 <input type="checkbox"/> Cable tool <input type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input checked="" type="checkbox"/> Reverse rotary			
			Top soil		0	3	6 Use: <input type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input checked="" type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Commercial <input type="checkbox"/> Test well <input type="checkbox"/>	
			Med. to coarse sand & gravel w/clay		3	31	7 Casing: Material Stl Height: above/below Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface 12 in. Diam. 16 in. to 127 ft. depth Drive shoe? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No in. to in. ft. depth	
			Clay		31	45	8 Screen: Manufacturer Doerr Type Stl Dia. 16" Slot/gauze 1/8" Length 68' Set between 127 ft. and 195 ft. Fittings: Gravel pack <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No Size range of material 1/8" x 3/8"	
			Med. to coarse sand & gravel		45	107	9 Static water level: 49.7 ft. below land surface Date 3/21/75	
			Clay		107	122	10 Pumping level below land surfaces: No Test ft. after hrs. pumping g.p.m. ft. after hrs. pumping g.p.m. Estimated maximum yield g.p.m.	
			Fine to coarse sand & gravel		122	194	11 Water sample submitted: <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Date	
			Red shale		194	197	12 Well head completion: <input type="checkbox"/> Pitless adapter <input checked="" type="checkbox"/> 12 Inches above grade	
							13 Well grouted? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input checked="" type="checkbox"/> clay Depth: From 0 ft. to 10 ft.	
							14 Nearest source of possible contamination: Farmland ft. Direction Type Well disinfected upon completion? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	
				15 Pump: <input type="checkbox"/> Not installed Manufacturer's name Layne Model number 770871 HP 60 Volts 460 Length of drop pipe 100 ft. capacity 200 g.p.m. Type: <input type="checkbox"/> Submersible <input checked="" type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other				
16 Remarks: elevation Topography: <input type="checkbox"/> Hill <input type="checkbox"/> Slope <input checked="" type="checkbox"/> Upland <input type="checkbox"/> Valley			17 Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Layne Western Co., Inc. 102 Business name License No. Address Wichita, Kansas Signed [Signature] Date 5/27/75					