

1 LOCATION OF WATER WELL: Fraction NE 1/4 NE 1/4 SW 1/4 Section Number 17 Township Number T 27 S Range Number R 9 EW

Distance and direction from nearest town or city street address of well if located within city?
 1 West & 2 South of Penalosa on East Side

2 WATER WELL OWNER: Stanley Hansen
 RR#, St. Address, Box #: Rt. 1 Box 20 Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: Penalosa, KS 67121 Application Number: 29687

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL: 136 ft. ELEVATION: ...

Depth(s) Groundwater Encountered 1. 54 ft. 2. ... ft. 3. ... ft.

WELL'S STATIC WATER LEVEL 54 ft. below land surface measured on mo/day/yr 3-21-92

Pump test data: Well water was N/A ft. after ... hours pumping ... gpm

Est. Yield ... gpm: Well water was ... ft. after ... hours pumping ... gpm

Bore Hole Diameter 28 in. to 136 ft., and ... in. to ... ft.

WELL WATER TO BE USED AS:

5 Public water supply	8 Air conditioning	11 Injection well
1 Domestic	3 Feedlot	6 Oil field water supply
2 Irrigation	4 Industrial	7 Lawn and garden only
		10 Monitoring well
		9 Dewatering
		12 Other (Specify below)

Was a chemical/bacteriological sample submitted to Department? Yes ... No ; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes ... No

5 TYPE OF BLANK CASING USED:

1 Steel	3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <input checked="" type="checkbox"/> Clamped ...
2 PVC	4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded ...
		7 Fiberglass		Threaded ...

Blank casing diameter 16 in. to 96 ft., Dia. ... in. to ... ft., Dia. ... in. to ... ft.

Casing height above land surface 12 in., weight Sch 40 lbs./ft. Wall thickness or gauge No. ...

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)	10 Asbestos-cement
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS	11 Other (specify) ...
				12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	
		7 Torch cut	10 Other (specify) ...	

SCREEN-PERFORATED INTERVALS: From 96 ft. to 136 ft., From ... ft. to ... ft.

GRAVEL PACK INTERVALS: From 20 ft. to 136 ft., From ... ft. to ... ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other ...

Grout Intervals: From 0 ft. to 20 ft., From ... ft. to ... ft., From ... ft. to ... ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	N/A

Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	Top Soil			
3	26	Fine Med Sand			
26	38	White Tight Clay			
38	44	Brown Clay			
44	48	Very Fine Sand			
48	54	Coarse Gravel W/ 10% Clay			
54	58	Med Sand W/ 20% Clay			
58	76	Coarse Gravel			
76	86	Fine Sand			
86	94	Med Sand			
94	111	Fine Med Sand			
111	136	Fine Med Sand W/ Shale Chips			
136		Red Bed			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-21-92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 537 This Water Well Record was completed on (mo/day/yr) 3-21-92 under the business name of Flowers Drilling & Pump Service by (signature) Mike Flowers