

MILL #1

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>SEDGWICK</u>		<u>NE 1/4 SW 1/4 NE 1/4</u>	<u>1</u>	<u>T 28 S</u>	<u>R 1 E</u>
Distance and direction from nearest town or city street address of well if located within city? <u>2600 S. CUSTER WICHITA, KANSAS</u>					
2 WATER WELL OWNER: <u>ELECTROTECH/WELCO</u>					
RR#, St. Address, Box # : City, State, ZIP Code : <u>2600 S. CUSTER WICHITA KANSAS 67217</u>					
Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>2'5"</u> ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL <u>13</u> ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter <u>7 1/4</u> in. to <u>2 1/2</u> in. and in. to ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only ☒ Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes..... No..... If yes, mo/day/yr sample was submitted			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped			
1 Steel 3 RMP (SR)		5 Wrought iron 8 Concrete tile Welded			
☒ PVC 4 ABS		6 Asbestos-Cement 9 Other (specify below) Threaded ☒ X			
Blank casing diameter <u>2</u> in. to <u>1 1/2</u> ft. Dia. in. to ft. Dia. in. to ft.					
Casing height above land surface <u>0</u> in., weight <u>SCHED 40</u> lbs./ft. Wall thickness or gauge No.					
TYPE OF SCREEN OR PERFORATION MATERIAL:		☒ PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot ☒ Mill slot 6 Wire wrapped 9 Drilled holes					
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From <u>2 1/2</u> ft. to <u>1 1/2</u> ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From <u>2 1/2</u> ft. to <u>1 1/2</u> ft. From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement ☒ Cement grout ☒ Bentonite 4 Other					
Grout Intervals: From <u>1 1/2</u> ft. to <u>6</u> ft. From <u>1 1/2</u> ft. to <u>1 1/2</u> ft. From ft. to ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)					
☒ Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage					
Direction from well? <u>WEST</u>		How many feet? <u>27'</u>			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	TOPSOIL			
2	5	BROWN PLASTIC CLAY			
5	10	LT BROWN, SILTY SANDY CLAY			
10	15	FINE, TO MED SAND, SATURATED AT 13'			
15	20	FINE TO MED. SAND			
20	25	MED. TO COARSE SAND			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ constructed, ☐ reconstructed, or ☐ plugged under my jurisdiction and was completed on (mo/day/year) <u>8-10-95</u> and this record is true to the best of my knowledge and belief. Kansas					
Water Well Contractor's License No. <u>575</u> This Water Well Record was completed on (mo/day/yr) <u>8-25-95</u>					
under the business name of <u>KURTZ ENVIRONMENTAL SERVICE</u> by (signature) <u>[Signature]</u>					