

1 LOCATION OF WATER WELL: Sedgwick		FRACTION NW 1/4 NW 1/4 NW 1/4		Section Number 22		Township Number T 28 S		Range Number R 1W E/W	
Distance and direction from nearest town or city street address of well if located within city? 7105 W. 47th St. S. Wichita, Kansas									
WATER WELL OWNER: LAUER, Ambrose RR#, ST. ADDRESS, BOX #: 8101 W. McArthur CITY, STATE, ZIP CODE: Wichita, Kansas 67215					Board of Agriculture, Division of Water Resource Application Number:				
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 			4 DEPTH OF COMPLETED WELL 97 ft. ELEVATION:						
			Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 60 FT. BELOW LAND SURFACE MEASURED ON 11/11/1996 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 12 in. to 97 ft. and in. to ft.						
			WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well						
			Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No						
5 TYPE OF CASING USED:									
1 Steel 3 RMP (SR)			5 Wrought iron		8 Concrete tile		CASING JOINTS: Glued X Clamped		
2 PVC 4 ABS			6 Asbestos-Cement		9 Other (Specify below)		Welded		
Blank casing Diameter 5 in. to 70 ft., Dia			7 Fiberglass		SDR-26		Threaded		
Casing height above land surface 12 in., weight 2.35 lbs. / ft.					Wall thickness or gauge No. .214				
TYPE OF SCREEN OR PERFORATION MATERIAL:									
1 Steel 3 Stainless Steel			5 Fiberglass		7 PVC		10 Asbestos-cement		
2 Brass 4 Galvanized steel			6 Concrete tile		8 RMP (SR)		11 other (specify)		
					9 ABS		12 None used (open hole)		
SCREEN OR PERFORATION OPENING ARE:									
1 Continuous slot 3 Mill slot			5 Gauzed wrapped		8 Saw cut		11 None (open hole)		
2 Louvered shutter 4 Key punched			6 Wire wrapped		9 Drilled holes				
			7 Torch cut		10 Other (specify)				
SCREEN-PERFORATION INTERVALS:									
from 70 ft. to 97 ft., From			ft. to			ft.			
from			ft. to			ft.			
GRAVEL PACK INTERVALS:									
from 24 ft. to 97 ft., From			ft. to			ft.			
from			ft. to			ft.			
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug									
Grout Intervals: From 4 ft. to 24 ft. From ft. to ft. From ft. to ft.									
What is the nearest source of possible contamination:									
1 Septic tank 4 Lateral lines			7 Pit privy		10 Livestock pens		14 Abandon water well		
2 Sewer lines 5 Cess pool			8 Sewage lagoon		11 Fuel storage		15 Oil well/Gas well		
3 Watertight sewer lines 6 Seepage pit			9 Feedyard		12 Fertilizer storage		16 Other (specify below)		
					13 Insecticide storage		None Apparent		
Direction from well? How many feet?									
FROM TO		LITHOLOGIC LOG		FROM TO		PLUGGING INTERVALS			
0	4	topsoil							
4	12	clay							
12	45	medium sand							
45	50	clay							
50	80	medium coarse sand							
80	85	clay							
85	92	medium sand							
92	97	shale							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11/11/1996 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 11/12/96 Under the business name of Harp Well & Pump Service, Inc. by (signature) Todd S. Harp									